

Microsoft.AZ-104.v2023-07-17.q255

Exam Code:	AZ-104
Exam Name:	Microsoft Azure Administrator
Certification Provider:	Microsoft
Free Question Number:	255
Version:	v2023-07-17
# of views:	2411
# of Questions views:	2550
https://www.freepdfdumps.com/Microsoft.AZ-104.v2023-07-17.q255.html	

NEW QUESTION: 1

You have an Azure web app named App1 that streams video content to users. App1 is located in the East US Azure region.

Users in North America stream the video content without any interruption.

Users in Asia and Europe report that the video buffer often and do not play back smoothly.

You need to recommend a solution to improve video streaming to the European and Asian users.

What should you recommend?

- A. Scale out the App Service plan.
- B. Scale up the App Service plan.
- C. Configure an Azure Content Delivery Network (CDN) endpoint.
- D. Configure Azure File Sync.

Answer: (SHOW ANSWER)

A content delivery network (CDN) is a distributed network of servers that can efficiently deliver web content to users. CDNs store cached content on edge servers in point-of-presence (POP) locations that are close to end users, to minimize latency.

Azure Content Delivery Network (CDN) offers developers a global solution for rapidly delivering high-bandwidth content to users by caching their content at strategically placed physical nodes across the world.

Reference:

<https://docs.microsoft.com/en-us/azure/cdn/cdn-overview>

NEW QUESTION: 2

You need to recommend an identify solution that meets the technical requirements.

What should you recommend?

- A. federated single-on (SSO) and Active Directory Federation Services (AD FS)
- B. password hash synchronization and single sign-on (SSO)
- C. cloud-only user accounts

D. Pass-through Authentication and single sign-on (SSO)

Answer: A ([LEAVE A REPLY](#))

Active Directory Federation Services is a feature and web service in the Windows Server Operating System that allows sharing of identity information outside a company's network.

Scenario: Technical Requirements include:

Prevent user passwords or hashes of passwords from being stored in Azure.

Topic 4, Contoso Ltd (Consulting Company)

To start the case study

To display the first question in this case study, click the Next button. Use the buttons in the left pane to explore the content of the case study before you answer the questions. Clicking these buttons displays information such as business requirements, existing environment, and problem statements. If the case study has an All Information tab, note that the information displayed is identical to the information displayed on the subsequent tabs. When you are ready to answer a question, click the Question button to return to the question.

Overview

General Overview

Contoso, Ltd. is a consulting company that has a main office in Montreal and branch offices in Seattle and New York.

Environment

Existing Environment

Contoso has an Azure subscription named Sub1 that is linked to an Azure Active Directory (Azure AD) tenant. The network contains an on-premises Active Directory domain that syncs to the Azure AD tenant.

The Azure AD tenant contains the users shown in the following table.

Sub1 contains two resource groups named RG1 and RG2 and the virtual networks shown in the following table.

User1 manages the resources in RG1. User4 manages the resources in RG2.

Sub1 contains virtual machines that run Windows Server 2019 as shown in the following table

No network security groups (NSGs) are associated to the network interfaces or the subnets.

Sub1 contains the storage accounts shown in the following table.

Requirements

Planned Changes

Contoso plans to implement the following changes:

Create a blob container named container1 and a file share named share1 that will use the Cool storage tier.

Create a storage account named storage5 and configure storage replication for the Blob service.

Create an NSG named NSG1 that will have the custom inbound security rules shown in the following table.

Associate NSG1 to the network interface of VM1.

Create an NSG named NSG2 that will have the custom outbound security rules shown in the following table.

Associate NSG2 to VNET1/Subnet2.

Technical Requirements

Contoso must meet the following technical requirements:

Create container1 and share1.

Use the principle of least privilege.

Create an Azure AD security group named Group4.

Back up the Azure file shares and virtual machines by using Azure Backup.

Trigger an alert if VM1 or VM2 has less than 20 GB of free space on volume C.

Enable User1 to create Azure policy definitions and User2 to assign Azure policies to RG1.

Create an internal Basic Azure Load Balancer named LB1 and connect the load balancer to

VNET1/Subnet1 Enable flow logging for IP traffic from VM5 and retain the flow logs for a period of eight months.

Whenever possible, grant Group4 Azure role-based access control (Azure RBAC) read-only permissions to the Azure file shares.

NEW QUESTION: 3

You have an Azure web app named App1 that has two deployment slots named Production and Staging. Each slot has the unique settings shown in the following table.

You perform a slot swap.

What are the configurations of the Production slot after the swap? To answer, select the appropriate options in the answer area.

NOTE: Each correction is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/app-service/deploy-staging-slots#what-happens-during-a-swap>

NEW QUESTION: 4

You have two Azure virtual networks named VNet1 and VNet2. VNet1 contains an Azure virtual machine named VM1. VNet2 contains an Azure virtual machine named VM2.

VM1 hosts a frontend application that connects to VM2 to retrieve data.

Users report that the frontend application is slower than usual.

You need to view the average round-trip time (RTT) of the packets from VM1 to VM2.

Which Azure Network Watcher feature should you use?

- A. NSG flow logs
- B. Connection troubleshoot
- C. IP flow verify
- D. Connection monitor

Answer: (SHOW ANSWER)

The Connection Monitor feature in Azure Network Watcher is now generally available in all public regions. Connection Monitor provides you RTT values on a per-minute granularity. You can

monitor a direct TCP connection from a virtual machine to a virtual machine, FQDN, URI, or IPv4 address.

Reference:

<https://azure.microsoft.com/en-us/updates/general-availability-azure-network-watcher-connection-monitor-in-all-public-regions/>

NEW QUESTION: 5

You have Azure virtual machines that run Windows Server 2019 and are configured as shown in the following table.

You create a private Azure DNS zone named adatum.com. You configure the adatum.com zone to allow auto registration from VNET1.

Which A records will be added to the adatum.com zone for each virtual machine? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/dns/private-dns-overview>

<https://docs.microsoft.com/en-us/azure/dns/private-dns-scenarios>

NEW QUESTION: 6

You have an Azure Active Directory (Azure AD) tenant named adatum.com. Adatum.com contains the groups in the following table.

You create two user accounts that are configured as shown in the following table.

To which groups do User1 and User2 belong? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

NEW QUESTION: 7

You need to implement Role1.

Which command should you run before you create Role1? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

NEW QUESTION: 8

You have an Azure subscription named Subscription1.

In Subscription1, you create an Azure file share named share1.

You create a shared access signature (SAS) named SAS1 as shown in the following exhibit.

To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/vs-azure-tools-storage-manage-with-storage-explorer?tabs=windows>

<https://feedback.azure.com/forums/217298-storage/suggestions/14498352-allow-azure-files-shares-to-be-mounted-using-sas-s>

<https://docs.microsoft.com/en-us/azure/storage/common/storage-sas-overview>

<https://docs.microsoft.com/en-us/azure/storage/files/storage-how-to-use-files-windows>

<http://www.rebeladmin.com/2018/03/step-step-guide-create-azure-file-share-map-windows-10/>

NEW QUESTION: 9

You need to create a bar chart that shows the number of distinct computers that have sent heartbeats each week. How should you complete the Log Analytics query? To answer, select the appropriate options in the answer are a. NOTE: Each correct selection is worth one point.

Answer:

NEW QUESTION: 10

You deploy an Azure Application Gateway.

You need to ensure that all the traffic requesting <https://adatum.com/internal> resources is directed to an internal server pool and all the traffic requesting <https://adatum.com/external> resources is directed to an external server pool.

What should you configure on the Application Gateway?

- A. URL path-based routing
- B. multi-site listeners
- C. basic routing
- D. SSL termination

Answer: A ([LEAVE A REPLY](#))

URL Path Based Routing allows you to route traffic to back-end server pools based on URL Paths of the request.

In the question there are two different path from where the traffic is getting generated as below

<https://adatum.com/internal>

<https://adatum.com/external>

So in this case we can use URL path-based routing feature of Application Gateway.

Reference:

<https://docs.microsoft.com/en-us/azure/application-gateway/url-route-overview>

NEW QUESTION: 11

You have an Azure App Services web app named App1.

You plan to deploy App1 by using Web Deploy.

You need to ensure that the developers of App1 can use their Azure Active Directory (Azure AD) credentials to deploy content to App1. The solution must use the principle of least privilege. What should you do?

- A. Configure app-level credentials for FTPS.
- B. Assign the Owner role to the developers.
- C. Configure user-level credentials for FTPS.
- D. Assign The Website Contributor role to the developers.

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 12

You have an Azure subscription named Subscription1.

In Subscription1, you create an alert rule named Alert1.

The Alert1 action group is configured as shown in the following exhibit.

Alert1 alert criteria is triggered every minute.

Use the drop-down menus to select the answer choice that completes each statement based on the information presented in the graphic.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://github.com/MicrosoftDocs/azure-docs/blob/master/articles/monitoring-and-diagnostics/monitoring-overview-alerts.md>

NEW QUESTION: 13

You have an Azure subscription that contains the resources shown in the following table.

You need to deploy Application1 to Cluster1. Which command should you run?

- A. kubectl apply
- B. az acr build
- C. docker build
- D. az aks create

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 14

You need to create container1 and share1.

Which storage accounts should you use for each resource? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/storage/blobs/storage-blob-storage-tiers>

<https://docs.microsoft.com/en-us/azure/storage/common/storage-account-overview>

NEW QUESTION: 15

You have an Azure subscription named Sub1.

You plan to deploy a multi-tiered application that will contain the tiers shown in the following table.

You need to recommend a networking solution to meet the following requirements:

Ensure that communication between the web servers and the business logic tier spreads equally across the virtual machines.

Protect the web servers from SQL injection attacks.

Which Azure resource should you recommend for each requirement? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/web-application-firewall/ag/ag-overview>

NEW QUESTION: 16

You have an Azure subscription that contains the storage accounts shown in the following exhibit.

Use the drop-down menus to select the answer choice that completes each statement based on the information presented in the graphic.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/storage/files/storage-how-to-create-premium-fileshare?tabs=azure-portal>

<https://docs.microsoft.com/en-us/azure/storage/blobs/storage-blob-storage-tiers>

Valid AZ-104 Dumps shared by Actual4test.com for Helping Passing AZ-104 Exam!

Actual4test.com now offer the **newest AZ-104 exam dumps**, the Actual4test.com AZ-104 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com AZ-104 dumps with Test Engine here:

https://www.actual4test.com/AZ-104_examcollection.html (430 Q&As Dumps, **30%OFF**

Special Discount: Freepdfdumps)

NEW QUESTION: 17

Your company has a main office in London that contains 100 client computers.

Three years ago, you migrated to Azure Active Directory (Azure AD).

The company's security policy states that all personal devices and corporate-owned devices must be registered or joined to Azure AD.

A remote user named User1 is unable to join a personal device to Azure AD from a home network.

You verify that other users can join their devices to Azure AD.

You need to ensure that User1 can join the device to Azure AD.

What should you do?

- A. From the Device settings blade, modify the Users may join devices to Azure AD setting.
- B. From the Device settings blade, modify the Maximum number of devices per user setting.
- C. Create a point-to-site VPN from the home network of User1 to Azure.
- D. Assign the User administrator role to User1.

Answer: (SHOW ANSWER)

The Maximum number of devices setting enables you to select the maximum number of devices that a user can have in Azure AD. If a user reaches this quota, they will not be able to add additional devices until one or more of the existing devices are removed.

Incorrect Answers:

A: The Users may join devices to Azure AD setting enables you to select the users who can join devices to Azure AD. Options are All, Selected and None. The default is All.

C: Azure AD Join enables users to join their devices to Active Directory from anywhere as long as they have connectivity with the Internet.

Reference:

<https://docs.microsoft.com/en-us/azure/active-directory/devices/device-management-azure-portal>

<http://techgenix.com/pros-and-cons-azure-ad-join/>

NEW QUESTION: 18

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure subscription named Subscription1. Subscription1 contains a resource group named RG1. RG1 contains resources that were deployed by using templates.

You need to view the date and time when the resources were created in RG1.

Solution: From the Subscriptions blade, you select the subscription, and then click Programmatic deployment.

Does this meet the goal?

- A. Yes
- B. No

Answer: B (LEAVE A REPLY)

From the RG1 blade, click Deployments. You see a history of deployment for the resource group.

Reference:

<https://docs.microsoft.com/en-us/azure/azure-resource-manager/templates/template-tutorial-create-first-template?tabs=azure-powershell> Through activity logs, you can determine:

§ what operations were taken on the resources in your subscription

§ who started the operation

§ when the operation occurred

§ the status of the operation

§ the values of other properties that might help you research the operation On the Azure portal menu, select Monitor, or search for and select Monitor from any page

2. Select Activity Log.

3. You see a summary of recent operations. A default set of filters is applied to the operations. Notice the information on the summary includes who started the action and when it happened.

<https://docs.microsoft.com/en-us/azure/azure-resource-manager/management/view-activity-logs>

NEW QUESTION: 19

You plan to automate the deployment of a virtual machine scale set that uses the Windows Server 2016 Datacenter image.

You need to ensure that when the scale set virtual machines are provisioned, they have web server components installed.

Which two actions should you perform? Each correct answer presents part of the solution.

NOTE Each correct selection is worth one point.

A. Modify the extensionProfile section of the Azure Resource Manager template.

B. Create a new virtual machine scale set in the Azure portal.

C. Create an Azure policy.

D. Create an automation account.

E. Upload a configuration script.

Answer: A,B (LEAVE A REPLY)

Virtual Machine Scale Sets can be used with the Azure Desired State Configuration (DSC) extension handler. Virtual machine scale sets provide a way to deploy and manage large numbers of virtual machines, and can elastically scale in and out in response to load. DSC is used to configure the VMs as they come online so they are running the production software.

Reference:

<https://docs.microsoft.com/en-us/azure/virtual-machine-scale-sets/virtual-machine-scale-sets-dsc>

NEW QUESTION: 20

You have an Azure subscription named Subscription1 that contains the virtual networks in the following table.

Subscription1 contains the virtual machines in the following table.

In Subscription1, you create a load balancer that has the following configurations:

Name: LB1

SKU: Basic

Type: Internal

Subnet: Subnet12

Virtual network: VNET1

For each of the following statements, select Yes if the statement is true. Otherwise, select No.
NOTE: each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/load-balancer/load-balancer-overview>

NEW QUESTION: 21

Your network contains an on-premises Active Directory Domain Services (AD DS) domain named contoso.com. The domain contains the servers shown in the following table.

You plan to migrate contoso.com to Azure.

You create an Azure virtual network named VNET1 that has the following settings:

* Address space: 10.0.0.0/16

* Subnet:

o Name: Subnet1

o IPv4: 10.0.1.0/24

You need to move DC1 to VNET1. The solution must ensure that the member servers in contoso.com can resolve AD DS DNS names.

How should you configure DO? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

NEW QUESTION: 22

You have an app named App1 that runs on an Azure web app named webapp1.

The developers at your company upload an update of App1 to a Git repository named GUI.

Webapp1 has the deployment slots shown in the following table.

You need to ensure that the App1 update is tested before the update is made available to users.

Which two actions should you perform? Each correct answer presents part of the solution.

NOTE Each correct selection is worth one point.

A. Stop webapp1 prod.

B. Stop webapp1-test

C. Deploy the App1 update to webapp1-test, and then test the update.

D. Deploy the App1 update to webapp1-prod, and then test the update.

E. Swap the slots.

Answer: C,E (LEAVE A REPLY)

You can validate web app changes in a staging deployment slot before swapping it with the production slot. Deploying an app to a slot first and swapping it into production makes sure that all instances of the slot are warmed up before being swapped into production. This eliminates downtime when you deploy your app. The traffic redirection is seamless, and no requests are dropped because of swap operations. You can automate this entire workflow by configuring auto swap when pre-swap validation isn't needed.

After the swap you can deploy the App1 update to webapp1-test, and then test the update. If the changes swapped into the production slot aren't as per your expectation then you can perform the same swap immediately to get your "last known good site" back.

Reference:

<https://docs.microsoft.com/en-us/azure/app-service/deploy-staging-slots>

NEW QUESTION: 23

You deploy an Azure Kubernetes Service (AKS) cluster that has the network profile shown in the following exhibit.

Use the drop-down menus to select the answer choice that completes each statement based on the information presented in the graphic. NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/aks/configure-azure-cni>

NEW QUESTION: 24

You have an Azure subscription that contains a user account named User1.

You need to ensure that User1 can assign a policy to the tenant root management group.

What should you do?

- A.** Assign the Owner role to User1. and then instruct User1 to configure access management for Azure resources.
- B.** Assign the Global administrator role to User1, and then modify the default conditional access policies.
- C.** Assign the Global administrator role to User1, and then instruct User1 to configure access management for Azure resources.
- D.** Assign the Owner role to User1. and then modify the default conditional access policies.

Answer: B (LEAVE A REPLY)

NEW QUESTION: 25

You have the Azure virtual machines shown in the following table.

A DNS service is install on VM1.

You configure the DNS server settings for each virtual network as shown in the following exhibit.

You need 10 ensure that all the virtual machines can resolve DNS names by using the DNS service on VM1. What should you do?

- A.** Add service endpoints on VNET2 and VNET3.
- B.** Configure peering between VNE11, VNETT2, and VNET3.
- C.** Configure a conditional forwarder on VM1
- D.** Add service endpoints on VNET1.

Answer: B (LEAVE A REPLY)

An Azure AD DS DNS zone should only contain the zone and records for the managed domain itself.

A conditional forwarder is a configuration option in a DNS server that lets you define a DNS domain, such as contoso.com, to forward queries to. Instead of the local DNS server trying to resolve queries for records in that domain, DNS queries are forwarded to the configured DNS for that domain. This configuration makes sure that the correct DNS records are returned, as you don't create a local a DNS zone with duplicate records in the managed domain to reflect those resources.

To create a conditional forwarder in your managed domain, complete the following steps:

1. Select your DNS zone, such as aaddscontoso.com.
2. Select Conditional Forwarders, then right-select and choose New Conditional Forwarder...
3. Enter your other DNS Domain, such as contoso.com, then enter the IP addresses of the DNS servers for that namespace, as shown in the following example:
4. Check the box for Store this conditional forwarder in Active Directory, and replicate it as follows, then select the option for All DNS servers in this domain, as shown in the following example:
5. To create the conditional forwarder, select OK.

Name resolution of the resources in other namespaces from VMs connected to the managed domain should now resolve correctly. Queries for the DNS domain configured in the conditional forwarder are passed to the relevant DNS servers.

Reference:

<https://docs.microsoft.com/en-us/azure/virtual-network/virtual-networks-name-resolution-for-vms-and-role-instances>

<https://docs.microsoft.com/en-us/azure/active-directory-domain-services/manage-dns>

NEW QUESTION: 26

You have an Azure AD tenant named adatum.com that contains the groups shown in the following table.

Adatum.com contains the users shown in the following table.

You assign an Azure Active Directory Premium P2 license to Group1 as shown in the following exhibit.

Group2 is NOT directly assigned a license.

For each of the following statements, select Yes if the statement is true. Otherwise, select No.

NOTE: Each correct selection is worth one point

Answer:

NEW QUESTION: 27

You have an Azure web app named App1. App1 has the deployment slots shown in the following table:

In webapp1-test, you test several changes to App1.

You back up App1.

You swap webapp1-test for webapp1-prod and discover that App1 is experiencing performance issues.

You need to revert to the previous version of App1 as quickly as possible.

What should you do?

- A. Redeploy App1
- B. Swap the slots
- C. Clone App1
- D. Restore the backup of App1

Answer: B (LEAVE A REPLY)

When you swap deployment slots, Azure swaps the Virtual IP addresses of the source and destination slots, thereby swapping the URLs of the slots. We can easily revert the deployment by swapping back.

You can validate app changes in a staging deployment slot before swapping it with the production slot. Deploying an app to a slot first and swapping it into production makes sure that all instances of the slot are warmed up before being swapped into production. This eliminates downtime when you deploy your app. The traffic redirection is seamless, and no requests are dropped because of swap operations. You can automate this entire workflow by configuring auto swap when pre-swap validation isn't needed.

After a swap, the slot with previously staged app now has the previous production app. If the changes swapped into the production slot aren't as you expect, you can perform the same swap immediately to get your "last known good site" back.

Reference:

<https://docs.microsoft.com/en-us/azure/app-service/deploy-staging-slots>

NEW QUESTION: 28

You have an Azure subscription

You need to receive an email alert when a resource lock is removed from any resource in the subscription What should you use to create an activity log alert in Azure Monitor?

- A. a resource a condition, and an action group
- B. a Log Analytics workspace a resource, and an action group
- C. a data collection endpoint, an application security group, and a resource group
- D. a resource, a condition and a Microsoft 365 group

Answer: B (LEAVE A REPLY)

NEW QUESTION: 29

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure subscription that contains the virtual machines shown in the following table.

You deploy a load balancer that has the following configurations:

Name: LB1

Type: Internal

SKU: Standard

Virtual network: VNET1

You need to ensure that you can add VM1 and VM2 to the backend pool of LB1.

Solution: You create two Standard public IP addresses and associate a Standard SKU public IP address to the network interface of each virtual machine.

Does this meet the goal?

A. Yes

B. No

Answer: (SHOW ANSWER)

A Backend Pool configured by IP address has the following limitations:

Standard load balancer only

Reference:

<https://docs.microsoft.com/en-us/azure/load-balancer/backend-pool-management>

NEW QUESTION: 30

You have an Azure subscription named Subscription1.

You deploy a Linux virtual machine named VM1 to Subscription1.

You need to monitor the metrics and the logs of VM1.

What should you use?

A. Linux Diagnostic Extension (LAD) 3.0

B. Azure Analysis Services

C. the AzurePerformanceDiagnostics extension

D. Azure HDInsight

Answer: A (LEAVE A REPLY)

You can use extensions to configure diagnostics on your VMs to collect additional metric data.

The basic host metrics are available, but to see more granular and VM-specific metrics, you need to install the Azure diagnostics extension on the VM. The Azure diagnostics extension allows additional monitoring and diagnostics data to be retrieved from the VM.

Reference:

<https://docs.microsoft.com/en-us/azure/virtual-machines/linux/tutorial-monitor>

NEW QUESTION: 31

You have an Azure subscription that contains a storage account named account1.

You plan to upload the disk files of a virtual machine to account1 from your on-premises network.

The on-premises network uses a public IP address space of 131.107.1.0/24.

You plan to use the disk files to provision an Azure virtual machine named VM1. VM1 will be attached to a virtual network named VNet1. VNet1 uses an IP address space of 192.168.0.0/24.

You need to configure account1 to meet the following requirements:

Ensure that you can upload the disk files to account1.

Ensure that you can attach the disks to VM1.

Prevent all other access to account1.

Which two actions should you perform? Each correct selection presents part of the solution.

NOTE: Each correct selection is worth one point.

A. From the Service endpoints blade of VNet1, add a service endpoint

B. From the Networking blade of account1, select Allow trusted Microsoft services to access this storage account

C. From the Networking blade of account1, add VNet1.

D. From the Networking blade of account1, add the 131.107.1.0/24 IP address range.

E. From the Networking blade of account1, select Selected networks.

Answer: D,E ([LEAVE A REPLY](#))

Valid AZ-104 Dumps shared by Actual4test.com for Helping Passing AZ-104 Exam!

Actual4test.com now offer the **newest AZ-104 exam dumps**, the Actual4test.com AZ-104 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com AZ-104 dumps with Test Engine here:

https://www.actual4test.com/AZ-104_examcollection.html (430 Q&As Dumps, **30%OFF**

Special Discount: [Freepdfdumps](#))

NEW QUESTION: 32

You are troubleshooting a performance issue for an Azure Application Gateway.

You need to compare the total requests to the failed requests during the past six hours.

What should you use?

A. Metrics in Application Gateway

B. Diagnostics logs in Application Gateway

C. NSG flow logs in Azure Network Watcher

D. Connection monitor in Azure Network Watcher

Answer: ([SHOW ANSWER](#))

Application Gateway currently has seven metrics to view performance counters.

Metrics are a feature for certain Azure resources where you can view performance counters in the portal. For Application Gateway, the following metrics are available:

Total Requests

Failed Requests

Current Connections

Healthy Host Count

Response Status

Throughput

Unhealthy Host count

You can filter on a per backend pool basis to show healthy/unhealthy hosts in a specific backend pool Reference:

Metrics

NEW QUESTION: 33

You have an Azure App Service plan named ASP1.
CPU usage for ASP1 is shown in the following exhibit.

Answer:

NEW QUESTION: 34

You create the following resources in an Azure subscription:

- * An Azure Container Registry instance named Registry1.
- * An Azure Kubernetes Service (AKS) cluster named Cluster1.

You create a container image named App1 on your administrative workstation. You need to deploy App1 to Cluster1. What should you do first?

- A. Create a host pool on Cluster1.
- B. Run the az acr build command.
- C. Run the docker build command.
- D. Run the docker push command.

Answer: ([SHOW ANSWER](#))

Run the az acr build command : Correct Choice

az acr build command queues a quick build, providing streaming logs for an Azure Container Registry az acr build --registry

[--agent-pool]

[--auth-mode {Default, None}]

[--build-arg]

[--file]

[--image]

[--no-format]

[--no-logs]

[--no-push]

[--no-wait]

[--platform]

[--resource-group]

[--secret-build-arg]

[--subscription]

[--target]

[--timeout]

[<SOURCE_LOCATION>]

Create a host pool on Cluster1 : Incorrect Choice

Host pools are a collection of one or more identical virtual machines (VMs) within Windows Virtual Desktop environments. It won't deploy the app to the cluster.

Run the docker push command : Incorrect Choice

Use docker push to share your images to the Docker Hub registry or to a self-hosted one. It won't deploy the app to the cluster.

Run the docker build command : Incorrect Choice

This command will build an image from a Dockerfile. But in the question it has been said that image file is already built and need to deploy. This command will not deploy the image.

Reference:

<https://docs.microsoft.com/en-us/cli/azure/acr?view=azure-cli-latest#az-acr-build>

<https://docs.docker.com/engine/reference/commandline/push/>

<https://docs.microsoft.com/en-us/azure/virtual-desktop/create-host-pools-azure-marketplace>

<https://docs.docker.com/engine/reference/commandline/build/>

NEW QUESTION: 35

You have an Azure subscription that includes data in following locations:

You plan to export data by using Azure import/export job named Export1.

You need to identify the data that can be exported by using Export1.

Which data should you identify?

- A. DB1
- B. Table1
- C. container1
- D. Share1

Answer: D ([LEAVE A REPLY](#))

Explanation

Azure Import/Export service is used to securely import large amounts of data to Azure Blob storage.

Only the Blob service is supported with the Export job feature

Reference:

<https://docs.microsoft.com/en-us/azure/storage/common/storage-import-export-requirements>

NEW QUESTION: 36

You have an Azure subscription named Sub1 that contains two users named User1 and User2.

You need to assign role-based access control (RBAC) roles to User1 and User2. The users must be able to perform the following tasks in Sub1:

- * User1 must view the data in any storage account.
- * User2 must assign users the Contributor role for storage accounts.

The solution must use the principle of least privilege.

Which RBAC role should you assign to each user? To answer, drag the appropriate roles to the correct users. Each role may be used once, more than once, or not at all.

Answer:

NEW QUESTION: 37

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have a computer named Computer1 that has a point-to-site VPN connection to an Azure virtual network named VNet1. The point-to-site connection uses a self-signed certificate.

From Azure, you download and install the VPN client configuration package on a computer named Computer2.

You need to ensure that you can establish a point-to-site VPN connection to VNet1 from Computer2.

Solution: On Computer2, you set the Startup type for the IPsec Policy Agent service to Automatic.

Does this meet the goal?

A. Yes

B. No

Answer: ([SHOW ANSWER](#))

Instead export the client certificate from Computer1 and install the certificate on Computer2.

Note: Each client computer that connects to a VNet using Point-to-Site must have a client certificate installed. You generate a client certificate from the self-signed root certificate, and then export and install the client certificate. If the client certificate is not installed, authentication fails.

Reference:

<https://docs.microsoft.com/en-us/azure/vpn-gateway/vpn-gateway-certificates-point-to-site>

NEW QUESTION: 38

You have an Azure subscription that contains several virtual machines and an Azure Log Analytics workspace named Workspace1. You create a log search query as shown in the following exhibit.

Use the drop-down menus to select the answer choice that completes each statement based on the information presented in the graphic.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/azure-monitor/log-query/log-query-overview>

[\[ous.azurewebsites.net/queryLanguage/query_language_renderoperator.html\]\(https://docs-analytics-ous.azurewebsites.net/queryLanguage/query_language_renderoperator.html\)](https://docs-analytics-</p></div><div data-bbox=)

NEW QUESTION: 39

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution. After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure subscription that contains the following resources:

A virtual network that has a subnet named Subnet1

Two network security groups (NSGs) named NSG-VM1 and NSG-Subnet1

A virtual machine named VM1 that has the required Windows Server configurations to allow Remote Desktop connections NSG-Subnet1 has the default inbound security rules only.

NSG-VM1 has the default inbound security rules and the following custom inbound security rule:

Priority: 100

Source: Any

Source port range: *

Destination: *

Destination port range: 3389

Protocol: UDP

Action: Allow

VM1 connects to Subnet1. NSG1-VM1 is associated to the network interface of VM1. NSG-Subnet1 is associated to Subnet1.

You need to be able to establish Remote Desktop connections from the internet to VM1.

Solution: You add an inbound security rule to NSG-Subnet1 that allows connections from the Internet source to the VirtualNetwork destination for port range 3389 and uses the UDP protocol.

Does this meet the goal?

A. Yes

B. No

Answer: (SHOW ANSWER)

The default port for RDP is TCP port 3389 not UDP.

NSGs deny all inbound traffic except from virtual network or load balancers. For inbound traffic, Azure processes the rules in a network security group associated to a subnet first, and then the rules in a network security group associated to the network interface.

By default NSG rule to allow traffic through RDP port 3389 is not created automatically during the creation of VM , unless you change the setting during creation.

Here in the solution UDP traffic is allowed at virtual network level which is not tcp/rdp protocol. So this will not work to achieve the goal.

Reference:

<https://docs.microsoft.com/en-us/azure/virtual-machines/troubleshooting/troubleshoot-rdp-connection>

<https://docs.microsoft.com/en-us/azure/virtual-network/security-overview#default-security-rules>

NEW QUESTION: 40

Your network contains an on-premises Active Directory forest named contoso.com that contains two domains named contoso.com and east.contoso.com.

The forest contains the users shown in the following table.

You plan to sync east.contoso.com to an Azure Active Directory (Azure AD) tenant by using Azure AD Connect.

You need to select an account for Azure AD Connect to use to connect to the forest.

Which account should you select?

- A. User1
- B. User2
- C. User3
- D. User4

Answer: D (LEAVE A REPLY)

It is no longer supported to use an enterprise admin or a domain admin account as the AD DS Connector account.

Reference:

<https://docs.microsoft.com/en-us/azure/active-directory/hybrid/reference-connect-accounts-permissions>

NEW QUESTION: 41

You have an Azure Kubernetes cluster in place.

You have to deploy an application using an Azure Container registry image.

Which of the following command can be used for this requirement?

- A. az kubernetes deploy
- B. kubectl apply
- C. New-AzKubernetes set
- D. docker run

Answer: B (LEAVE A REPLY)

kubectl apply : Correct Choice

The kubectl command can be used to deploy applications to a Kubernetes cluster.

az kubernetes deploy : Incorrect Choice

This command is used to manage Azure Kubernetes Services. This is not used to deploy applications to a Kubernetes cluster.

New-AzKubernetes set : Incorrect Choice

This command is used to create a new managed Kubernetes cluster. This is not used to deploy applications to a Kubernetes cluster.

docker run : Incorrect Choice

This is run command in a new container. This is not used to deploy applications to a Kubernetes cluster.

Reference:

<https://kubernetes.io/docs/reference/generated/kubectl/kubectl-commands#apply>

<https://docs.microsoft.com/en-us/cli/azure/aks?view=azure-cli-latest>

<https://docs.microsoft.com/en-us/powershell/module/az.aks/New-AzAks?view=azps-3.8.0&viewFallbackFrom=azps-4.3.0>
<https://docs.docker.com/engine/reference/commandline/run/>

NEW QUESTION: 42

You need to the appropriate sizes for the Azure virtual for Server2.

What should you do? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/site-recovery/migrate-tutorial-on-premises-azure>

NEW QUESTION: 43

Your company has an Azure subscription named Subscription1.

The company also has two on-premises servers named Server1 and Server2 that run Windows Server 2016. Server1 is configured as a DNS server that has a primary DNS zone named adatum.com. Adatum.com contains 1,000 DNS records.

You manage Server1 and Subscription1 from Server2. Server2 has the following tools installed:

The DNS Manager console

Azure PowerShell

Azure CLI 2.0

You need to move the adatum.com zone to Subscription1. The solution must minimize administrative effort.

What should you use?

- A.** Azure PowerShell
- B.** Azure CLI
- C.** the Azure portal
- D.** the DNS Manager console

Answer: (SHOW ANSWER)

Azure DNS supports importing and exporting zone files by using the Azure command-line interface (CLI). Zone file import is not currently supported via Azure PowerShell or the Azure portal.

NEW QUESTION: 44

You have an Azure subscription named Subscription1. Subscription1 contains the resources in the following table.

In Azure, you create a private DNS zone named adatum.com. You set the registration virtual network to VNet2. The adatum.com zone is configured as shown in the following exhibit.

For each of the following statements, select Yes if the statement is true. Otherwise, select No.

NOTE: Each correct selection is worth one point.

Answer:

NEW QUESTION: 45

You have an Azure subscription that contains an Azure Active Directory (Azure AD) tenant named contoso.com and an Azure Kubernetes Service (AKS) cluster named AKS1.

An administrator reports that she is unable to grant access to AKS1 to the users in contoso.com. You need to ensure that access to AKS1 can be granted to the contoso.com users.

What should you do first?

- A. From contoso.com, modify the Organization relationships settings.
- B. From contoso.com, create an OAuth 2.0 authorization endpoint.
- C. Recreate AKS1.
- D. From AKS1, create a namespace.

Answer: B ([LEAVE A REPLY](#))

With Azure AD-integrated AKS clusters, you can grant users or groups access to Kubernetes resources within a namespace or across the cluster. To obtain a kubectl configuration context, a user can run the `az aks get-credentials` command. When a user then interacts with the AKS cluster with kubectl, they're prompted to sign in with their Azure AD credentials. This approach provides a single source for user account management and password credentials. The user can only access the resources as defined by the cluster administrator.

Azure AD authentication is provided to AKS clusters with OpenID Connect. OpenID Connect is an identity layer built on top of the OAuth 2.0 protocol. For more information on OpenID Connect, see the Open ID connect documentation. From inside of the Kubernetes cluster, Webhook Token Authentication is used to verify authentication tokens. Webhook token authentication is configured and managed as part of the AKS cluster.

Reference:

<https://kubernetes.io/docs/reference/access-authn-authz/authentication/>

<https://docs.microsoft.com/en-us/azure/aks/concepts-identity>

NEW QUESTION: 46

Your on-premises network contains a VPN gateway.

You have an Azure subscription that contains the resources shown in the following table.

You need to ensure that all the traffic from VM1 to storage1 travels across the Microsoft backbone network.

What should you configure?

- A. Azure Virtual WAN
- B. service endpoints
- C. a network security group (NSG)
- D. Azure Active Directory (Azure AD) Application Proxy

Answer: C ([LEAVE A REPLY](#))

Valid AZ-104 Dumps shared by Actual4test.com for Helping Passing AZ-104 Exam!
Actual4test.com now offer the **newest AZ-104 exam dumps**, the Actual4test.com AZ-104 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com AZ-104 dumps with Test Engine here:

https://www.actual4test.com/AZ-104_examcollection.html (430 Q&As Dumps, **30%OFF**

Special Discount: Freepdfdumps)

NEW QUESTION: 47

You discover that VM3 does NOT meet the technical requirements.

You need to verify whether the issue relates to the NSGs.

What should you use?

- A. Diagram in VNet1
- B. the security recommendations in Azure Advisor
- C. Diagnostic settings in Azure Monitor
- D. Diagnose and solve problems in Traffic Manager Profiles
- E. IP flow verify in Azure Network Watcher

Answer: E (LEAVE A REPLY)

Scenario: Litware must meet technical requirements including:

Ensure that VM3 can establish outbound connections over TCP port 8080 to the applications servers in the Montreal office.

IP flow verify checks if a packet is allowed or denied to or from a virtual machine. The information consists of direction, protocol, local IP, remote IP, local port, and remote port. If the packet is denied by a security group, the name of the rule that denied the packet is returned. While any source or destination IP can be chosen, IP flow verify helps administrators quickly diagnose connectivity issues from or to the internet and from or to the on-premises environment.

Reference:

<https://docs.microsoft.com/en-us/azure/network-watcher/network-watcher-ip-flow-verify-overview>

Topic 3, Contoso Ltd

Existing Environment

Currently, Contoso uses multiple types of servers for business operations, including the following:

File servers

Domain controllers

Microsoft SQL Server servers

Your network contains an Active Directory forest named contoso.com. All servers and client computers are joined to Active Directory.

You have a public-facing application named App1. App1 is comprised of the following three tiers:

A SQL database

A web front end

A processing middle tier

Each tier is comprised of five virtual machines. Users access the web front end by using HTTPS only.

Requirements

Planned Changes

Contoso plans to implement the following changes to the infrastructure:

Move all the tiers of App1 to Azure.

Move the existing product blueprint files to Azure Blob storage.

Create a hybrid directory to support an upcoming Microsoft Office 365 migration project.

Technical Requirements

Contoso must meet the following technical requirements:

Move all the virtual machines for App1 to Azure.

Minimize the number of open ports between the App1 tiers.

Ensure that all the virtual machines for App1 are protected by backups.

Copy the blueprint files to Azure over the Internet.

Ensure that the blueprint files are stored in the archive storage tier.

Ensure that partner access to the blueprint files is secured and temporary.

Prevent user passwords or hashes of passwords from being stored in Azure.

Use unmanaged standard storage for the hard disks of the virtual machines.

Ensure that when users join devices to Azure Active Directory (Azure AD), the users use a mobile phone to verify their identity.

Minimize administrative effort whenever possible.

User Requirements

Contoso identifies the following requirements for users:

Ensure that only users who are part of a group named Pilot can join devices to Azure AD.

Designate a new user named Admin1 as the service administrator of the Azure subscription.

Admin1 must receive email alerts regarding service outages.

Ensure that a new user named User3 can create network objects for the Azure subscription.

NEW QUESTION: 48

You need to configure a new Azure App Service app named WebApp1. The solution must meet the following requirements:

* WebApp1 must be able to verify a custom domain name of app.contoso.com.

* WebApp1 must be able to automatically scale up to eight instances.

* Costs and administrative effort must be minimized.

Which pricing plan should you choose, and which type of record should you use to verify the domain? To answer, select the appropriate options in the answer area.

NOTE: Each correct answer is worth one point.

Answer:

NEW QUESTION: 49

You have a public load balancer that balances ports 80 and 443 across three virtual machines. You need to direct all the Remote Desktop Protocol (RDP) connections to VM3 only. What should you configure?

- A. a load balancing rule
- B. a new public load balancer for VM3
- C. an inbound NAT rule
- D. a frontend IP configuration

Answer: C (LEAVE A REPLY)

To port forward traffic to a specific port on specific VMs use an inbound network address translation (NAT) rule.

<https://docs.microsoft.com/en-us/azure/load-balancer/load-balancer-overview> an inbound NAT rule :

Create a load balancer inbound network address translation (NAT) rule to forward traffic from a specific port of the front-end IP address to a specific port of a back-end VM.

Hence this option is Correct

a load balancing rule : Incorrect Choice

A load balancer rule defines how traffic is distributed to the VMs. The rule defines the front-end IP configuration for incoming traffic, the back-end IP pool to receive the traffic, and the required source and destination ports.

a new public load balancer for VM3 : Incorrect Choice

This option will not help you since this will route all traffic to VM3 only.

a frontend IP configuration : Incorrect Choice

When you define an Azure Load Balancer, a frontend and a backend pool configuration are connected with rules. The health probe referenced by the rule is used to determine how new flows are sent to a node in the backend pool. The frontend (aka VIP) is defined by a 3-tuple comprised of an IP address (public or internal), a transport protocol (UDP or TCP), and a port number from the load balancing rule. The backend pool is a collection of Virtual Machine IP configurations (part of the NIC resource) which reference the Load Balancer backend pool.

Reference:

<https://docs.microsoft.com/en-us/azure/load-balancer/tutorial-load-balancer-port-forwarding-portal>

<https://pixelrobots.co.uk/2017/08/azure-load-balancer-for-rds/>

NEW QUESTION: 50

Which blade should you instruct the finance department auditors to use?

- A. invoices
- B. partner information
- C. cost analysis
- D. External services

Answer: C (LEAVE A REPLY)

Cost analysis: Correct Option

In cost analysis blade of Azure, you can see all the detail for custom time span. You can use this to determine expenditure of last few day, weeks, and month. Below options are available in Cost analysis blade for filtering information by time span: last 7 days, last 30 days, and custom date range. Choosing the first option (last 7 days) auditors can view the costs by time span.

Cost analysis shows data for the current month by default. Use the date selector to switch to common date ranges quickly. Examples include the last seven days, the last month, the current year, or a custom date range. Pay-as-you-go subscriptions also include date ranges based on your billing period, which isn't bound to the calendar month, like the current billing period or last invoice. Use the <PREVIOUS and NEXT> links at the top of the menu to jump to the previous or next period, respectively. For example, <PREVIOUS will switch from the Last 7 days to 8-14 days ago or 15-21 days ago.

Invoice: Incorrect Option

Invoices can only be used for past billing periods not for current billing period, i.e. if your requirement is to know the last week's cost then that also not filled by invoices because Azure generates invoice at the end of the month. Even though Invoices have custom timespan, but when you put in dates for a week, the pane would be empty. Below is from Microsoft document:

Resource Provider: Incorrect Option

When deploying resources, you frequently need to retrieve information about the resource providers and types. For example, if you want to store keys and secrets, you work with the Microsoft.KeyVault resource provider. This resource provider offers a resource type called vaults for creating the key vault. This is not useful for reviewing all Azure costs from the past week which is required for audit.

Payment method: Incorrect Option

Payment methods is not useful for reviewing all Azure costs from the past week which is required for audit.

Reference:

<https://docs.microsoft.com/en-us/azure/cost-management-billing/costs/quick-acm-cost-analysis>

<https://docs.microsoft.com/en-us/azure/cost-management-billing/manage/download-azure-invoice-daily-usage-date>

NEW QUESTION: 51

You have an Azure subscription named Subscription1 that contains a resource group named RG1. In RG1, you create an internal load balancer named LB1 and a public load balancer named LB2. You need to ensure that an administrator named Admin 1 can manage LB1 and LB2. The solution must follow the principle of least privilege.

Which role should you assign to Admin1 for each task? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/role-based-access-control/built-in-roles>

NEW QUESTION: 52

You have the App Service plans shown in the following table.

You plan to create the Azure web apps shown in the following table.

You need to identify which App Service plans can be used for the web apps.

What should you identify? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/app-service/quickstart-dotnetcore?pivots=platform-linux>

<https://docs.microsoft.com/en-us/azure/app-service/app-service-plan-manage#>

NEW QUESTION: 53

You have two Azure virtual machines as shown in the following table.

You create the Azure DNS zones shown in the following table.

You perform the following actions:

To fabrikam.com, you add a virtual network link to vnet1 and enable auto registration.

For contoso.com, you assign vm1 and vm2 the Owner role.

For each of the following statements, select Yes if the statement is true. Otherwise, select No.

NOTE: Each correct selection is worth one point.

Answer:**NEW QUESTION: 54**

You have an Azure subscription that contains the following storage account:

You need to create a request to Microsoft Support to perform a live migration of storage1 to Zone Redundant Storage (ZRS) replication. How should you modify storage1 before the Live migration?

- A. Set the replication to Locally-redundant storage (LRS)
- B. Disable Advanced threat protection
- C. Remove the lock
- D. Set the access tier to Hot

Answer: A (LEAVE A REPLY)

If you want to live migration from RA-GRS to ZRS, at first you have to Switch the storage tier to LRS and then only you can request a live migration.

Reference:

<https://docs.microsoft.com/en-us/azure/storage/common/redundancy-migration?toc=%2Fazure%2Fstorage%2Fblobs%2Ftoc.json&tabs=portal>

NEW QUESTION: 55

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution. After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure subscription named Subscription1. Subscription1 contains a resource group named RG1. RG1 contains resources that were deployed by using templates. You need to view the date and time when the resources were created in RG1.

Solution: From the RG1 blade, you click Deployments.

Does this meet the goal?

A. Yes

B. No

Answer: A (LEAVE A REPLY)

1. Select the resource group (Here RG1) you want to examine.
2. Select the link under Deployments.
3. Select one of the deployments from the deployment history.
4. You will see a history of deployment for the resource group, including the correlation ID.

Reference:

<https://docs.microsoft.com/en-us/azure/azure-resource-manager/templates/deployment-history?tabs=azure-portal>

NEW QUESTION: 56

You configure Azure AD Connect for Azure Active Directory Seamless Single Sign-On (Azure AD Seamless SSO) for an on-premises network. Users report that when they attempt to access myapps.microsoft.com, they are prompted multiple times to sign in and are forced to use an account name that ends with onmicrosoft.com.

You discover that there is a UPN mismatch between Azure AD and the on-premises Active Directory. You need to ensure that the users can use single-sign on (SSO) to access Azure resources.

What should you do first?

A. From the on-premises network, deploy Active Directory Federation Services (AD FS).

B. From Azure AD, add and verify a custom domain name.

C. From the on-premises network, request a new certificate that contains the Active Directory domain name.

D. From the server that runs Azure AD Connect, modify the filtering options.

Answer: (SHOW ANSWER)

Azure AD Connect lists the UPN suffixes that are defined for the domains and tries to match them with a custom domain in Azure AD. Then it helps you with the appropriate action that needs to be taken. The Azure AD sign-in page lists the UPN suffixes that are defined for on-premises Active Directory and displays the corresponding status against each suffix. The status values can be one of the following:

State: Verified

Azure AD Connect found a matching verified domain in Azure AD. All users for this domain can sign in by using their on-premises credentials.

State: Not verified

Azure AD Connect found a matching custom domain in Azure AD, but it isn't verified. The UPN suffix of the users of this domain will be changed to the default .onmicrosoft.com suffix after synchronization if the domain isn't verified.

Action Required: Verify the custom domain in Azure AD.

NEW QUESTION: 57

You deploy an Azure Kubernetes Service (AKS) cluster named Cluster1 that uses the IP addresses shown in the following table.

You need to provide internet users with access to the applications that run in Cluster1.

Which IP address should you include in the DNS record for Ousted?

- A. 172.17.7.1
- B. 131.107.2.1
- C. 192.168.10.2
- D. 10.0.10.11

Answer: B (LEAVE A REPLY)

When any internet user will try to access the cluster which is behind a load balancer, traffic will first hit to load balancer front end IP. So in the DNS configuration you have to provide the IP address of the load balancer.

Reference:

<https://stackoverflow.com/questions/43660490/giving-a-dns-name-to-azure-load-balancer>

NEW QUESTION: 58

You have an Azure subscription that contains the resources shown in the following table.

You need to deploy Application1 to Cluster1.

Which command should you run?

- A. az aks create
- B. kubectl apply
- C. az acr build
- D. docker build

Answer: C (LEAVE A REPLY)

NEW QUESTION: 59

You have an Azure subscription named AZPT1 that contains the resources shown in the following table:

You create a new Azure subscription named AZPT2.

You need to identify which resources can be moved to AZPT2.

Which resources should you identify?

- A. VM1, storage1, VNET1, and VM1Managed only
- B. VM1 and VM1Managed only
- C. VM1, storage1, VNET1, VM1Managed, and RVAULT1
- D. RVAULT1 only

Answer: (SHOW ANSWER)

You can move a VM and its associated resources to a different subscription by using the Azure portal.

You can now move an Azure Recovery Service (ASR) Vault to either a new resource group within the current subscription or to a new subscription.

Reference:

<https://docs.microsoft.com/en-us/azure/azure-resource-manager/management/move-resource-group-and-subscription>

<https://docs.microsoft.com/en-us/azure/key-vault/general/keyvault-move-subscription>

NEW QUESTION: 60

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure subscription that contains the following resources:

A virtual network that has a subnet named Subnet1

Two network security groups (NSGs) named NSG-VM1 and NSG-Subnet1

A virtual machine named VM1 that has the required Windows Server configurations to allow Remote Desktop connections NSG-Subnet1 has the default inbound security rules only.

NSG-VM1 has the default inbound security rules and the following custom inbound security rule:

Priority: 100

Source: Any

Source port range: *

Destination: *

Destination port range: 3389

Protocol: UDP

Action: Allow

VM1 connects to Subnet1. NSG1-VM1 is associated to the network interface of VM1. NSG-Subnet1 is associated to Subnet1.

You need to be able to establish Remote Desktop connections from the internet to VM1.

Solution: You add an inbound security rule to NSG-Subnet1 and NSG-VM1 that allows connections from the internet source to the VirtualNetwork destination for port range 3389 and uses the TCP protocol.

Does this meet the goal?

- A. Yes

B. No

Answer: ([SHOW ANSWER](#))

The default port for RDP is TCP port 3389. A rule to permit RDP traffic must be created automatically when you create your VM.

Note on NSG-Subnet1: Azure routes network traffic between all subnets in a virtual network, by default.

Reference:

<https://docs.microsoft.com/en-us/azure/virtual-machines/troubleshooting/troubleshoot-rdp-connection>

NEW QUESTION: 61

You have an Azure subscription that contains the virtual networks shown in the following table. The subscription contains the private DNS zones shown in the following table.

You add virtual network links to the private DNS zones as shown in the following table.

For each of the following statements, select Yes if the statement is true. Otherwise, select No.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/dns/private-dns-virtual-network-links>

<https://docs.microsoft.com/en-us/azure/dns/private-dns-autoregistration>

Valid AZ-104 Dumps shared by Actual4test.com for Helping Passing AZ-104 Exam!

Actual4test.com now offer the **newest AZ-104 exam dumps**, the Actual4test.com AZ-104 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com AZ-104 dumps with Test Engine here:

https://www.actual4test.com/AZ-104_examcollection.html (430 Q&As Dumps, **30%OFF**

Special Discount: Freepdfdumps)

NEW QUESTION: 62

You have an on-premises server that contains a folder named D:\Folder1.

You need to copy the contents of D:\Folder1 to the public container in an Azure Storage account named contoso data.

Which command should you run?

A. `https://contosodata.blob.core.windows.net/public`

B. `azcopy sync D:\folder1 https://contosodata.blob.core.windows.net/public --snapshot`

C. `azcopy copy D:\folder1 https://contosodata.blob.core.windows.net/public --recursive`

D. `az storage blob copy start-batch D:\Folder1 https://`

Answer: ([SHOW ANSWER](#))

`contosodata.blob.core.windows.net/public`

Explanation:

The azcopy copy command copies a directory (and all of the files in that directory) to a blob container. The result is a directory in the container by the same name.

Incorrect Answers:

B: The azcopy sync command replicates the source location to the destination location. However, the file is skipped if the last modified time in the destination is more recent.

D: The az storage blob copy start-batch command copies multiple blobs to a blob container.

Reference:

<https://docs.microsoft.com/en-us/azure/storage/common/storage-use-azcopy-blobs>

<https://docs.microsoft.com/en-us/azure/storage/common/storage-ref-azcopy-copy>

NEW QUESTION: 63

You have an Azure subscription that contains a user account named User1.

You need to ensure that User1 can assign a policy to the tenant root management group.

What should you do?

- A.** Create a new management group and delegate User1 as the owner of the new management group.
- B.** Assign the Owner role for the Azure subscription to User1, and then instruct User1 to configure access management for Azure resources.
- C.** Assign the Owner role for the Azure subscription to User1, and then modify the default conditional access policies.
- D.** Assign the Global administrator role to User1, and then instruct User1 to configure access management for Azure resources.

Answer: B (LEAVE A REPLY)

The following chart shows the list of roles and the supported actions on management groups.

Note:

Each directory is given a single top-level management group called the "Root" management group. This root management group is built into the hierarchy to have all management groups and subscriptions fold up to it. This root management group allows for global policies and Azure role assignments to be applied at the directory level. The Azure AD Global Administrator needs to elevate themselves to the User Access Administrator role of this root group initially. After elevating access, the administrator can assign any Azure role to other directory users or groups to manage the hierarchy. As administrator, you can assign your own account as owner of the root management group.

Reference:

<https://docs.microsoft.com/en-us/azure/governance/management-groups/overview>

NEW QUESTION: 64

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure subscription that contains 10 virtual networks. The virtual networks are hosted in separate resource groups.

Another administrator plans to create several network security groups (NSGs) in the subscription. You need to ensure that when an NSG is created, it automatically blocks TCP port 8080 between the virtual networks.

Solution: From the Resource providers blade, you unregister the Microsoft.ClassicNetwork provider.

Does this meet the goal?

A. Yes

B. No

Answer: B (LEAVE A REPLY)

You should use a policy definition.

Reference:

<https://docs.microsoft.com/en-us/azure/azure-policy/policy-definition>

NEW QUESTION: 65

You need to meet the user requirement for Admin1.

What should you do?

A. From the Subscriptions blade, select the subscription, and then modify the Properties.

B. From the Subscriptions blade, select the subscription, and then modify the Access control (IAM) settings.

C. From the Azure Active Directory blade, modify the Properties.

D. From the Azure Active Directory blade, modify the Groups.

Answer: A (LEAVE A REPLY)

Change the Service administrator for an Azure subscription

Sign in to Account Center as the Account administrator.

Select a subscription.

On the right side, select Edit subscription details.

Scenario: Designate a new user named Admin1 as the service administrator of the Azure subscription.

NEW QUESTION: 66

You have an Azure Subscription that contains the virtual networks Shown in the following table.

All the virtual networks are peered. Each virtual network contains nine virtual machines.

You need to configure secure RDP connections to the virtual machines by using Azure Bastion.

What is the minimum number of Bastion nests required?

A. 1

B. 10

C. 3

D. 9

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 67

You have an Azure subscription named Subscription1. Subscription1 contains two Azure virtual machines named VM1 and VM2. VM1 and VM2 run Windows Server 2016.

VM1 is backed up daily by Azure Backup without using the Azure Backup agent.

VM1 is affected by ransomware that encrypts data.

You need to restore the latest backup of VM1.

To which location can you restore the backup? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/backup/backup-azure-arm-restore-vm>

<https://docs.microsoft.com/en-us/azure/backup/backup-azure-restore-files-from-vm#system-requirements>

NEW QUESTION: 68

You have an Azure subscription that contains three virtual networks named VNet1, VNet2, VNet3. VNet2 contains a virtual appliance named VM2 that operates as a router.

You are configuring the virtual networks in a hub and spoke topology that uses VNet2 as the hub network.

You plan to configure peering between VNet1 and VNet2 and between VNet2 and VNet3.

You need to provide connectivity between VNet1 and VNet3 through VNet2.

Which two configurations should you perform? Each correct answer presents part of the solution.

NOTE: Each correct selection is worth one point.

- A. On the peering connections, allow forwarded traffic.
- B. On the peering connections, allow gateway transit.
- C. Create route tables and assign the table to subnets.
- D. Create a route filter.
- E. On the peering connections, use remote gateways.

Answer: A,C ([LEAVE A REPLY](#))

Allow gateway transit: Check this box if you have a virtual network gateway attached to this virtual network and want to allow traffic from the peered virtual network to flow through the gateway.

The peered virtual network must have the Use remote gateways checkbox checked when setting up the peering from the other virtual network to this virtual network.

Reference:

<https://docs.microsoft.com/en-us/azure/virtual-network/virtual-network-manage-peering#requirements-andconstraints>

NEW QUESTION: 69

You have an Azure subscription that is linked to an Azure AD tenant. The tenant contains the custom role-based access control (RBAC) roles shown in the following table.

From the Azure portal, you need to create two custom roles named Role3 and Role4. Role3 will be an Azure subscription role. Role4 will be an Azure AD role. Which roles can you clone to create the new roles? To answer, select the appropriate options in the answer area.

Answer:

NEW QUESTION: 70

You have an Azure subscription that contains an Azure Storage account storageaccount1.

You export storage account as an Azure Resource Manager template. The template contains the following sections.

For each of the following statements, select Yes if the statement is true. Otherwise, select No.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/templates/microsoft.storage/storageaccounts?tabs=json>

NEW QUESTION: 71

You have an Azure subscription that contains a virtual machine named VM1 and an Azure function named App1. You need to create an alert rule that will run App1 if VM1 stops. What should you create for the alert rule?

- A. an application group
- B. an application security group
- C. an action group
- D. a security group that has dynamic device membership

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 72

You have an Azure subscription that contains the resource groups shown in the following table.

RG1 contains the resources shown in the following table.

RG2 contains the resources shown in the following table.

You need to identify which resources you can move from RG1 to RG2, and which resources you can move from RG2 to RG1.

Which resources should you identify? To answer, select the appropriate options in the answer area.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/governance/blueprints/concepts/resource-locking>

NEW QUESTION: 73

You have an Azure App Service plan that hosts an Azure App Service named App1. You configure one production slot and four staging slots for App1. You need to allocate 10 percent of the traffic to each staging slot and 60 percent of the traffic to the production slot.

What should you add to App1?

- A. slots to the Testing in production blade
- B. a performance test
- C. a WebJob
- D. templates to the Automation script blade

Answer: A (LEAVE A REPLY)

Besides swapping, deployment slots offer another killer feature: testing in production. Just like the name suggests, using this, you can actually test in production. This means that you can route a specific percentage of user traffic to one or more of your deployment slots.

Example:

Reference:

<https://stackify.com/azure-deployment-slots/>

NEW QUESTION: 74

You have an Azure virtual machine named VM1 that runs Windows Server 2019. You save VM1 as a template named Template1 to the Azure Resource Manager library. You plan to deploy a virtual machine named VM2 from Template1.

What can you configure during the deployment of VM2?

- A. virtual machine size
- B. operating system
- C. administrator username
- D. resource group

Answer: C (LEAVE A REPLY)

When deploying a virtual machine from a template, you must specify:

the Resource Group name and location for the VM

the administrator username and password

an unique DNS name for the public IP

Reference:

<https://docs.microsoft.com/en-us/azure/virtual-machines/windows/ps-template>

NEW QUESTION: 75

You have an Azure subscription.

You enable multi-factor authentication for all users.

Some users report that the email applications on their mobile device cannot connect to their Microsoft Exchange Online mailbox. The users can access Exchange Online by using a web browser and from Microsoft Outlook 2016 on their computer.

You need to ensure that the users can use the email applications on their mobile device. What should you instruct the users to do?

- A. Create an app password
- B. Reset the Azure Active Directory (Azure AD) password
- C. Enable self-service password reset
- D. Reinstall the Microsoft Authenticator app

Answer: A (LEAVE A REPLY)

If you're enabled for multi-factor authentication, make sure that you have set up app passwords. Note: During your initial two-factor verification registration process, you're provided with a single app password. If you require more than one, you'll have to create them yourself.

Go to the Additional security verification page.

Reference:

<https://docs.microsoft.com/en-us/office365/troubleshoot/sign-in/sign-in-to-office-365-azure-intune>

<https://docs.microsoft.com/sv-se/azure/active-directory/user-help/multi-factor-authentication-end-user-app-passwords>

NEW QUESTION: 76

You have an Azure subscription that contains the resources shown in the following table.

You need to perform the tasks shown in the following table.

Which tasks can you perform by using Azure Storage Explorer ?

- A. Take1, Take2, Take3, and Take4
- B. Task2, Task3, and Task4 only
- C. Task1 Task2 and Task3 only
- D. Task1. Task2 and Task3 only
- E. Task1 and Task3 only

Answer: E (LEAVE A REPLY)

Valid AZ-104 Dumps shared by Actual4test.com for Helping Passing AZ-104 Exam!

Actual4test.com now offer the **newest AZ-104 exam dumps**, the Actual4test.com AZ-104 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com AZ-104 dumps with Test Engine here:

https://www.actual4test.com/AZ-104_examcollection.html (430 Q&As Dumps, **30%OFF**

Special Discount: Freepdfdumps)

NEW QUESTION: 77

You have an Azure subscription that contains virtual machine named VM1.

You need to back up VM. The solution must ensure that backups are stored across three availability zones in the primary region.

Which three actions should you perform in sequence? To answer, move the appropriate actions from the list of actions to the answer area and arrange them in the correct order.

Answer:

- 1 - Create a Recovery Services vault.
- 2 - For VM1, create a backup policy and configure the backup.
- 3 - Configure a replication policy.

NEW QUESTION: 78

You have an Azure web app named webapp1.

Users report that they often experience HTTP 500 errors when they connect to webapp1.

You need to provide the developers of webapp1 with real-time access to the connection errors.

The solution must provide all the connection error details.

What should you do first?

- A. From webapp1, enable Web server logging
- B. From Azure Monitor, create a workbook
- C. From Azure Monitor, create a Service Health alert
- D. From webapp1, turn on Application Logging

Answer: A (LEAVE A REPLY)

To resolve this you need to catch connection error. When the connection fails for webapp, it happens on web server, not within application. You can find out the web server log by below steps:

Open the web application --> Go to Application Service logs --> Go to Web server logging (there are multiple switches there) You can also see the errors live going to "Log stream" pane.

To ensure that you will get web server log, you have to enable it.

Reference:

<https://docs.microsoft.com/en-us/azure/app-service/troubleshoot-diagnostic-logs>

NEW QUESTION: 79

You develop the following Azure Resource Manager (ARM) template to create a resource group and deploy an Azure Storage account to the resource group.

Which cmdlet should you run to deploy the template?

- A. New-AzResourceGroupDeployment
- B. New-AzDeployment
- C. New-AzResource
- D. new-AzTenantDeployment

Answer: A (LEAVE A REPLY)

<https://learn.microsoft.com/en-us/azure/azure-resource-manager/templates/deploy-to-resource-group?tabs=azure-cli#create-resource-group>

NEW QUESTION: 80

You need to define a custom domain name for Azure AD to support the planned infrastructure.

Which domain name should you use?

- A. Join the client computers in the Miami office to Azure AD.
- B. Add <http://autologon.microsoftazuread-ssocom> to the intranet zone of each client computer in the Miami office.
- C. Allow inbound TCP port 8080 to the domain controllers in the Miami office.
- D. Install Azure AD Connect on a server in the Miami office and enable Pass-through Authentication
- E. Install the Active Directory Federation Services (AD FS) role on a domain controller in the Miami office.

Answer: B,D (LEAVE A REPLY)

Every Azure AD directory comes with an initial domain name in the form of `domainname.onmicrosoft.com`. The initial domain name cannot be changed or deleted, but you can add your corporate domain name to Azure AD as well. For example, your organization probably has other domain names used to do business and users who sign in using your corporate domain name. Adding custom domain names to Azure AD allows you to assign user names in the directory that are familiar to your users, such as 'alice@contoso.com.' instead of 'alice@domain name.onmicrosoft.com'.

Scenario:

Network Infrastructure: Each office has a local data center that contains all the servers for that office. Each office has a dedicated connection to the Internet.

Humongous Insurance has a single-domain Active Directory forest named

`humongousinsurance.com` Planned Azure AD Infrastructure: The on-premises Active Directory domain will be synchronized to Azure AD.

NEW QUESTION: 81

You have an Azure policy as shown in the following exhibit.

What is the effect of the policy?

Which of the following statements are true?

- A. You can create Azure SQL servers in ContosoRG1 only.
- B. You are prevented from creating Azure SQL servers anywhere in Subscription 1.
- C. You are prevented from creating Azure SQL Servers in ContosoRG1 only.
- D. You can create Azure SQL servers in any resource group within Subscription 1.

Answer: (SHOW ANSWER)

You are prevented from creating Azure SQL servers anywhere in Subscription 1 with the exception of ContosoRG1 Reference:

<https://docs.microsoft.com/en-us/azure/governance/policy/concepts/definition-structure>

NEW QUESTION: 82

You have an Azure subscription named Subscription1 that contains a virtual network named VNet1. You add the users in the following table.

Which user can perform each configuration? To answer select the appropriate options in the answer are a. NOTE: Each correct selection is worth one point.

Answer:

NEW QUESTION: 83

You have an Azure AD tenant that is linked to 10 Azure subscriptions. You need to centrally monitor user activity across all the subscriptions. What should you use?

- A. Activity log filters
- B. access reviews
- C. Azure Application Insights Profiler
- D. Log Analytics workspace

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 84

You plan to deploy three Azure virtual machines named VM1, VM2, and VM3. The virtual machines will host a web app named App1.

You need to ensure that at least two virtual machines are available if a single Azure datacenter becomes unavailable.

What should you deploy?

- A. all three virtual machines in a single Availability Zone
- B. all virtual machines in a single Availability Set
- C. each virtual machine in a separate Availability Zone
- D. each virtual machine in a separate Availability Set

Answer: C ([LEAVE A REPLY](#))

<https://docs.microsoft.com/de-de/azure/virtual-machines/windows/tutorial-availability-sets> Each zone is made up of one or more datacenters equipped with independent power, cooling, and networking. To ensure resiliency, there are a minimum of three separate zones in all enabled regions.

NEW QUESTION: 85

You have an Azure subscription named Subscription1 that contains a virtual network named VNet1. VNet1 is in a resource group named RG1.

Subscription1 has a user named User1. User1 has the following roles;

- * Reader
- * Security Admin
- * Security Reader

You need to ensure that User1 can assign the Reader role for VNet1 to other users. What should you do?

- A. Assign User1 the Contributor role for VNet1.
- B. Remove User from the Security Reader and Reader roles tot Subscription1.
- C. Assign User1 the Network Contributor role for VNet1.

D. Assign User1 the User Access Administrator role for VNet1

Answer: D ([LEAVE A REPLY](#))

The User Access Administrator role allows you to manage user access to Azure resources.

Reference:

<https://docs.microsoft.com/en-us/azure/role-based-access-control/built-in-roles#user-access-administrator>

NEW QUESTION: 86

You plan to use Azure Network Watcher to perform the following tasks:

Task1: Identify a security rule that prevents a network packet from reaching an Azure virtual machine

Task2: Validate outbound connectivity from an Azure virtual machine to an external host

Which feature should you use for each task? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/network-watcher/network-watcher-monitoring-overview>

<https://docs.microsoft.com/en-us/azure/network-watcher/network-watcher-ip-flow-verify-overview>

<https://docs.microsoft.com/en-us/azure/network-watcher/network-watcher-connectivity-overview>

NEW QUESTION: 87

You have an Azure subscription named Subscription1.

In Subscription1, you create an Azure web app named WebApp1. WebApp1 will access an external service that requires certificate authentication.

You plan to require the use of HTTPS to access WebApp1.

You need to upload certificates to WebApp1.

In which formats should you upload the certificate? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

NEW QUESTION: 88

You are building a custom Azure function app to connect to Azure Event Grid.

You need to ensure that resources are allocated dynamically to the function app. Billing must be based on the executions of the app.

What should you configure when you create the function app?

A. the Windows operating system and the Consumption plan hosting plan

B. the Windows operating system and the App Service plan hosting plan

C. the Docker container and an App Service plan that uses the B1 pricing tier

D. the Docker container and an App Service plan that uses the S1 pricing

Answer: A ([LEAVE A REPLY](#))

Azure Functions runs in two different modes: Consumption plan and Azure App Service plan. The Consumption plan automatically allocates compute power when your code is running. Your app is scaled out when needed to handle load, and scaled down when code is not running.

Incorrect Answers:

B: When you run in an App Service plan, you must manage the scaling of your function app.

Reference:

<https://docs.microsoft.com/en-us/azure/azure-functions/functions-create-first-azure-function>

NEW QUESTION: 89

You have a resource group named RG1. RG1 contains an Azure Storage account named storageaccount1 and a virtual machine named VM1 that runs Windows Server 2016. Storageaccount1 contains the disk files for VM1. You apply a ReadOnly lock to RG1. What can you do from the Azure portal?

- A. Generate an automation script for RG1.
- B. View the keys of storageaccount1.
- C. Upload a blob to storageaccount1.
- D. Start VM1.

Answer: (SHOW ANSWER)

Applying locks can lead to unexpected results because some operations that don't seem to modify the resource actually require actions that are blocked by the lock. Locks are inherited to all of its resources if it applies on resource group level.

Upload a blob to storageaccount1 is possible if we have readonly lock on RG1 since we are trying to modify the data not resource properties.

When a R/O lock is put on a resource, you lock it's properties not the resource. So while a read only lock is present on a storage account(inherited from a resource group), a file can still be uploaded to the already existing container of a storage account.

Incorrect Answers:

Generate an automation script for RG1 is NOT possible in read only mode.

A read-only lock on a storage account prevents all users from listing the keys. The list keys operation is handled through a POST request because the returned keys are available for write operations. When we tried to read the Access Key of the Storage Account , get the below message.

Access blocked The resource is locked Cannot access the data plane because of a read lock on the resource or its parent.

A read-only lock on a resource group that contains a virtual machine prevents all users from starting or restarting the virtual machine. These operations require a POST request.

Reference:

<https://docs.microsoft.com/en-us/azure/azure-resource-manager/management/lock-resources>

NEW QUESTION: 90

Note: The question is included in a number of questions that depicts the identical set-up. However, every question has a distinctive result. Establish if the solution satisfies the requirements.

Your company has an Azure Active Directory (Azure AD) tenant named weyland.com that is configured for hybrid coexistence with the on-premises Active Directory domain.

You have a server named DirSync1 that is configured as a DirSync server.

You create a new user account in the on-premise Active Directory. You now need to replicate the user information to Azure AD immediately.

Solution: You use Active Directory Sites and Services to force replication of the Global Catalog on a domain controller.

Does the solution meet the goal?

A. No

B. Yes

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 91

You have an existing Azure subscription that contains 10 virtual machines.

You need to monitor the latency between your on-premises network and the virtual machines.

What should you use?

A. Service Map

B. Connection troubleshoot

C. Network Performance Monitor

D. Effective routes

Answer: C ([LEAVE A REPLY](#))

Network Performance Monitor is a cloud-based hybrid network monitoring solution that helps you monitor network performance between various points in your network infrastructure. It also helps you monitor network connectivity to service and application endpoints and monitor the performance of Azure ExpressRoute.

You can monitor network connectivity across cloud deployments and on-premises locations, multiple data centers, and branch offices and mission-critical multitier applications or microservices. With Performance Monitor, you can detect network issues before users complain.

Reference:

<https://docs.microsoft.com/en-us/azure/azure-monitor/insights/network-performance-monitor>

Valid AZ-104 Dumps shared by Actual4test.com for Helping Passing AZ-104 Exam!

Actual4test.com now offer the **newest AZ-104 exam dumps**, the Actual4test.com AZ-104 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com AZ-104 dumps with Test Engine here:

Special Discount: **Freepdfdumps**)

NEW QUESTION: 92

You have the web apps shown in the following table

You need to monitor the performance and usage of the apps by using Azure Application Insights. The solution must minimize modifications to the application code.

What should you do on each app? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer in image

Answer:

NEW QUESTION: 93

You are planning to deploy an Ubuntu Server virtual machine to your company's Azure subscription.

You are required to implement a custom deployment that includes adding a particular trusted root certification authority (CA).

Which of the following should you use to create the virtual machine?

- A. The New-AzureRmVm cmdlet.
- B. The New-AzVM cmdlet.
- C. The Create-AzVM cmdlet.
- D. The az vm create command.

Answer: (SHOW ANSWER)

<https://docs.microsoft.com/en-us/azure/virtual-machines/linux/tutorial-automate-vm-deployment>

NEW QUESTION: 94

You need to define a custom domain name for Azure AD to support the planned infrastructure.

Which domain name should you use?

- A. ad.humongousinsurance.com
- B. humongousinsurance.onmicrosoft.com
- C. humongousinsurance.local
- D. humongousinsurance.com

Answer: D (LEAVE A REPLY)

Every Azure AD directory comes with an initial domain name in the form of domainname.onmicrosoft.com.

The initial domain name cannot be changed or deleted, but you can add your corporate domain name to Azure AD as well. For example, your organization probably has other domain names used to do business and users who sign in using your corporate domain name. Adding custom domain names to Azure AD allows you to assign user names in the directory that are familiar to your users, such as 'alice@contoso.com.' instead of 'alice@domain name.onmicrosoft.com'.

Scenario:

Network Infrastructure: Each office has a local data center that contains all the servers for that office. Each office has a dedicated connection to the Internet.

Humongous Insurance has a single-domain Active Directory forest named

humongousinsurance.com Planned Azure AD Infrastructure: The on-premises Active Directory domain will be synchronized to Azure AD.

Reference:

<https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/add-custom-domain>

NEW QUESTION: 95

Note: The question is included in a number of questions that depicts the identical set-up. However, every question has a distinctive result. Establish if the solution satisfies the requirements.

Your company has an Azure Active Directory (Azure AD) tenant named weyland.com that is configured for hybrid coexistence with the on-premises Active Directory domain.

You have a server named DirSync1 that is configured as a DirSync server.

You create a new user account in the on-premise Active Directory. You now need to replicate the user information to Azure AD immediately.

Solution: You restart the NetLogon service on a domain controller.

Does the solution meet the goal?

A. No

B. Yes

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 96

You have an Azure subscription,

You have an on-premises virtual machine named VM1, The settings for VM" are shown in the exhibit. (Click the Exhibit tab.) You need to ensure that you can use the disks attached to VM' as a template for Azure virtual machines, What should you modify on VM1?

A. the hard drive

B. the processor

C. the network adapters

D. Integration Services

E. the memory

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 97

You have an Azure Storage account named storage1.

You have an Azure App Service app named app1 and an app named App2 that runs in an Azure container instance. Each app uses a managed identity.

You need to ensure that App1 and App2 can read blobs from storage1 for the next 30 days.

What should you configure in storage1 for each app?

Answer:

With Shared access signature you can limit the resources for access and at the same time can control the duration of the access.

A shared access signature (SAS) provides secure delegated access to resources in your storage account without compromising the security of your data. With a SAS, you have granular control over how a client can access your data. You can control what resources the client may access, what permissions they have on those resources, and how long the SAS is valid, among other parameters.

Reference:

<https://docs.microsoft.com/en-us/azure/storage/common/storage-sas-overview>

NEW QUESTION: 98

You have Azure virtual machines that run Windows Server 2019 and are configured as shown in the following table.

You create a public Azure DNS zone named adatum.com and a private Azure DNS zone named contoso.com.

For contoso.com, you create a virtual network link named link1 as shown in the exhibit. (Click the Exhibit tab.)

You discover that VM1 can resolve names in contoso.com but cannot resolve names in adatum.com. VM1 can resolve other hosts on the internet.

You need to ensure that VM1 can resolve host names in adatum.com.

What should you do?

- A. Update the DNS suffix on VM1 to be adatum.com.
- B. Create an SRV record in the contoso.com zone.
- C. Configure the name servers for adatum.com at the domain registrar.
- D. Modify the Access control (IAM) settings for link1.

Answer: C ([LEAVE A REPLY](#))

Explanation

Adatum.com is a public DNS zone. The Internet top level domain DNS servers need to know which DNS servers to direct DNS queries for adatum.com to. You configure this by configuring the name servers for adatum.com at the domain registrar.

Reference:

<https://docs.microsoft.com/en-us/azure/dns/dns-getstarted-portal>

NEW QUESTION: 99

Your VMware vSphere on-premises infrastructure hosts 600 virtual machines (VMs).

Your company is planning to move all of these VMs to Azure. You are asked to provide information about the resources that will be needed in Azure to host all of the VMs.

All VMs hosted in your on-premise infrastructure are based on Windows Server 2012 R2 or newer and RedHat Enterprise Linux 7.0 or newer.

You conduct the initial migration assessment and get a message that some virtual machines are conditionally ready for Azure.

You need to find the cause of this message.

What are two reasons why you might get this message on some VMs? (Choose two) Each correct answer presents part of the solution.

- A. The vCenter user does not have enough permissions on affected VMs.
- B. The operating system is configured as Windows Server 2003 in vCenter Server.
- C. The operating system is configured as Others in vCenter Server.
- D. The VMs are configured with the BIOS boot type.
- E. The VMs are configured with the UEFI boot type.

Answer: B,E (LEAVE A REPLY)

To prepare for VMware VM assessment, you need to:

Verify VMware settings. Make sure that the vCenter Server and VMs you want to migrate meet requirements.

Set up permissions for assessment. Azure Migrate uses a vCenter account to access the vCenter Server, to discover and assess VMs.

Verify appliance requirements. Verify deployment requirements for the Azure Migrate appliance, before you deploy it in the next tutorial.

Reference:

<https://docs.microsoft.com/en-us/azure/migrate/tutorial-prepare-vmware>

NEW QUESTION: 100

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure subscription that contains the following resources:

A virtual network that has a subnet named Subnet1

Two network security groups (NSGs) named NSG-VM1 and NSG-Subnet1

A virtual machine named VM1 that has the required Windows Server configurations to allow Remote Desktop connections NSG-Subnet1 has the default inbound security rules only.

NSG-VM1 has the default inbound security rules and the following custom inbound security rule:

Priority: 100

Source: Any

Source port range: *

Destination: *

Destination port range: 3389

Protocol: UDP

Action: Allow

VM1 connects to Subnet1. NSG1-VM1 is associated to the network interface of VM1. NSG-Subnet1 is associated to Subnet1.

You need to be able to establish Remote Desktop connections from the internet to VM1.

Solution: You modify the custom rule for NSG-VM1 to use the internet as a source and TCP as a protocol.

Does this meet the goal?

A. Yes

B. No

Answer: (SHOW ANSWER)

NSGs deny all inbound traffic except from virtual network or load balancers. For inbound traffic, Azure processes the rules in a network security group associated to a subnet first, and then the rules in a network security group associated to the network interface.

By default NSG rule to allow traffic through RDP port 3389 is not created automatically during the creation of VM , unless you change the setting during creation. Subnets usually do not have any NSG associated unless you go out of the way to do so, which this scenario does. when you create that extra NSG, it won't have an RDP rule by default, thus blocking inbound connections. Request first goes to NSG -subnet1 and as there is no allow rule for RDP so it will block the request by default. Since the Subnet NSG (the one with the default rules) is evaluated first, it blocks the inbound RDP connection.

Reference:

<https://docs.microsoft.com/en-us/azure/virtual-machines/troubleshooting/troubleshoot-rdp-connection>

<https://docs.microsoft.com/en-us/azure/virtual-network/security-overview#default-security-rules>

NEW QUESTION: 101

You have an Azure subscription that contains the resources shown in the following table.

You need to assign User1 the Storage File Data SMB Share Contributor role for share1. What should you do first?

A. Select Default to Azure Active Directory authorization in the Azure portal for storage1.

B. Enable identity-based data access for the file shares in storage1.

C. Configure Access control (IAM) for share1.

D. Modify the security profile for the file shares in storage1.

Answer: C (LEAVE A REPLY)

NEW QUESTION: 102

You have the Azure virtual machines shown in the following table.

VNNET1 is linked to a private DNS zone named contoso.com that contains the records shown in the following table.

Which DNS names can you use to ping VM2?

A. comp1.contoso.com and comp2.contoso.com only

B. comp2.contoso.com and comp4.contoso.com only

- C. comp2.contoso.cam only
- D. comp1.contoso.com, comp2.contoso.com, and comp4.contoso.com only
- E. comp1.contoso.com, comp2.contoso.com, comp3.contoso.com, and comp4.contoso.com

Answer: (SHOW ANSWER)

Reference:

<https://medium.com/azure-architects/exploring-azure-private-dns-be65de08f780>

<https://simplifiedns.plus/help/dns-record-types>

NEW QUESTION: 103

You have an Azure App Service plan named AdatumASP1 that uses the P2v2 pricing tier. AdatumASP1 hosts MI Azure web app named adatumwebapp1. You need to delegate the management of adatumwebapp1 to a group named Devs. Devs must be able to perform the following tasks:

- * Add deployment slots.
- * View the configuration of AdatumASP1.
- * Modify the role assignment for adatumwebapp1.

Which role should you assign to the Devs group?

- A. Owner
- B. Contributor
- C. Web Plan Contributor
- D. Website Contributor

Answer: A (LEAVE A REPLY)

Owner : Correct Choice

The Owner role lets you manage everything, including access to resources.

Contributor : Incorrect Choice

With contributor role you can Add deployment slots and View the configuration of App service plan but you can't Modify the role assignment. For this you need User Access Administrator or Owner role. So this is incorrect.

Web Plan Contributor : Incorrect Choice

The Web Plan Contributor role lets you manage the web plans for websites, but not access to them. So this option is incorrect.

Website Contributor : Incorrect Choice

The Website Contributor role lets you manage websites (not web plans), but not access to them. So this is incorrect option.

Note:

As per least privilege principle it is not advisable to provide owner role to any group, rather you should create custom RBAC role with custom policy and use that role for this operation. However as this option is not available here so only option to go with owner role.

Reference:

<https://docs.microsoft.com/en-us/azure/role-based-access-control/role-assignments-portal>

<https://docs.microsoft.com/en-us/azure/role-based-access-control/built-in-roles>

NEW QUESTION: 104

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You need to ensure that an Azure Active Directory (Azure AD) user named Admin1 is assigned the required role to enable Traffic Analytics for an Azure subscription.

Solution: You assign the Reader role at the subscription level to Admin1.

Does this meet the goal?

A. Yes

B. No

Answer: A (LEAVE A REPLY)

Your account must meet one of the following to enable traffic analytics:

Your account must have any one of the following Azure roles at the subscription scope: owner, contributor, reader, or network contributor.

Reference:

<https://docs.microsoft.com/en-us/azure/network-watcher/traffic-analytics-faq>

NEW QUESTION: 105

You have a sync group that has the endpoints shown in the following table.

Cloud tiering is enabled for Endpoint3.

You add a file named File1 to Endpoint1 and a file named File2 to Endpoint2.

You need to identify on which endpoints File1 and File2 will be available within 24 hours of adding the files.

What should you identify? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/storage/files/storage-sync-cloud-tiering>

NEW QUESTION: 106

You need to meet the connection requirements for the New York office.

What should you do? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/architecture/reference-architectures/hybrid-networking/vpn>

Valid AZ-104 Dumps shared by Actual4test.com for Helping Passing AZ-104 Exam!
Actual4test.com now offer the **newest AZ-104 exam dumps**, the Actual4test.com AZ-104 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com AZ-104 dumps with Test Engine here:

https://www.actual4test.com/AZ-104_examcollection.html (430 Q&As Dumps, **30%OFF**

Special Discount: Freepdfdumps)

NEW QUESTION: 107

You have an Azure subscription that uses the public IP addresses shown in the following table. You need to create a public Azure Standard Load Balancer.

Which public IP addresses can you use?

- A. IP1 and IP3 only
- B. IP1, IP2, and IP3
- C. IP2 only
- D. IP3 only

Answer: D (LEAVE A REPLY)

Matching SKUs are required for load balancer and public IP resources. You can't have a mixture of Basic SKU resources and standard SKU resources.

Reference:

<https://docs.microsoft.com/en-us/azure/virtual-network/ip-services/public-ip-addresses>

NEW QUESTION: 108

You have an Azure subscription named Subscription1 that contains a virtual network named VNet1.

You add the users in the following table.

Which2? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/role-based-access-control/built-in-roles>

NEW QUESTION: 109

You need to recommend a solution to automate the configuration for the finance department users. The solution must meet the technical requirements.

What should you include in the recommended?

- A. Azure AP B2C
- B. Azure AD Identity Protection
- C. an Azure logic app and the Microsoft Identity Management (MIM) client
- D. dynamic groups and conditional access policies

Answer: D (LEAVE A REPLY)

Technically, The finance department needs to migrate their users from AD to AAD using AADC based on the finance OU, and need to enforce MFA use. This is conditional access policy. Employees also often get promotions and/or join other departments and when that occurs, the user's OU attribute will change when the admin puts the user in a new OU, and the dynamic group conditional access exception (OU= [Department Name Value]) will move the user to the appropriate dynamic group on next AADC delta sync.

<https://docs.microsoft.com/en-us/azure/active-directory/enterprise-users/groups-dynamic-membership>

<https://docs.microsoft.com/en-us/azure/active-directory/conditional-access/overview>

<https://docs.microsoft.com/en-us/azure/active-directory/authentication/howto-mfa-userstates>

NEW QUESTION: 110

You have peering configured as shown in the following exhibit.

Use the drop-down menus to select the answer choice that completes each statement based on the information presented in the graphic.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://blog.kloud.com.au/2018/10/19/address-space-maintenance-with-vnet-peering/>

<https://docs.microsoft.com/en-us/azure/virtual-network/virtual-network-manage-peering#requirements-andconstraints>

NEW QUESTION: 111

You have a Basic App Service plan named ASP1 that hosts an Azure App Service named App1. You need to configure a custom domain and enable backups for App1.

What should you do first?

- A. Configure a WebJob for App1.
- B. Scale up ASP1.
- C. Scale out ASP1.
- D. Configure the application settings for App1.

Answer: (SHOW ANSWER)

Scale up ASP1 : Correct

Basic App service plan does not support backup/restore.

The Backup and Restore feature requires the App Service plan to be in the Standard, Premium or Isolated tier. Since in question it is mentioned as a Basic service plan app so at first you need to do it to Scale up the service plan so that backup can be enabled on App1.

Scale up: Get more CPU, memory, disk space, and extra features like dedicated virtual machines (VMs), custom domains and certificates, staging slots, autoscaling, and more. You scale up by changing the pricing tier of the App Service plan that your app belongs to.

Configure a WebJob for App1 : Incorrect

WebJobs is a feature of Azure App Service that enables you to run a program or script in the same instance as a web app, API app, or mobile app. There is no additional cost to use WebJobs
Scale out ASP1 : Incorrect

Scale out: Increase the number of VM instances that run your app. You can scale out to as many as 30 instances, depending on your pricing tier.

Configure the application settings for App1 : Incorrect

This is the 2nd step you need to perform once azure service plan upgraded to standard.

Most folks don't realize how easy it is to configure a backup copy of your Azure App Service to ensure you have restorable archive copies of your app and database. In order to take advantage of this, you'll need to log into your Azure account and go to your App Service that you created and look under Settings then you will see Backup

Reference:

<https://azure.microsoft.com/en-in/pricing/details/app-service/windows/>

<https://docs.microsoft.com/en-us/azure/app-service/manage-scale-up>

<https://docs.microsoft.com/en-us/azure/app-service/webjobs-create>

<https://microsoft.github.io/AzureTipsAndTricks/blog/tip28.html>

NEW QUESTION: 112

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure subscription that contains 10 virtual networks. The virtual networks are hosted in separate resource groups.

Another administrator plans to create several network security groups (NSGs) in the subscription. You need to ensure that when an NSG is created, it automatically blocks TCP port 8080 between the virtual networks.

Solution: You configure a custom policy definition, and then you assign the policy to the subscription.

Does this meet the goal?

A. Yes

B. No

Answer: A ([LEAVE A REPLY](#))

Resource policy definition used by Azure Policy enables you to establish conventions for resources in your organization by describing when the policy is enforced and what effect to take. By defining conventions, you can control costs and more easily manage your resources.

NEW QUESTION: 113

You need to create storage5. The solution must support the planned changes.

Which type of storage account should you use, and which account should you configure as the destination storage account? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/storage/blobs/object-replication-configure?tabs=portal>

NEW QUESTION: 114

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You deploy an Azure Kubernetes Service (AKS) cluster named AKS1.

You need to deploy a YAML file to AKS1.

Solution: From the Azure CLI, you run azcopy.

Does this meet the goal?

A. Yes

B. No

Answer: ([SHOW ANSWER](#))

Kubectl is not installed by installing AZ CLI. As stated Azure CLI is already available but installing Azure CLI doesn't mean that Azure Kubernetes client is also installed. So before running any aks command, we have to install kubectl, the Kubernetes command-line client. az aks install-cli

Reference:

<https://docs.microsoft.com/en-us/azure/aks/kubernetes-walkthrough#connect-to-the-cluster>

NEW QUESTION: 115

You have a Microsoft SQL Server Always On availability group on Azure virtual machines. You need to configure an Azure internal load balancer as a listener for the availability group. What should you do?

A. Enable Floating IP.

B. Set Session persistence to Client IP and protocol.

C. Set Session persistence to Client IP.

D. Create an HTTP health probe on port 1433.

Answer: **A** ([LEAVE A REPLY](#))

Reference:

<https://docs.microsoft.com/en-us/azure/virtual-machines/windows/sql/virtual-machines-windows-portal-sql-alwayson-int-listener>

NEW QUESTION: 116

You have an Azure subscription that contains a resource group named Test RG.

You use TestRG to validate an Azure deployment.

TestRG contains the following resources:

You need to delete TestRG.

What should you do first?

- A. Modify the backup configurations of VM1 and modify the resource lock type of VNET1.
- B. Turn off VM1 and delete all data in Vault1.
- C. Remove the resource lock from VNET1 and delete all data in Vault1.
- D. Turn off VM1 and remove the resource lock from VNET1.

Answer: C (LEAVE A REPLY)

You can't delete a vault that contains backup data. You must remove the delete locks before trying to delete a resource group. When you delete a resource group, all of its resources are also deleted. Deleting a resource group deletes all of its template deployments and currently stored operations. <https://docs.microsoft.com/en-us/azure/azure-resource-manager/management/delete-resource-group?tabs=azure-powershell>

NEW QUESTION: 117

You have an Azure subscription that contains the virtual machines shown in the following table.

javascript:void(0)

You deploy a load balancer that has the following configurations:

- * Name: LB1
- * Type internal
- * SKU: Standard
- * Virtual network VNET1

You need to ensure that you can add VM1 and VM2 to the backend pool of LB1.

Solution: You create a Basic SKU public IP address, associate the address to the network interface of VM1, and then start VM1.

Does this meet the goal?

- A. Yes
- B. No

Answer: B (LEAVE A REPLY)

A Backend Pool configured by IP address has the following limitations:

Standard load balancer only

Reference:

<https://docs.microsoft.com/en-us/azure/load-balancer/backend-pool-management> You can only attach virtual machines in the same region and that have a standard SKU public IP configuration or no public IP configuration. All IP configurations must be on the same virtual network.

NEW QUESTION: 118

You have an Azure subscription that contains an Azure Service Bus named Bus1.

Your company plans to deploy two Azure web apps named App1 and App2. The web apps will create messages that have the following requirements:

Each message created by App1 must be consumed by only a single consumer Each message created by App2 will be consumed by multiple consumers.

Which resource should you create for each web app? To answer, drag the appropriate resources to the correct web apps. Each resource may be used once, more than once, or not at all. You may need to drag the split bar between panes or scroll to view content.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/service-bus-messaging/service-bus-queues-topics-subscriptions>

NEW QUESTION: 119

You have an Azure subscription that contains the following resources:

100 Azure virtual machines

20 Azure SQL databases

50 Azure file shares

You need to create a daily backup of all the resources by using Azure Backup.

What is the minimum number of backup policies that you must create?

- A. 1
- B. 2
- C. 3
- D. 150
- E. 170

Answer: C ([LEAVE A REPLY](#))

There is a limit of 100 VMs that can be associated to the same backup policy from portal. We recommend that for more than 100 VMs, create multiple backup policies with same schedule or different schedule.

One policy for VMS, one for SQL databases, and one for the file shares.

Reference:

<https://docs.microsoft.com/en-us/azure/backup/backup-azure-vm-backup-faq>

NEW QUESTION: 120

You have an Azure subscription that contains two on-premises locations named site1 and site2.

You need to connect site1 and site2 by using an Azure Virtual WAN.

Which four actions should you perform in sequence? To answer, move the appropriate actions from the list of actions to the answer area and arrange them in the correct order.

Answer:

NEW QUESTION: 121

You implement the planned changes for NSG1 and NSG2.

For each of the following statements, select Yes if the statement is true. Otherwise, select No.

NOTE: Each correct selection is worth one point.

Answer:

Valid AZ-104 Dumps shared by Actual4test.com for Helping Passing AZ-104 Exam! Actual4test.com now offer the **newest AZ-104 exam dumps**, the Actual4test.com AZ-104 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com AZ-104 dumps with Test Engine here:

https://www.actual4test.com/AZ-104_examcollection.html (430 Q&As Dumps, **30%OFF**

Special Discount: Freepdfdumps)

NEW QUESTION: 122

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure virtual machine named VM1 that runs Windows Server 2016.

You need to create an alert in Azure when more than two error events are logged to the System log on VM1 within an hour.

Solution: You create an Azure Log Analytics workspace and configure the data settings. You install the Microsoft Monitoring Agent on VM1. You create an alert in Azure Monitor and specify the Log Analytics workspace as the source.

Does this meet the goal?

A. Yes

B. No

Answer: A (LEAVE A REPLY)

Alerts in Azure Monitor can identify important information in your Log Analytics repository. They are created by alert rules that automatically run log searches at regular intervals, and if results of the log search match particular criteria, then an alert record is created and it can be configured to perform an automated response.

The Log Analytics agent collects monitoring data from the guest operating system and workloads of virtual machines in Azure, other cloud providers, and on-premises. It collects data into a Log Analytics workspace.

Reference:

<https://docs.microsoft.com/en-us/azure/azure-monitor/learn/tutorial-response>

<https://docs.microsoft.com/en-us/azure/azure-monitor/platform/agents-overview>

NEW QUESTION: 123

Your company has three offices. The offices are located in Miami, Los Angeles, and New York. Each office contains a datacenter.

You have an Azure subscription that contains resources in the East US and West US Azure regions. Each region contains a virtual network. The virtual networks are peered.

You need to connect the datacenters to the subscription. The solution must minimize network latency between the datacenters.

What should you create?

- A. three virtual WANs and one virtual hub
- B. three virtual hubs and one virtual WAN
- C. three On-premises data gateways and one Azure Application Gateway
- D. three Azure Application Gateways and one On-premises data gateway

Answer: A (LEAVE A REPLY)

Azure Virtual WAN is a networking service that brings many networking, security, and routing functionalities together to provide a single operational interface.

The Virtual WAN architecture is a hub and spoke architecture with scale and performance built in for branches (VPN/SD-WAN devices), users (Azure VPN/OpenVPN/IKEv2 clients), ExpressRoute circuits, and virtual networks.

Azure regions serve as hubs that you can choose to connect to. All hubs are connected in full mesh in a Standard Virtual WAN making it easy for the user to use the Microsoft backbone for any-to-any (any spoke) connectivity.

Virtual WAN offers the following advantages:

Integrated connectivity solutions in hub and spoke: Automate site-to-site configuration and connectivity between on-premises sites and an Azure hub.

Automated spoke setup and configuration: Connect your virtual networks and workloads to the Azure hub seamlessly.

Intuitive troubleshooting: You can see the end-to-end flow within Azure, and then use this information to take required actions.

Reference:

<https://docs.microsoft.com/en-us/azure/virtual-wan/virtual-wan-about>

NEW QUESTION: 124

You have an Azure virtual machine named VM1.

Azure collects events from VM1.

You are creating an alert rule in Azure Monitor to notify an administrator when an error is logged in the System event log of VM1.

You need to specify which resource type to monitor.

What should you specify?

- A. metric alert
- B. Azure Log Analytics workspace
- C. virtual machine
- D. virtual machine extension

Answer: B (LEAVE A REPLY)

Azure Monitor can collect data directly from your Azure virtual machines into a Log Analytics workspace for analysis of details and correlations. Installing the Log Analytics VM extension for Windows and Linux allows Azure Monitor to collect data from your Azure VMs.

Azure Log Analytics workspace is also used for on-premises computers monitored by System Center Operations Manager.

Reference:

<https://docs.microsoft.com/en-us/azure/azure-monitor/learn/quick-collect-azurevm>

NEW QUESTION: 125

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure virtual machine named VM1 that runs Windows Server 2016.

You need to create an alert in Azure when more than two error events are logged to the System log on VM1 within an hour.

Solution: You create an event subscription on VM1. You create an alert in Azure Monitor and specify VM1 as the source.

Does this meet the goal?

A. Yes

B. No

Answer: B (LEAVE A REPLY)

Instead: You create an Azure Log Analytics workspace and configure the data settings. You install the Microsoft Monitoring Agent on VM1. You create an alert in Azure Monitor and specify the Log Analytics workspace as the source.

Reference:

<https://docs.microsoft.com/en-us/azure/azure-monitor/platform/agents-overview>

NEW QUESTION: 126

You have an Azure subscription that contains a user named User1.

You need to ensure that User1 can deploy virtual machines and manage virtual networks. The solution must use the principle of least privilege.

Which role-based access control (RBAC) role should you assign to User1?

A. Owner

B. Virtual Machine Administrator Login

C. Contributor

D. Virtual Machine Contributor

Answer: C (LEAVE A REPLY)

NEW QUESTION: 127

You have an Azure virtual machine named VM1.

The network interface for VM1 is configured as shown in the exhibit (Click the Exhibit tab.)

You deploy a web server on VM1, and then create a secure website that is accessible by using the HTTPS protocol. VM1 is used as a web server only.

You need to ensure that users can connect to the website from the internet.

What should you do?

- A. For Rule4, change the protocol from UDP to Any
- B. Modify the protocol of Rule4.
- C. Modify the action of Rule1.
- D. Change the priority of Rule3 to 450

Answer: ([SHOW ANSWER](#))

Rule 2 is blocking HTTPS access (port 443) and has a priority of 500.

Changing Rule 3 (ports 60-500) and giving it a lower priority number will allow access on port 443.

Note: Rules are processed in priority order, with lower numbers processed before higher numbers, because lower numbers have higher priority. Once traffic matches a rule, processing stops.

Incorrect Answers:

A: HTTPS uses port 443. Rule6 only applies to ports 150 to 300.

C, D: Rule 1 blocks access to port 80, which is used for HTTP, not HTTPS.

Reference:

<https://docs.microsoft.com/en-us/azure/virtual-network/security-overview>

NEW QUESTION: 128

You have an Azure subscription that contains a virtual network named VNet1. VNet1 uses an IP address space of 10.0.0.0/16 and contains the subnets in the following table.

Subnet1 contains a virtual appliance named VM1 that operates as a router.

You create a routing table named RT1.

You need to route all inbound traffic to VNet1 through VM1.

How should you configure RT1? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/virtual-network/manage-route-table#create-a-route-table>

<https://docs.microsoft.com/en-us/azure/network-watcher/network-watcher-next-hop-overview>

NEW QUESTION: 129

You are developing an Azure web app named WebApp1. WebApp1 uses an Azure App Service plan named Plan1 that uses the B1 pricing tier.

You need to configure WebApp1 to add additional instances of the app when CPU usage exceeds 70 percent for 10 minutes.

Which three actions should you perform in sequence? To answer, move the appropriate actions from the list of actions to the answer area and arrange them in the correct order.

Answer:

Reference:

<https://azure.microsoft.com/en-us/pricing/details/app-service/windows/>

<https://blogs.msdn.microsoft.com/hsirtl/2017/07/03/autoscaling-azure-web-apps/>

NEW QUESTION: 130

You have the Azure management groups shown in the following table.

You add Azure subscriptions to the management groups as shown in the following table.

You create the Azure policies shown in the following table.

For each of the following statements, select Yes if the statement is true. Otherwise, select No.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/governance/management-groups/overview>

<https://docs.microsoft.com/en-us/azure/governance/management-groups/manage#moving-management-groups-and-subscriptions>

NEW QUESTION: 131

You create a virtual machine scale set named Scale1. Scale1 is configured as shown in the following exhibit.

Use the drop-down menus to select the answer choice that completes each statement based on the information presented in the graphic.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/azure-monitor/platform/autoscale-overview>

<https://docs.microsoft.com/en-us/azure/azure-monitor/platform/autoscale-best-practices>

<https://docs.microsoft.com/en-us/azure/azure-monitor/platform/autoscale-common-scale-patterns>

NEW QUESTION: 132

You have a service deployed to a Kubernetes cluster.

Another application needs to access the service via the private IP address of the pod.

Which of the following would you define as the networking type for the cluster to meet this requirement?

- A. Kubenet
- B. Azure container networking plugin
- C. Service Endpoints

D. Network security groups

Answer: (SHOW ANSWER)

Azure container networking plugin : Correct Choice

With the Azure container networking plugin , every pod gets an IP address allocated.

With Azure CNI, every pod gets an IP address from the subnet and can be accessed directly.

These IP addresses must be unique across your network space, and must be planned in advance. Each node has a configuration parameter for the maximum number of pods that it supports. The equivalent number of IP addresses per node are then reserved up front for that node. This approach requires more planning, as can otherwise lead to IP address exhaustion or the need to rebuild clusters in a larger subnet as your application demands grow.

Nodes use the Azure Container Networking Interface (CNI) Kubernetes plugin.

Kubenet : Incorrect Choice

The kubenet networking option is the default configuration for AKS cluster creation. With kubenet, nodes get an IP address from the Azure virtual network subnet. Pods receive an IP address from a logically different address space to the Azure virtual network subnet of the nodes.

Service Endpoints : Incorrect Choice

Capabilities like service endpoints or UDRs are supported with both kubenet and Azure CNI, the support policies for AKS define what changes you can make. For example:

* If you manually create the virtual network resources for an AKS cluster, you're supported when configuring your own UDRs or service endpoints.

* If the Azure platform automatically creates the virtual network resources for your AKS cluster, it isn't supported to manually change those AKS-managed resources to configure your own UDRs or service endpoints.

Network security groups : Incorrect Choice

A network security group filters traffic for VMs, such as the AKS nodes. As you create Services, such as a LoadBalancer, the Azure platform automatically configures any network security group rules that are needed.

Reference:

<https://docs.microsoft.com/en-us/azure/aks/concepts-network>

NEW QUESTION: 133

You have an Azure subscription that contains the storage accounts shown in the following table. You need to identify which storage accounts support lifecycle management, and which storage accounts support moving data to the Archive access tier. What should you identify for each requirement? To answer, select the appropriate options in the answer area. NOTE: Each correct answer is worth one point.

Answer:

NEW QUESTION: 134

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution. After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure virtual machine named VM1 that runs Windows Server 2016.

You need to create an alert in Azure when more than two error events are logged to the System log on VM1 within an hour.

Solution: You create an Azure Log Analytics workspace and configure the data settings. You add an extension to VM1. You create an alert in Azure Monitor and specify the Log Analytics workspace as the source.

Does this meet the goal?

A. Yes

B. No

Answer: B (LEAVE A REPLY)

Instead: You create an Azure Log Analytics workspace and configure the data settings. You install the Microsoft Monitoring Agent on VM1. You create an alert in Azure Monitor and specify the Log Analytics workspace as the source.

Reference:

<https://docs.microsoft.com/en-us/azure/azure-monitor/platform/agents-overview>

NEW QUESTION: 135

You have an Azure Storage account named storage1 that stores images.

You need to create a new storage account and replicate the images in storage1 to the new account by using object replication.

How should you configure the new account? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

NEW QUESTION: 136

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution. After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an app named App1 that is installed on two Azure virtual machines named VM1 and VM2. Connections to App1 are managed by using an Azure Load Balancer.

The effective network security configurations for VM2 are shown in the following exhibit.

You discover that connections to App1 from 131.107.100.50 over TCP port 443 fail. You verify that the Load Balancer rules are configured correctly.

You need to ensure that connections to App1 can be established successfully from 131.107.100.50 over TCP port 443.

Solution: You modify the priority of the Allow_131.107.100.50 inbound security rule.

Does this meet the goal?

A. Yes

B. No

Answer: B (LEAVE A REPLY)

The rule currently has the highest priority.

Reference:

<https://fastreroute.com/azure-network-security-groups-explained/>

Allow_131.107.100.50 rule already has the highest priority.

<https://docs.microsoft.com/en-us/azure/virtual-network/network-security-groups-overview>

Valid AZ-104 Dumps shared by Actual4test.com for Helping Passing AZ-104 Exam!

Actual4test.com now offer the **newest AZ-104 exam dumps**, the Actual4test.com AZ-104 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com AZ-104 dumps with Test Engine here:

https://www.actual4test.com/AZ-104_examcollection.html (430 Q&As Dumps, **30%OFF**

Special Discount: Freepdfdumps)

NEW QUESTION: 137

You have an Azure subscription that contains a storage account named storageacct1234 and two users named User1 and User2.

You assign User1 the roles shown in the following exhibit.

Which two actions can User1 perform? Each correct answer presents a complete solution. NOTE: Each correct selection is worth one point.

- A. Upload blob data to storageacct1234.
- B. View file shares in storageacct1234.
- C. Modify the firewall of storageacct1234.
- D. View blob data in storageacct1234.
- E. Assign roles to User2 for storageacct1234.

Answer: A,E (LEAVE A REPLY)

NEW QUESTION: 138

You have an Azure subscription that contains the resources in the following table.

To which subnets can you apply NSG1?

- A. the subnets on VNet1 only
- B. the subnets on VNet2 only
- C. the subnets on VNet3 only

D. the subnets on VNet2, VNet2, and VNet3

E. the subnets on VNet2 and VNet3 only

Answer: C (LEAVE A REPLY)

All Azure resources are created in an Azure region and subscription. A resource can only be created in a virtual network that exists in the same region and subscription as the resource.

Reference:

<https://docs.microsoft.com/en-us/azure/virtual-network/virtual-network-vnet-plan-design-arm>

NEW QUESTION: 139

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution. After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have a computer named Computer1 that has a point-to-site VPN connection to an Azure virtual network named VNet1. The point-to-site connection uses a self-signed certificate.

From Azure, you download and install the VPN client configuration package on a computer named Computer2.

You need to ensure that you can establish a point-to-site VPN connection to VNet1 from Computer2.

Solution: You export the client certificate from Computer1 and install the certificate on Computer2.

Does this meet this goal?

A. Yes

B. No

Answer: A (LEAVE A REPLY)

Each client computer that connects to a VNet using Point-to-Site must have a client certificate installed. You generate a client certificate from the self-signed root certificate, and then export and install the client certificate. If the client certificate is not installed, authentication fails.

Reference:

<https://docs.microsoft.com/en-us/azure/vpn-gateway/vpn-gateway-certificates-point-to-site>

NEW QUESTION: 140

You have an Azure subscription that has a Recovery Services vault named Vault1. The subscription contains the virtual machines shown in the following table.

You plan to schedule backups to occur every night at 23:00.

Which virtual machines can you back up by using Azure Backup?

A. VM1 only

B. VM1 and VM3 only

C. VM1, VM2, VM3 and VM4

D. VM1 and VM2 only

Answer: (SHOW ANSWER)

Azure Backup supports backup of 64-bit Windows server operating system from Windows Server 2008.

Azure Backup supports backup of 64-bit Windows 10 operating system.

Azure Backup supports backup of 64-bit Ubuntu Server operating system from Ubuntu 12.04.

Azure Backup supports backup of VM that are shutdown or offline.

Reference:

<https://docs.microsoft.com/en-us/azure/backup/backup-support-matrix-iaas>

<https://docs.microsoft.com/en-us/azure/virtual-machines/linux/endorsed-distros>

NEW QUESTION: 141

You have an Azure subscription that is linked to an Azure AD tenant. The tenant contains two users named User1 and User2. The subscription contains the resources shown in the following table.

The subscription contains the alert rules shown in the following table.

The users perform the following actions:

* User1 creates a new virtual disk and attaches the disk to VM1.

* User2 creates a new resource tag and assigns the tag to RG1 and VM1.

Which alert rules are triggered by each user? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

NEW QUESTION: 142

You have an Azure Active Directory (Azure AD) tenant named contoso.com that contains the users shown in the following table:

User3 is the owner of Group1.

Group2 is a member of Group1.

You configure an access review named Review1 as shown in the following exhibit:

For each of the following statements, select Yes if the statement is true. Otherwise, select No.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/active-directory/governance/create-access-review>

NEW QUESTION: 143

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You manage a virtual network named VNet1 that is hosted in the West US Azure region. VNet1 hosts two virtual machines named VM1 and VM2 that run Windows Server. You need to inspect all the network traffic from VM1 to VM2 for a period of three hours. Solution: From Azure Network Watcher, you create a packet capture.

Does this meet the goal?

A. Yes

B. No

Answer: A (LEAVE A REPLY)

<https://azure.microsoft.com/en-us/updates/general-availability-azure-network-watcher-connection-monitor-in-all-public-regions/>

NEW QUESTION: 144

You have the Azure virtual machines shown in the following table.

VNET1, VNET2, and VNET3 are peered.

VM4 has a DNS server that is authoritative for a zone named Contoso.com and contains the records shown in the following table.

VNET1 and VNET2 are linked to an Azure private DNS zone named Contoso.com that contains the records shown in the following table.

The virtual networks are configured to use the DNS servers shown in the following table.

For each of the following statements, select Yes if the statement is true. Otherwise, select No.

NOTE: Each correct selection is worth one point.

Answer:

NEW QUESTION: 145

You are deploying a containerized web application in Azure.

When deploying the web app, which of the following are valid container image sources?

A. Virtual machine

B. Docker hub

C. ACR

D. On-premises

Answer: B,C (LEAVE A REPLY)

When you create a web app from a Docker image, you configure the following properties:

* The registry that contains the image. The registry can be Docker Hub, Azure Container Registry (ACR), or some other private registry.

* The image :This item is the name of the repository.

* The tag : This item indicates which version of the image to use from the repository. By convention, the most recent version is given the tag latest when it's built.

* Startup File :This item is the name of an executable file or a command to be run when the image is loaded. It's equivalent to the command that you can supply to Docker when running an image from the command line by using docker run. If you're deploying a ready-to-run, containerized app

that already has the ENTRYPOINT and/or COMMAND values configured, you don't need to fill this in.

Reference:

<https://docs.microsoft.com/en-us/learn/modules/deploy-run-container-app-service/4-deploy-web-app>

NEW QUESTION: 146

Your network contains an on-premises Active Directory domain named adatum.com. The domain contains an organizational unit (OU) named OU1. OU1 contains the objects shown in the following table.

You sync OU1 to Azure Active Directory (Azure AD) by using Azure AD Connect.

You need to identify which objects are synced to Azure AD.

Which objects should you identify?

- A. User1 and Group1 only
- B. User1, Group1, and Group2 only
- C. User1, Group1, Group2, and Computer1
- D. Computer1 only

Answer: B (LEAVE A REPLY)

Reference:

<https://docs.microsoft.com/en-us/azure/active-directory-domain-services/synchronization>

NEW QUESTION: 147

You have an Azure Storage account named storage1.

You plan to use AzCopy to copy data to storage1.

You need to identify the storage services in storage1 to which you can copy the data.

What should you identify?

- A. blob, file, table, and queue
- B. blob and file only
- C. file and table only
- D. file only
- E. blob, table, and queue only

Answer: B (LEAVE A REPLY)

AzCopy is a command-line utility that you can use to copy blobs or files to or from a storage account.

Incorrect Answers:

A, C, E: AzCopy does not support table and queue storage services.

D: AzCopy supports file storage services, as well as blob storage services.

Reference:

<https://docs.microsoft.com/en-us/azure/storage/common/storage-use-azcopy-v10>

NEW QUESTION: 148

You have an Azure subscription that contains the resources shown in the following table.

VM1 connects to VNET1.

You need to connect VM1 to VNET2.

Solution: You create a new network interface, and then you add the network interface to VM1.

Does this meet the goal?

A. Yes

B. No

Answer: B (LEAVE A REPLY)

Instead you should delete VM1. You recreate VM1, and then you add the network interface for VM1.

Note: When you create an Azure virtual machine (VM), you must create a virtual network (VNet) or use an existing VNet. You can change the subnet a VM is connected to after it's created, but you cannot change the VNet.

Reference:

<https://docs.microsoft.com/en-us/azure/virtual-machines/windows/network-overview>

NEW QUESTION: 149

You have a general purpose v1 storage account named storageaccount1 that has a private container named container1. You need to allow read access to the data inside container1, but only within a 14 day window. How do you accomplish this?

A. Create a stored access policy

B. Create a service SAS

C. Create a shared access signatures

D. Upgrade the storage account to general purpose v2

Answer: (SHOW ANSWER)

Explanation

A Stored Access Policy allows granular control over a single storage container using a Shared Access Signature (SAS).

A Shared Access Signature (SAS) allows you to have granular control over your storage account, including access to only certain services (i.e. Azure Blobs) and permitting only read, write, delete, list, add, or create access.

NEW QUESTION: 150

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You need to ensure that an Azure Active Directory (Azure AD) user named Admin1 is assigned the required role to enable Traffic Analytics for an Azure subscription.

Solution: You assign the Traffic Manager Contributor role at the subscription level to Admin1.

A. Yes

B. No

Answer: (SHOW ANSWER)

Explanation

With Traffic Manager Contributor role you can manage Traffic Manager profiles, do traffic analysis but does not let you control who has access to them.

Reference:

<https://docs.microsoft.com/en-us/azure/network-watcher/traffic-analytics>

<https://docs.microsoft.com/en-us/azure/role-based-access-control/built-in-roles>

NEW QUESTION: 151

You have an Azure Active Directory (Azure AD) tenant named contoso.com. Multi-factor authentication (MFA) is enabled for all users.

You need to provide users with the ability to bypass MFA for 10 days on devices to which they have successfully signed in by using MFA.

What should you do?

A. From the multi-factor authentication page, configure the users' settings.

B. From Azure AD, create a conditional access policy.

C. From the multi-factor authentication page, configure the service settings.

D. From the MFA blade in Azure AD, configure the MFA Server settings.

Answer: C (LEAVE A REPLY)

Enable remember Multi-Factor Authentication

Sign in to the Azure portal.

On the left, select Azure Active Directory > Users.

Select Multi-Factor Authentication.

Under Multi-Factor Authentication, select service settings.

On the Service Settings page, manage remember multi-factor authentication, select the Allow users to remember multi-factor authentication on devices they trust option.

Set the number of days to allow trusted devices to bypass two-step verification. The default is 14 days.

Select Save.

Reference:

<https://docs.microsoft.com/en-us/azure/active-directory/authentication/howto-mfa-mfasettings>

Valid AZ-104 Dumps shared by Actual4test.com for Helping Passing AZ-104 Exam!

Actual4test.com now offer the **newest AZ-104 exam dumps**, the Actual4test.com AZ-104 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com AZ-104 dumps with Test Engine here:

Special Discount: **Freepdfdumps**)

NEW QUESTION: 152

You need to move the blueprint files to Azure.

What should you do?

- A. Generate a shared access signature (SAS). Map a drive, and then copy the files by using File Explorer.
- B. Use the Azure Import/Export service.
- C. Generate an access key. Map a drive, and then copy the files by using File Explorer.
- D. Use Azure Storage Explorer to copy the files.

Answer: D (LEAVE A REPLY)

Azure Storage Explorer is a free tool from Microsoft that allows you to work with Azure Storage data on Windows, macOS, and Linux. You can use it to upload and download data from Azure blob storage.

Scenario:

Planned Changes include: move the existing product blueprint files to Azure Blob storage.

Technical Requirements include: Copy the blueprint files to Azure over the Internet.

NEW QUESTION: 153

You have an Azure Active Directory (Azure AD) tenant named Tenant1 and an Azure subscription named You enable Azure AD Privileged Identity Management.

You need to secure the members of the Lab Creator role. The solution must ensure that the lab creators request access when they create labs.

What should you do first?

- A. From Azure AD Privileged Identity Management, edit the role settings for Lab Creator.
- B. From Subscription1 edit the members of the Lab Creator role.
- C. From Azure AD Identity Protection, creates a user risk policy.
- D. From Azure AD Privileged Identity Management, discover the Azure resources of Conscription.

Answer: A (LEAVE A REPLY)

As a Privileged Role Administrator you can:

Enable approval for specific roles

Specify approver users and/or groups to approve requests

View request and approval history for all privileged roles

Reference:

<https://docs.microsoft.com/en-us/azure/active-directory/privileged-identity-management/pim-configure>

NEW QUESTION: 154

Your on-premises network contains a VPN gateway.

You have an Azure subscription that contains the resources shown in the following table.

You need to ensure that all the traffic from VM1 to storage! travels across the Microsoft backbone network.

What should you configure?

- A. Azure Firewall
- B. Azure AD Application Proxy
- C. Azure Peering Service
- D. private endpoints

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 155

You need to configure an Azure web app named contoso.azurewebsites.net to host wwwcontoso.com.

What should you do first?

- A. Create a TXT record named wwsv.contoso.com that has a value of contosoazurewebsites.net.
- B. Create a TXT record named asuid that contains the domain verification ID.
- C. Create a CNAME record named asuid that contains the domain verification ID.
- D. Create A records named www.contoso.com and asuid.contoso.com.

Answer: D ([LEAVE A REPLY](#))

<https://learn.microsoft.com/en-us/azure/dns/dns-web-sites-custom-domain>

NEW QUESTION: 156

Note: This question is part of a series of questions that present the same scenario goals. Some question sets might have more than one correct solution, while others in the series contains a unique solution that might meet the stated not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure web app named Appl. App1 runs in an Azure App Service plan named Plan1. Plan1 is associated to the Free pricing tier.

You discover that App1 stops each day after running continuously for 60 minutes.

You need to ensure that App1 can run continuously for the entire day.

Solution: You add a triggered WebJob to App1.

Does this meet the goal?

- A. Yes
- B. No

Answer: B ([LEAVE A REPLY](#))

You need to change to Basic pricing Tier.

Note: The Free Tier provides 60 CPU minutes / day. This explains why App1 is stops. The Basic tier has no such cap.

Reference:

<https://azure.microsoft.com/en-us/pricing/details/app-service/windows/>

NEW QUESTION: 157

You need to configure the alerts for VM1 and VM2 to meet the technical requirements. Which three actions should you perform in sequence? To answer, move all actions from the list of actions to the answer area and arrange them in the correct order.

Answer:

- 1 - Create an alert rule.
- 2 - Create an Azure SQL database.
- 3 - Collect Windows performance counters from the Log Analytics agents.

NEW QUESTION: 158

You have an Azure subscription that contains 100 virtual machines. You regularly create and delete virtual machines. You need to identify unattached disks that can be deleted. What should you do?

- A. From Microsoft Azure Storage Explorer, view the Account Management properties.
- B. From Azure Cost Management, create a Cost Management report.
- C. From the Azure portal, configure the Advisor recommendations.

Answer: A ([LEAVE A REPLY](#))

Explanation

You can find unused disks in the Azure Storage Explorer console. Once you drill down to the Blob containers under a storage account, you can see the lease state of the residing VHD (the lease state determines if the VHD is being used by any resource) and the VM to which it is leased out. If you find that the lease state and the VM fields are blank, it means that the VHD in question is unused. The screenshot below shows two active VHDs being used by VMs as data and OS disks. The name of the VM and lease state are shown in the "VM Name" and "Lease State" columns, respectively.

Reference:

<https://cloud.netapp.com/blog/reduce-azure-storage-costs>

NEW QUESTION: 159

You need to deploy two Azure web apps named WebApp1 and WebApp2. The web apps have the following requirements:

WebApp1 must be able to use staging slots

WebApp2 must be able to access the resources located on an Azure virtual network What is the least costly plan that you can use to deploy each web app? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://azure.microsoft.com/en-au/pricing/details/app-service/windows/>

<https://azure.microsoft.com/en-gb/pricing/details/app-service/plans/>

NEW QUESTION: 160

You have an on-premises network that you plan to connect to Azure by using a site-to-site VPN. In Azure, you have an Azure virtual network named VNet1 that uses an address space of 10.0.0.0/16. VNet1 contains a subnet named Subnet1 that uses an address space of 10.0.0.0/24. You need to create a site-to-site VPN to Azure.

Which four actions should you perform in sequence? To answer, move the appropriate actions from the list of actions to the answer area and arrange them in the correct order.

NOTE: More than one order of answer choices is correct. You will receive credit for any of the correct orders you select.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/vpn-gateway/vpn-gateway-howto-site-to-site-resource-manager-portal>

NEW QUESTION: 161

You plan to move services from your on-premises network to Azure.

You identify several virtual machines that you believe can be hosted in Azure. The virtual machines are shown in the following table.

Which two virtual machines can you access by using Azure migrate? Each correct answer presents a complete solution.

NOTE: Each correct selection is worth one point.

- A. Sea-CA01
- B. Hou-NW01
- C. NYC-FS01
- D. Sea-DC01
- E. BOS-DB01

Answer: ([SHOW ANSWER](#))

Azure Migrate provides a centralized hub to assess and migrate to Azure on-premises servers, infrastructure, applications, and data. It provides the following:

Unified migration platform: A single portal to start, run, and track your migration to Azure.

Range of tools: A range of tools for assessment and migration. Azure Migrate tools include Server Assessment and Azure Migrate: Server Migration. Azure Migrate also integrates with other Azure services and tools, and with independent software vendor (ISV) offerings.

Assessment and migration: In the Azure Migrate hub, you can assess and migrate:

Servers: Assess on-premises servers and migrate them to Azure virtual machines or Azure VMware Solution (AVS) (Preview).

Databases: Assess on-premises databases and migrate them to Azure SQL Database or to SQL Managed Instance.

Web applications: Assess on-premises web applications and migrate them to Azure App Service by using the Azure App Service Migration Assistant.

Virtual desktops: Assess your on-premises virtual desktop infrastructure (VDI) and migrate it to Windows Virtual Desktop in Azure.

Data: Migrate large amounts of data to Azure quickly and cost-effectively using Azure Data Box products.

Based on this information let's analyze each option:

NYC-FS01 : Its role "Server" fall under above categories. Hence it can be accessed by using Azure migrate.

BOS-DB01 : Its role "server" fall under above categories. Hence it can be accessed by using Azure migrate.

Sea-CA01 : Its role "CA" does not fall under above categories. Hence it can not be accessed by using Azure migrate.

Hou-NW01 : Its role "DNS" does not fall under above categories. Hence it can not be accessed by using Azure migrate.

Sea-DC01 : Its role "DC" does not fall under above categories. Hence it can not be accessed by using Azure migrate.

Reference:

<https://docs.microsoft.com/en-us/azure/migrate/migrate-services-overview>

NEW QUESTION: 162

You have an Azure Active Directory (Azure AD) tenant that has the initial domain name.

You have a domain name of contoso.com registered at a third-party registrar.

You need to ensure that you can create Azure AD users that have names containing a suffix of @contoso.com.

Which three actions should you perform in sequence? To answer, move the appropriate cmdlets from the list of cmdlets to the answer area and arrange them in the correct order.

Answer:

- 1 - Add a custom domain name.
- 2 - Add a record to the public contoso.com DNS zone.
- 3 - Verify the domain.

NEW QUESTION: 163

You have an Active Directory forest named contoso.com.

You install and configure Azure AD Connect to use password hash synchronization as the single sign-on (SSO) method. Staging mode is enabled.

You review the synchronization results and discover that the Synchronization Service Manager does not display any sync jobs.

You need to ensure that the synchronization completes successfully.

What should you do?

- A. From Synchronization Service Manager, run a full import.
- B. Run Azure AD Connect and set the SSO method to Pass-through Authentication.
- C. From Azure PowerShell, run Start-AdSyncSyncCycle -PolicyType Initial.

D. Run Azure AD Connect and disable staging mode.

Answer: D (LEAVE A REPLY)

Staging mode must be disabled. If the Azure AD Connect server is in staging mode, password hash synchronization is temporarily disabled.

NEW QUESTION: 164

You have an Azure resource manager template that will be used to deploy 10 Azure Web Apps.

You have to ensure to deploy the pre-requisites before the deployment of the template.

You have to minimize the costs associated with the implementation.

Which of the following would you deploy as pre-requisites?

A. An Azure Load Balancer

B. An Application Gateway

C. 10 Azure App Service Plans

D. One App Service Plan

Answer: (SHOW ANSWER)

In App Service (Web Apps, API Apps, or Mobile Apps), an app always runs in an App Service plan. An App Service plan defines a set of compute resources for a web app to run.

One App Service Plan : Correct Choice

For an Azure Web App, you need to have an Azure App Service Plan in place. You can associate multiple Azure Web Apps with the same App Service Plan. Hence to save on costs, you can just have one Azure App Service Plan in place.

An Azure Load Balancer : Incorrect Choice

An Azure load balancer is a Layer-4 (TCP, UDP) load balancer that provides high availability by distributing incoming traffic among healthy VMs. A load balancer health probe monitors a given port on each VM and only distributes traffic to an operational VM An Application Gateway :

Incorrect Choice Azure Application Gateway is a web traffic load balancer that enables you to manage traffic to your web applications. Traditional load balancers operate at the transport layer (OSI layer 4 - TCP and UDP) and route traffic based on source IP address and port, to a destination IP address and port.

10 Azure App Service Plans : Incorrect Choice

For an Azure Web App, you need to have an Azure App Service Plan in place. You can associate multiple Azure Web Apps with the same App Service Plan. Hence to save on costs, you can just have one Azure App Service Plan in place. So there is no need for 10 App Service Plans.

Reference:

<https://docs.microsoft.com/en-us/azure/app-service/overview-hosting-plans>

<https://docs.microsoft.com/en-us/azure/virtual-machines/windows/tutorial-load-balancer>

<https://docs.microsoft.com/en-us/azure/application-gateway/overview>

NEW QUESTION: 165

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution. After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure virtual machine named VM1. VM1 was deployed by using a custom Azure Resource Manager template named ARM1.json.

You receive a notification that VM1 will be affected by maintenance.

You need to move VM1 to a different host immediately.

Solution: From the Redeploy blade, you click Redeploy.

Does this meet the goal?

A. Yes

B. No

Answer: (SHOW ANSWER)

When you redeploy a VM, it moves the VM to a new node within the Azure infrastructure and then powers it back on, retaining all your configuration options and associated resources.

NEW QUESTION: 166

You need to ensure that VM1 can communicate with VM4. The solution must minimize administrative effort.

What should you do?

A. Create a user-defined route from VNET1 to VNET3.

B. Assign VM4 an IP address of 10.0.1.5/24.

C. Establish peering between VNET1 and VNET3.

D. Create an NSG and associate the NSG to VMI and VM4.

Answer: (SHOW ANSWER)

Reference:

<https://docs.microsoft.com/en-us/azure/vpn-gateway/tutorial-site-to-site-portal>

Valid AZ-104 Dumps shared by Actual4test.com for Helping Passing AZ-104 Exam!

Actual4test.com now offer the **newest AZ-104 exam dumps**, the Actual4test.com AZ-104 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com AZ-104 dumps with Test Engine here:

https://www.actual4test.com/AZ-104_examcollection.html (430 Q&As Dumps, **30%OFF**

Special Discount: Freepdfdumps)

NEW QUESTION: 167

You plan to deploy the resources shown in the following table.

You need to create a single Azure Resource Manager (ARM) template that will be used to deploy the resources.

Which resource should be added to the depends On section for VM1?

- A. IP1
- B. NSG1
- C. VNET1
- D. NIC 1

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 168

You have an Azure subscription that contains the resources shown in the following table.

You plan to create a data collection rule named DCRI in Azure Monitor.

Which resources can you set as data sources in DCRI, and which resources can you set as destinations in DCRI? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

NEW QUESTION: 169

You purchase a new Azure subscription named Subscription1.

You create a virtual machine named VM1 in Subscription1. VM1 is not protected by Azure Backup.

You need to protect VM1 by using Azure Backup. Backups must be created at 01:00 and stored for 30 days.

What should you do? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/backup/backup-configure-vault>

<https://docs.microsoft.com/en-us/azure/backup/backup-azure-backup-faq>

A Recovery Services vault is a storage entity in Azure that houses data

a. The data is typically copies of data, or configuration information for virtual machines (VMs), workloads, servers, or workstations. You can use Recovery Services vaults to hold backup data for various Azure services such as IaaS VMs (Linux or Windows) and Azure SQL databases.

You can use backup policy to configure schedule.

<https://docs.microsoft.com/en-us/azure/backup/backup-azure-recovery-services-vault-overview>

<https://docs.microsoft.com/en-us/azure/backup/backup-azure-vms-first-look-arm>

<https://docs.microsoft.com/en-us/azure/backup/backup-azure-recovery-services-vault-overview>

<https://docs.microsoft.com/en-us/azure/backup/backup-azure-vms-first-look-arm>

NEW QUESTION: 170

You have an Azure virtual machine named VM1 and a Recovery Services vault named Vault1.

You create a backup Policy1 as shown in the exhibit. (Click the Exhibit tab.)

You configure the backup of VM1 to use Policy1 on Thursday, January 1.

You need to identify the number of available recovery points for VM1.

How many recovery points are available on January 8 and on January 15? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

NEW QUESTION: 171

You have five Azure virtual machines that run Windows Server 2016. The virtual machines are configured as web servers.

You have an Azure load balancer named LB1 that provides load balancing services for the virtual machines.

You need to ensure that visitors are serviced by the same web server for each request.

What should you configure?

- A. Floating IP (direct server return) to Enabled
- B. Idle Time-out (minutes) to 20
- C. Protocol to UDP
- D. Session persistence to Client IP and Protocol

Answer: ([SHOW ANSWER](#))

With Sticky Sessions when a client starts a session on one of your web servers, session stays on that specific server. To configure An Azure Load-Balancer For Sticky Sessions set Session persistence to Client IP or to Client IP and protocol.

On the following image you can see sticky session configuration:

Note:

§ Client IP and protocol specifies that successive requests from the same client IP address and protocol combination will be handled by the same virtual machine.

§ Client IP specifies that successive requests from the same client IP address will be handled by the same virtual machine.

Reference:

<https://cloudopszone.com/configure-azure-load-balancer-for-sticky-sessions/>

NEW QUESTION: 172

You have an Azure subscription named Subscription1. Subscription1 contains the resource groups in the following table.

RG1 has a web app named WebApp1. WebApp1 is located in West Europe.

You move WebApp1 to RG2.

What is the effect of the move?

- A. The App Service plan to WebApp1 moves to North Europe. Policy2 applies to WebApp1.
- B. The App Service plan to WebApp1 moves to North Europe. Policy1 applies to WebApp1.
- C. The App Service plan to WebApp1 remains to West Europe. Policy2 applies to WebApp1.

D. The App Service plan to WebApp1 remains to West Europe. Policy1 applies to WebApp1.

Answer: C (LEAVE A REPLY)

You can move an app to another App Service plan, as long as the source plan and the target plan are in the same resource group and geographical region.

The region in which your app runs is the region of the App Service plan it's in. However, you cannot change an App Service plan's region.

NEW QUESTION: 173

You have Azure subscriptions named Subscription1 and Subscription2.

Subscription1 has following resource groups:

RG1 includes a web app named App1 in the West Europe location.

Subscription2 contains the following resource groups:

For each of the following statements, select Yes if the statement is true. Otherwise, select No.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/azure-resource-manager/management/move-limitations/app-service-move-limitations>

NEW QUESTION: 174

You are evaluating the connectivity between the virtual machines after the planned implementation of the Azure networking infrastructure.

For each of the following statements, select Yes if the statement is true. Otherwise, select No.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/virtual-network/virtual-network-peering-overview>

<https://docs.microsoft.com/en-us/azure/networking/networking-overview#internet-connectivity>

NEW QUESTION: 175

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure subscription that contains the virtual machines shown in the following table.

You deploy a load balancer that has the following configurations:

Name: LB1

Type: Internal

SKU: Standard

Virtual network: VNET1

You need to ensure that you can add VM1 and VM2 to the backend pool of LB1.

Solution: You create a Standard SKU public IP address, associate the address to the network interface of VM1, and then stop VM2.

Does this meet the goal?

A. Yes

B. No

Answer: B (LEAVE A REPLY)

A Backend Pool configured by IP address has the following limitations:

Standard load balancer only

Reference:

<https://docs.microsoft.com/en-us/azure/load-balancer/backend-pool-management>

NEW QUESTION: 176

You have an Azure subscription that contains a virtual machine scale set. The scale set contains four instances that have the following configurations:

Operating system: Windows Server 2016

Size: Standard_D1_v2

You run the get-azvmss cmdlet as shown in the following exhibit:

Use the drop-down menus to select the answer choice that completes each statement based on the information presented in the graphic.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/virtual-machine-scale-sets/virtual-machine-scale-sets-upgrade-scale-set>

<https://docs.microsoft.com/en-us/azure/virtual-machine-scale-sets/virtual-machine-scale-sets-automatic-upgrade>

NEW QUESTION: 177

You have an on-premises network that includes a Microsoft SQL Server instance named SQL1.

You create an Azure Logic App named App1.

You need to ensure that App1 can query a database on SQL1.

Which three actions should you perform in sequence? To answer, move the appropriate actions from the list of actions to the answer area and arrange them in the correct order.

Answer:

1 - From an on-premises computer, install an on-premises data gateway.

2 - From the Azure portal, create an on-premises data gateway

3 - From the Logic Apps Designer in the Azure portal, add a connector

Reference:

<https://docs.microsoft.com/en-us/azure/logic-apps/logic-apps-gateway-connection>

NEW QUESTION: 178

You have an Azure subscription.

You have an on-premises virtual machine named VM1. The settings for VM1 are shown in the exhibit. (Click the Exhibit button.)

You need to ensure that you can use the disks attached to VM1 as a template for Azure virtual machines.

What should you modify on VM1?

- A. Integration Services
- B. the network adapters
- C. the memory
- D. the hard drive
- E. the processor

Answer: (SHOW ANSWER)

From the exhibit we see that the disk is in the VHDX format.

Before you upload a Windows virtual machines (VM) from on-premises to Microsoft Azure, you must prepare the virtual hard disk (VHD or VHDX). Azure supports only generation 1 VMs that are in the VHD file format and have a fixed sized disk. The maximum size allowed for the VHD is 1,023 GB. You can convert a generation 1 VM from the VHDX file system to VHD and from a dynamically expanding disk to fixed-sized.

Reference:

<https://docs.microsoft.com/en-us/azure/virtual-machines/windows/prepare-for-upload-vhd-image?toc=%2fazure%2fvirtual-machines%2fwindows%2ftoc.json>

NEW QUESTION: 179

You have an Azure subscription named Subscription1 that contains the following resource group:

Name: RG1

Region: West US

Tag: "tag1": "value1"

You assign an Azure policy named Policy1 to Subscription1 by using the following configurations:

Exclusions: None

Policy definition: Append tag and its default value

Assignment name: Policy1

Parameters:

- Tag name: Tag2

- Tag value: Value2

After Policy1 is assigned, you create a storage account that has the following configurations:

Name: storage1

Location: West US

Resource group: RG1

Tags: "tag3": "value3"

You need to identify which tags are assigned to each resource.

What should you identify? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/azure-resource-manager/resource-group-using-tags>

NEW QUESTION: 180

You manage a virtual network named VNet1 that is hosted in the West US region. Two virtual machines named VM1 and VM2, both running Windows Server, are on VNet1. You need to monitor traffic between VM1 and VM2 for a period of five hours.

As a solution, you propose to create a connection monitor in Azure Network Watcher. Does this solution meet the goal?

A. Yes

B. No

Answer: A (LEAVE A REPLY)

The connection monitor capability in Azure Network Watcher monitors communication at a regular interval and informs you of reachability, latency, and network topology changes between the VM and the endpoint.

NEW QUESTION: 181

This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure subscription named Subscription1 that contains the resources shown in the following table.

VM1 connects to a virtual network named VNET2 by using a network interface named NIC1.

You need to create a new network interface named NIC2 for VM1.

Solution: You create NIC2 in RG1 and Central US.

Does this meet the goal?

A. Yes

B. No

Answer: B (LEAVE A REPLY)

The virtual machine you attach a network interface to and the virtual network you connect it to must exist in the same location, here West US, also referred to as a region.

Reference:

<https://docs.microsoft.com/en-us/azure/virtual-network/virtual-network-network-interface>

Valid AZ-104 Dumps shared by Actual4test.com for Helping Passing AZ-104 Exam!
Actual4test.com now offer the **newest AZ-104 exam dumps**, the Actual4test.com AZ-104 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com AZ-104 dumps with Test Engine here:

https://www.actual4test.com/AZ-104_examcollection.html (430 Q&As Dumps, **30%OFF**

Special Discount: Freepdfdumps)

NEW QUESTION: 182

You have an Azure subscription that contains the resource groups shown in the following table. RG1 contains the resources shown in the following table.

Answer:

NEW QUESTION: 183

You have an Azure subscription that contains the following resources:

- * a virtual network named VNet1
- * a replication policy named ReplPolicy1
- * a Recovery Services vault named Vault1
- * an Azure Storage account named Storage1

You have an Amazon Web Services (AWS) EC2 virtual machine named VM1 that runs Windows Server 2019.

You need to migrate VM1 to VNet1 by using Azure Site Recovery.

Which three actions should you perform in sequence? To answer, move the appropriate actions from the list of actions to the answer area and arrange them in the correct order.

Answer:

- 1 - Deploy an EC2 virtual machine as a configuration server
- 2 - Install Azure Site Recovery Unified Setup.
- 3 - Enable replication for VM1.

Reference:

<https://docs.microsoft.com/en-us/azure/site-recovery/migrate-tutorial-aws-azure>

NEW QUESTION: 184

You have an Azure subscription that contains the resources in the following table.

You install the Web Server server role (IIS) on VM1 and VM2, and then VM1 and VM2 to LB1.

LB1 is configured as shown in the LB1 exhibit. (Click the LB1 tab.)

Rule1 is configure as shown in the Rule1 exhibit. (Click the Rule tab.) For each of the following statements, select Yes if the statements is true. Otherwise, select No.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/load-balancer/skus>

<https://docs.microsoft.com/en-us/azure/load-balancer/load-balancer-custom-probe-overview>

NEW QUESTION: 185

You create a Recovery Services vault backup policy named Policy1 as shown in the following exhibit:

Use the drop-down menus to select the answer choice that completes each statement based on the information presented in the graphic.

NOTE: Each correct selection is worth one point.

Answer:

NEW QUESTION: 186

You plan to move a distributed on-premises app named App1 to an Azure subscription.

After the planned move, App1 will be hosted on several Azure virtual machines.

You need to ensure that App1 always runs on at least eight virtual machines during planned Azure maintenance.

What should you create?

- A. one virtual machine scale set that has 12 virtual machines instances
- B. one virtual machine scale set that has 10 virtual machines instances
- C. one Availability Set that has 10 update domains and one fault domain
- D. one Availability Set that has three fault domains and one update domain

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 187

You have an Azure subscription named Subscription1.

You have 5 TB of data that you need to transfer to Subscription1.

You plan to use an Azure Import/Export job.

What can you use as the destination of the imported data?

- A. Azure Data Lake Store
- B. a virtual machine
- C. the Azure File Sync Storage Sync Service
- D. Azure Blob storage

Answer: ([SHOW ANSWER](#))

Azure Import/Export service is used to securely import large amounts of data to Azure Blob storage and Azure Files by shipping disk drives to an Azure datacenter.

The maximum size of an Azure Files Resource of a file share is 5 TB.

Reference:

<https://docs.microsoft.com/en-us/azure/storage/common/storage-import-export-service>

NEW QUESTION: 188

You have an Azure subscription named Subscription1.

You have 5 TB of data that you need to transfer to Subscription1.

You plan to use an Azure Import/Export job.

What can you use as the destination of the imported data?

- A. an Azure Cosmos DB database
- B. Azure File Storage
- C. the Azure File Sync Storage Sync Service
- D. Azure Data Factory

Answer: B (LEAVE A REPLY)

Azure Import/Export service is used to securely import large amounts of data to Azure Blob storage and Azure Files by shipping disk drives to an Azure datacenter.

The maximum size of an Azure Files Resource of a file share is 5 TB.

Reference:

<https://docs.microsoft.com/en-us/azure/storage/common/storage-import-export-service>

NEW QUESTION: 189

Your company registers a domain name of contoso.com.

You create an Azure DNS named contoso.com and then you add an A record to the zone for a host named www that has an IP address of 131.107.1.10.

You discover that Internet hosts are unable to resolve www.contoso.com to the 131.107.1.10 IP address.

You need to resolve the name resolution issue.

Solution: You modify the name server at the domain registrar.

Does this meet the goal?

- A. Yes
- B. No

Answer: B (LEAVE A REPLY)

Reference:

<https://docs.microsoft.com/en-us/azure/dns/dns-delegate-domain-azure-dns>

NEW QUESTION: 190

You have an Azure subscription that contains two resource groups named RG1 and RG2. RG2 does not contain any resources. RG1 contains the resources in the following table.

Which resource can you move to RG2?

- A. W10_OsDisk
- B. VNet1
- C. VNet3
- D. W10

Answer: (SHOW ANSWER)

When moving a virtual network, you must also move its dependent resources. For example, you must move gateways with the virtual network. VM W10, which is in Vnet1, is not a dependent resource.

Incorrect Answers:

A: Managed disks don't support move.

C: Virtual networks (classic) can't be moved.

D: Virtual machines with the managed disks cannot be moved.

NEW QUESTION: 191

You have an Azure subscription named Subscription1 that contains the resources shown in the following table.

You plan to configure Azure Backup reports for Vault1.

You are configuring the Diagnostics settings for the AzureBackupReports log.

Which storage accounts and which Log Analytics workspaces can you use for the Azure Backup reports of Vault1? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

NEW QUESTION: 192

You have an Azure subscription named Subscription1 that contains the quotas shown in the following table.

javascript:void(0)

You deploy virtual machine to Subscription1 as shown in the following table.

javascript:void(0)

You plan to deploy the virtual machines shown in the following table.

javascript:void(0)

For each of the following statements, select Yes if the statement is true. Otherwise, select No.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/virtual-machines/windows/quotas>

NEW QUESTION: 193

You have an Azure virtual machine that runs Windows Server 2019 and has the following configurations:

Name: VM1

Location: West US

Connected to: VNET1

Private IP address: 10.1.0.4

Public IP address: 52.186.85.63

DNS suffix in Windows Server: Adatum.com

You create the Azure DNS zones shown in the following table.

You need to identify which DNS zones you can link to VNET1 and the DNS zones to which VM1 can automatically register.

Which zones should you identify? To answer, select the appropriate options in the answer area.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/dns/private-dns-overview>

NEW QUESTION: 194

You have an Azure subscription that contains eight virtual machines and the resources shown in the following table.

You need to configure access for VNET1. The solution must meet the following requirements:

- * The virtual machines connected to VNET1 must be able to communicate with the virtual machines connected to VNET2 by using the Microsoft backbone.
- * The virtual machines connected to VNET1 must be able to access storage1, storage2 and Azure AD by using the Microsoft backbone.

What is the minimum number of service endpoints you should add to VNET1?

- A. 3
- B. 1
- C. 2
- D. 5

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 195

You have an Azure subscription that contains a storage account.

You have an on-premises server named Server1 that runs Window Server 2016. Server1 has 2 TB of data.

You need to transfer the data to the storage account by using the Azure Import/Export service.

In which order should you perform the actions? To answer, move all actions from the list of actions to the answer area and arrange them in the correct order.

NOTE: More than one order of answer choices is correct. You will receive credit for any of the correct orders you select.

Answer:

- 1 - Attach an external disk to Server1 and then run waimportexport.exe
- 2 - From the Azure portal, create an import job.
- 3 - Detach the external disks from Server1 and ship the disks to an Azure data center.
- 4 - From the Azure portal, update the import job

Reference:

<https://docs.microsoft.com/en-us/azure/storage/common/storage-import-export-service>

NEW QUESTION: 196

Your company has several departments. Each department has a number of virtual machines (VMs).

The company has an Azure subscription that contains a resource group named RG1.

All VMs are located in RG1.

You want to associate each VM with its respective department.

What should you do?

A. Create Azure Management Groups for each department.

B. Create a resource group for each department.

C. Assign tags to the virtual machines.

D. Modify the settings of the virtual machines.

Answer: C (LEAVE A REPLY)

Reference:

<https://docs.microsoft.com/en-us/azure/azure-resource-manager/resource-group-using-tags>

Valid AZ-104 Dumps shared by Actual4test.com for Helping Passing AZ-104 Exam!

Actual4test.com now offer the **newest AZ-104 exam dumps**, the Actual4test.com AZ-104 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com AZ-104 dumps with Test Engine here:

https://www.actual4test.com/AZ-104_examcollection.html (430 Q&As Dumps, **30%OFF**

Special Discount: Freepdfdumps)

NEW QUESTION: 197

You have Azure subscription that includes following Azure file shares:

You have the following on-premises servers:

You create a Storage Sync Service named Sync1 and an Azure File Sync group named Group1.

Group1 uses share1 as a cloud endpoint.

You register Server1 and Server2 in Sync1. You add D:\Folder1 on Server1 as a server endpoint of Group1.

For each of the following statements, select Yes if the statement is true. Otherwise, select No.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/storage/file-sync/file-sync-server-endpoint-create?tabs=azure-portal>

NEW QUESTION: 198

You have an Azure subscription named Subscription1. Subscription1 contains a virtual machine named VM1.

You have a computer named Computer1 that runs Windows 10. Computer1 is connected to the Internet.

You add a network interface named Interface1 to VM1 as shown in the exhibit (Click the Exhibit button.)

From Computer1, you attempt to connect to VM1 by using Remote Desktop, but the connection fails.

You need to establish a Remote Desktop connection to VM1.

What should you do first?

- A. Start VM1.
- B. Attach a network interface.
- C. Delete the DenyAllOutBound outbound port rule.
- D. Delete the DenyAllInBound inbound port rule.

Answer: A (LEAVE A REPLY)

Note: Rules are processed in priority order, with lower numbers processed before higher numbers, because lower numbers have higher priority. Once traffic matches a rule, processing stops. As a result, any rules that exist with lower priorities (higher numbers) that have the same attributes as rules with higher priorities are not processed.

NEW QUESTION: 199

You plan to deploy an Azure container instance by using the following Azure Resource Manager template.

Use the drop-down menus to select the answer choice that completes each statement based on the information presented in the template.

Answer:

Reference:

<https://docs.microsoft.com/en-us/cli/azure/container?view=azure-cli-latest>

<https://docs.docker.com/config/containers/start-containers-automatically/>

NEW QUESTION: 200

You have several Azure virtual machines on a virtual network named VNet1.

You configure an Azure Storage account as shown in the following exhibit.

Use the drop-down menus to select the answer choice that completes each statement based on the information presented in the graphic.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/storage/common/storage-private-endpoints>

<https://azure.microsoft.com/en-us/blog/azure-backup-now-supports-storage-accounts-secured-with-azurestorage-firewalls-and-virtual-networks/>

NEW QUESTION: 201

You have an Azure subscription named Subscription' that contains an Azure Log Analytics workspace named Workspace', You need to view the error events from a table named Event. Which query should you run in Workspace1?

- A. Event | where EventType is "error"
- B. search in (Event) * | where EventType -eq "error"
- C. select * from Event where EventType is "error"
- D. search in (Event) "error"

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 202

You have an Azure subscription.

You need to deploy a virtual machine by using an Azure Resource Manager (ARM) template.

How should you complete the template? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

NEW QUESTION: 203

Your on-premises network contains an SMB share named Share1.

You have an Azure subscription that contains the following resources:

A web app named webapp1

A virtual network named VNET1

You need to ensure that webapp1 can connect to Share1.

What should you deploy?

- A. an Azure Application Gateway
- B. an Azure Active Directory (Azure AD) Application Proxy
- C. an Azure Virtual Network Gateway

Answer: ([SHOW ANSWER](#))

A Site-to-Site VPN gateway connection can be used to connect your on-premises network to an Azure virtual network over an IPsec/IKE (IKEv1 or IKEv2) VPN tunnel.

This type of connection requires a VPN device, a VPN gateway, located on-premises that has an externally facing public IP address assigned to it.

Reference:

<https://docs.microsoft.com/en-us/azure/vpn-gateway/vpn-gateway-howto-site-to-site-resource-manager-portal>

NEW QUESTION: 204

You have an Azure subscription named Subscription1 that contains the resources shown in the following table.

In storage1, you create a blob container named blob1 and a file share named share1.

Which resources can be backed up to Vault1 and Vault2? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/bs-cyrl-ba/azure/backup/backup-create-rs-vault>

<https://docs.microsoft.com/en-us/azure/backup/backup-afs>

NEW QUESTION: 205

You have an Azure subscription that contains the resources shown in the following table.

You need to load balance HTTPS connections to vm1 and vm2 by using lb1.

Which three actions should you perform in sequence? To answer, move the appropriate actions from the list of actions to the answer area and arrange them in the correct order.

Answer:

1 - Remove the public IP addresses from vm1 and vm2.

2 - Create a health probe and backend pool on lb1.

3 - Create a load balancing rule on lb1.

Reference:

<https://docs.microsoft.com/en-us/azure/load-balancer/tutorial-load-balancer-standard-public-zone-redundant-portal>

NEW QUESTION: 206

You are the global administrator for an Azure Active Directory (Azure AD) tenant named adatum.com.

You need to enable two-step verification for Azure users.

What should you do?

A. Configure a playbook in Azure AD conditional access policy.

B. Create an Azure AD conditional access policy.

C. Create and configure the Identify Hub.

D. Install and configure Azure AD Connect.

Answer: B (LEAVE A REPLY)

Conditional Access policies enforce registration, requiring unregistered users to complete registration at first sign-in, an important security consideration.

Reference:

<https://docs.microsoft.com/en-us/azure/active-directory/authentication/howto-mfa-getstarted>

NEW QUESTION: 207

You have an Azure virtual machine that runs Windows Server 2019 and has the following configurations:

Name: VM1

Location: West US

Connected to: VNET1

Private IP address: 10.1.0.4

Public IP addresses: 52.186.85.63

DNS suffix in Windows Server: Adatum.com

You create the Azure DNS zones shown in the following table.

You need to identify which DNS zones you can link to VNET1 and the DNS zones to which VM1 can automatically register.

Which zones should you identify? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/dns/private-dns-overview>

NEW QUESTION: 208

You have a Recovery Service vault that you use to test backups. The test backups contain two protected virtual machines.

You need to delete the Recovery Services vault.

What should you do first?

- A. From the Recovery Service vault, stop the backup of each backup item.
- B. From the Recovery Service vault, delete the backup data.
- C. Modify the disaster recovery properties of each virtual machine.
- D. Modify the locks of each virtual machine.

Answer: A (LEAVE A REPLY)

You can't delete a Recovery Services vault if it is registered to a server and holds backup data. If you try to delete a vault, but can't, the vault is still configured to receive backup data.

Remove vault dependencies and delete vault

In the vault dashboard menu, scroll down to the Protected Items section, and click Backup Items. In this menu, you can stop and delete Azure File Servers, SQL Servers in Azure VM, and Azure virtual machines.

NEW QUESTION: 209

You have an Azure subscription that contains the Azure virtual machines shown in the following table.

You configure the network interfaces of the virtual machines to use the settings shown in the following table

From the settings of VNET1, you configure the DNS servers shown in the following exhibit.

The virtual machines can successfully connect to the DNS server that has an IP address of 192.168.10.15 and the DNS server that has an IP address of 193.77.134.10.

For each of the following statements, select Yes if the statement is true. Otherwise, select No.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/virtual-network/virtual-networks-faq#name-resolution-dns>

NEW QUESTION: 210

You have an Azure subscription.

You plan to deploy a storage account named storage1 by using the following Azure Resource Manager (ARM) template.

Answer:

NEW QUESTION: 211

You have two Azure App Service apps named App1 and App2. Each app has a production deployment slot and a test deployment slot. The Backup Configuration settings for the production slots are shown in the following table.

For each of the following statements, select Yes if the statement is true. Otherwise, select No.

Answer:

Valid AZ-104 Dumps shared by Actual4test.com for Helping Passing AZ-104 Exam! Actual4test.com now offer the **newest AZ-104 exam dumps**, the Actual4test.com AZ-104 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com AZ-104 dumps with Test Engine here:

https://www.actual4test.com/AZ-104_examcollection.html (430 Q&As Dumps, **30%OFF**

Special Discount: Freepdfdumps)

NEW QUESTION: 212

You have an Azure Active Directory (Azure AD) tenant.

You plan to delete multiple users by using Bulk delete in the Azure Active Directory admin center.

You need to create and upload a file for the bulk delete.

Which user attributes should you include in the file?

- A. The user principal name and usage location of each user only
- B. The user principal name of each user only
- C. The display name of each user only
- D. The display name and usage location of each user only
- E. The display name and user principal name of each user only

Answer: B ([LEAVE A REPLY](#))

Reference:

<https://docs.microsoft.com/en-us/azure/active-directory/enterprise-users/users-bulk-delete>

NEW QUESTION: 213

You plan to create an Azure virtual machine named VM1 that will be configured as shown in the following exhibit.

The planned disk configurations for VM1 are shown in the following exhibit.

You need to ensure that VM1 can be created in an Availability Zone.

Which two settings should you modify? Each correct answer presents part of the solution.

NOTE: Each correct selection is worth one point.

- A. Use managed disks
- B. Availability options
- C. OS disk type
- D. Size
- E. Image

Answer: A,C ([LEAVE A REPLY](#))

Reference:

<https://docs.microsoft.com/en-us/azure/site-recovery/move-azure-vms-avset-azone>

<https://docs.microsoft.com/en-us/azure/virtual-machines/windows/create-portal-availability-zone>

NEW QUESTION: 214

You have an Azure Active Directory (Azure AD) tenant named Contoso.com that is synced to an Active Directory domain.

The tenant contains the users shown in the following table.

The user have the attributes shown in the following table.

You need to ensure that you can enable Azure Multi-Factor Authentication (MFA) for all four users.

Solution: You create a new user account in Azure AD for User3.

Does this meet the goal?

- A. Yes
- B. No

Answer: A ([LEAVE A REPLY](#))

User3 requires a user account in Azure AD.

Note: Your Azure AD password is considered an authentication method. It is the one method that cannot be disabled.

Reference:

<https://docs.microsoft.com/en-us/azure/active-directory/authentication/concept-authentication-methods>

NEW QUESTION: 215

You have an Azure subscription named Subscription1 that contains the quotas shown in the following table.

You deploy virtual machines to Subscription1 as shown in the following table.

Answer:

NEW QUESTION: 216

You have an Azure subscription.

You need to implement a custom policy that meet the following requirements:

*Ensures that each new resource group in the subscription has a tag named organization set to a value of Contoso.

*Ensures that resource group can be created from the Azure portal.

*Ensures that compliance reports in the Azure portal are accurate.

How should you complete the policy? To answer, select the appropriate options in the answers area.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/governance/policy/concepts/definition-structure>

<https://docs.microsoft.com/en-us/azure/role-based-access-control/custom-roles>

<https://docs.microsoft.com/en-us/azure/governance/policy/concepts/effects>

NEW QUESTION: 217

You have an Azure subscription. The subscription contains a virtual machine that runs Windows 10.

You need to join the virtual machine to an Active Directory domain.

How should you complete the Azure Resource Manager (ARM) template? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:**NEW QUESTION: 218**

You have an Azure subscription.

You deploy a virtual machine scale set that is configure as shown in the following exhibit.

Answer:**NEW QUESTION: 219**

You onboard 10 Azure virtual machines to Azure Automation State Configuration.

You need to use Azure Automation State Configuration to manage the ongoing consistency of the virtual machine configurations.

Which three actions should you perform in sequence? To answer, move the appropriate actions from the list of actions to the answer area and arrange them in the correct order.

NOTE: More than one order of answer choices is correct. You will receive credit for any of the correct orders you select.

Answer:

1 - Upload a configuration to Azure Automation State Configuration.

2 - Compile a configuration into a node configuration.

3 - Assign the node configuration

Reference:

<https://docs.microsoft.com/en-us/azure/automation/automation-dsc-getting-started>

NEW QUESTION: 220

You have an Azure subscription that contains an Azure Directory (Azure AD) tenant named contoso.com. The tenant is synced to the on-premises Active Directory domain. The domain contains the users shown in the following table.

You enable self-service password reset (SSPR) for all users and configure SSPR to have the following authentication methods:

Number of methods required to reset: 2

Methods available to users: Mobile phone, Security questions

Number of questions required to register: 3

Number of questions required to reset: 3

You select the following security questions:

What is your favorite food?

In what city was your first job?

What was the name of your first pet?

For each of the following statements, select Yes if the statement is true. Otherwise, select No.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/active-directory/authentication/howto-sspr-deployment>

NEW QUESTION: 221

You need to identify which storage account to use for the flow logging of IP traffic from VM5. The solution must meet the retention requirements.

Which storage account should you identify?

A. storage3

B. storage4

C. storage1

D. storage2

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 222

You have an Azure subscription that contains the resources in the following table.

Store1 contains a File share named data. Data contains 5,000 files.

You need to synchronize the files in the file share named data to an on-premises server named Server1.

Which three actions should you perform? Each correct answer presents part of the solution.

- A. Download an automation script.
- B. Create a container instance.
- C. Create a sync group.
- D. Register Server1.
- E. Install the Azure File Sync agent on Server1.

Answer: C,D,E (LEAVE A REPLY)

Step 1 (E): Install the Azure File Sync agent on Server1

The Azure File Sync agent is a downloadable package that enables Windows Server to be synced with an Azure file share Step 2 (D): Register Server1.

Register Windows Server with Storage Sync Service

Registering your Windows Server with a Storage Sync Service establishes a trust relationship between your server (or cluster) and the Storage Sync Service.

Step 3 (C): Create a sync group and a cloud endpoint.

A sync group defines the sync topology for a set of files. Endpoints within a sync group are kept in sync with each other. A sync group must contain one cloud endpoint, which represents an Azure file share and one or more server endpoints. A server endpoint represents a path on registered server.

NEW QUESTION: 223

You have an Azure subscription. You need to transfer 34TB of data from an on-premise Windows 2016 server to your Azure storage account. You need to ensure that the data transfer has zero impact on the network, preserves your existing drives and is the fastest and most secure method. What should be your first step?

- A. Start an Import Job via the Azure Portal
- B. Order an Azure Databox via the Azure Portal
- C. Open a ticket with Microsoft Support
- D. Prepare your hard drives using the WAImportExport tool

Answer: B (LEAVE A REPLY)

The Microsoft Azure Data Box cloud solution lets you send terabytes of data into and out of Azure in a quick, inexpensive, and reliable way.

<https://docs.microsoft.com/en-us/azure/databox/data-box-overview>

NEW QUESTION: 224

Note: The question is included in a number of questions that depicts the identical set-up. However, every question has a distinctive result. Establish if the solution satisfies the requirements.

Your company has an Azure Active Directory (Azure AD) tenant named weyland.com that is configured for hybrid coexistence with the on-premises Active Directory domain.

You have a server named DirSync1 that is configured as a DirSync server.

You create a new user account in the on-premise Active Directory. You now need to replicate the user information to Azure AD immediately.

Solution: You run the Start-ADSyncSyncCycle -PolicyType Initial PowerShell cmdlet.

Does the solution meet the goal?

A. Yes

B. No

Answer: ([SHOW ANSWER](#))

Reference:

<https://blog.kloud.com.au/2016/03/08/azure-ad-connect-manual-sync-cycle-with-powershell-start-adsyncsynccycle/>

NEW QUESTION: 225

You have an Azure subscription that contains an Azure file share.

You have an on-premises server named Server1 that runs Windows Server 2016.

You plan to set up Azure File Sync between Server1 and the Azure file share.

You need to prepare the subscription for the planned Azure File Sync.

Which two actions should you perform in the Azure subscription? To answer, drag the appropriate actions to the correct targets. Each action may be used once, more than once, or not at all. You may need to drag the split bar between panes or scroll to view content.

Answer:

1 - Create a Storage Sync Service

2 - Create a sync group

Reference:

<https://docs.microsoft.com/en-us/azure/storage/files/storage-sync-files-deployment-guide?tabs=azure-portal>

NEW QUESTION: 226

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You manage a virtual network named VNet1 that is hosted in the West US Azure region.

VNet1 hosts two virtual machines named VM1 and VM2 that run Windows Server.

You need to inspect all the network traffic from VM1 to VM2 for a period of three hours.

Solution: From Azure Monitor, you create a metric on Network in and Network Out.

Does this meet the goal?

A. Yes

B. No

Answer: ([SHOW ANSWER](#))

You should use Azure Network Watcher.

Reference:

<https://docs.microsoft.com/en-us/azure/network-watcher/network-watcher-monitoring-overview>

Valid AZ-104 Dumps shared by Actual4test.com for Helping Passing AZ-104 Exam!
Actual4test.com now offer the **newest AZ-104 exam dumps**, the Actual4test.com AZ-104 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com AZ-104 dumps with Test Engine here:
https://www.actual4test.com/AZ-104_examcollection.html (430 Q&As Dumps, **30%OFF**
Special Discount: Freepdfdumps)

NEW QUESTION: 227

You have an Azure subscription that contains 10 virtual machines, a key vault named Vault 1, and a network security group (NSG) named NSG1. All the resources are deployed to the East US Azure region.

The virtual machines are protected by using NSG1. NSG1 is configured to block all outbound traffic to the internet.

You need to ensure that the virtual machines can access Vault1. The solution must use the principle of least privilege and minimize administrative effort.

What should you configure as the destination of the outbound security rule for NSG1 ?

- A. an application security group
- B. an IP address range
- C. a service tag

Answer: C (LEAVE A REPLY)

NEW QUESTION: 228

You have two Azure virtual machines named VM1 and VM2. You have two Recovery Services vaults named RSV1 and RSV2.

VM2 is protected by RSV1.

You need to use RSV2 to protect VM2.

What should you do first?

- A. From the RSV1 blade, click Backup items and stop the VM2 backup.
- B. From the RSV1 blade, click Backup Jobs and export the VM2 backup.
- C. From the RSV1 blade, click Backup. From the Backup blade, select the backup for the virtual machine, and then click Backup.
- D. From the VM2 blade, click Disaster recovery, click Replication settings, and then select RSV2 as the Recovery Services vault.

Answer: (SHOW ANSWER)

The Azure Site Recovery service contributes to your disaster recovery strategy by managing and orchestrating replication, failover, and failback of on-premises machines and Azure virtual machines (VMs).

Reference:

<https://docs.microsoft.com/en-us/azure/site-recovery/azure-to-azure-quickstart>

<https://docs.microsoft.com/en-us/azure/site-recovery/azure-to-azure-tutorial-enable-replication>

NEW QUESTION: 229

You have an Azure App Service plan named AdatumASP1 that hosts several Azure web apps. You discover that the web apps respond slowly.

You need to provide additional memory and CPU resources to each instance of the web apps. What should you do?

- A. Add continuous WebJob that use the multi-instance scale
- B. Scale out AdatumASP1
- C. Add a virtual machine scale set
- D. Scale up AdatumASP1

Answer: D (LEAVE A REPLY)

Reference:

<https://github.com/MicrosoftDocs/azure-docs/blob/master/articles/app-service/web-sites-scale.md>

Scale up : Correct Choice Scale up: Get more CPU, memory, disk space, and extra features like dedicated virtual machines (VMs), custom domains and certificates, staging slots, autoscaling, and more. You scale up by changing the pricing tier of the App Service plan that your app belongs to.

Scale out : Incorrect Choice

Scale out: Increase the number of VM instances that run your app. You can scale out to as many as 30 instances, depending on your pricing tier. App Service Environments in Isolated tier further increases your scale-out count to 100 instances. For more information about scaling out, see Scale instance count manually or automatically.

Add continuous WebJobs : Incorrect Choice

WebJobs is a feature of Azure App Service that enables you to run a program or script in the same instance as a web app, API app, or mobile app. Add continuous WebJobs will Starts immediately when the WebJob is created. To keep the job from ending, the program or script typically does its work inside an endless loop. If the job does end, you can restart it. Starts only when triggered manually or on a schedule.

Add a virtual machine scale set : Incorrect Choice

A virtual machine scale set allows you to deploy and manage a set of identical, autoscaling virtual machines. You can scale the number of VMs in the scale set manually. You can also define rules to autoscale based on resource usage such as CPU, memory demand, or network traffic. It will not increase the slowness of the apps.

<https://docs.microsoft.com/en-us/azure/app-service/manage-scale-up>

<https://docs.microsoft.com/en-us/azure/app-service/webjobs-create#webjob-types>

NEW QUESTION: 230

You have five Azure virtual machines that run Windows Server 2016. The virtual machines are configured as web servers. You have an Azure load balancer named LB1 that provides load

balancing services for the virtual machines. You need to ensure that visitors are serviced by the same web server for each request. What should you configure?

- A. a health probe
- B. Session persistence to Client IP protocol
- C. Floating IP (direct server return) to Disabled
- D. Session persistence to None

Answer: B (LEAVE A REPLY)

NEW QUESTION: 231

You recently created a new Azure subscription that contains a user named Admin1. Admin1 attempts to deploy an Azure Marketplace resource by using an Azure Resource Manager template. Admin1 deploys the template by using Azure PowerShell and receives the following error message: "User failed validation to purchase resources. Error message: "Legal terms have not been accepted for this item on this subscription. To accept legal terms, please go to the Azure portal (<http://go.microsoft.com/fwlink/?LinkId=534873>) and configure programmatic deployment for the Marketplace item or create it there for the first time." You need to ensure that Admin1 can deploy the Marketplace resource successfully.

What should you do?

- A. From Azure PowerShell, run the Set-AzApiManagementSubscription cmdlet
- B. From the Azure portal, register the Microsoft.Marketplace resource provider
- C. From Azure PowerShell, run the Set-AzMarketplaceTerms cmdlet
- D. From the Azure portal, assign the Billing administrator role to Admin1

Answer: C (LEAVE A REPLY)

The Set-AzMarketplaceTerms cmdlet saves the terms object for given publisher id(Publisher), offer id(Product) and plan id(Name) tuple.

Reference:

<https://docs.microsoft.com/en-us/powershell/module/az.marketplaceordering/set-azmarketplaceterms?view=azps-4.5.0>

NEW QUESTION: 232

You have a sync group named Sync1 that has a cloud endpoint. The cloud endpoint includes a file named File1.txt.

Your on-premises network contains servers that run Windows Server 2016. The servers are configured as shown in the following table.

You add Share1 as an endpoint for Sync1. One hour later, you add Share2 as an endpoint for Sync1.

For each of the following statements, select Yes if the statement is true. Otherwise, select No.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/storage/files/storage-sync-files-planning>

<http://techgenix.com/azure-file-sync-replicating-data/>

NEW QUESTION: 233

You are the global administrator for an Azure Active Directory (Azure AD) tenet named adatum.com.

You need to enable two-step verification for Azure users.

What should you do?

- A.** Create a sign-in risk policy in Azure AD Identity Protection
- B.** Enable Azure AD Privileged Identity Management.
- C.** Create and configure the Identity Hub.
- D.** Configure a security policy in Azure Security Center.

Answer: A (LEAVE A REPLY)

Identity Protection analyzes signals from each sign-in, both real-time and offline, and calculates a risk score based on the probability that the sign-in wasn't performed by the user. Administrators can make a decision based on this risk score signal to enforce organizational requirements. Administrators can choose to block access, allow access, or allow access but require multi-factor authentication.

If risk is detected, users can perform multi-factor authentication to self-remediate and close the risky sign-in event to prevent unnecessary noise for administrators.

With Azure Active Directory Identity Protection, you can:

require users to register for multi-factor authentication

handle risky sign-ins and compromised users

Reference:

<https://docs.microsoft.com/en-us/azure/active-directory/identity-protection/flows>

NEW QUESTION: 234

From Azure Active Directory (AD) Privileged Identify Management, you configure the Role settings for the Owner role of an Azure subscription as shown in the following exhibit.

From Azure AD Privileged Identify Management, you assign the Owner role for the subscription to a user named User1, and you set the Assignment type to Active and Permanently eligible.

Use the drop-down menus to select the answer choice that completes each statement based on the information presented in the graphic.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/active-directory/privileged-identity-management/pim-how-to-add-role-to-user?tabs=new>

NEW QUESTION: 235

You sign up for Azure Active Directory (Azure AD) Premium.

You need to add a user named admin1@contoso.com as an administrator on all the computers that will be joined to the Azure AD domain.

What should you configure in Azure AD?

- A. Device settings from the Devices blade.
- B. General settings from the Groups blade.
- C. User settings from the Users blade.
- D. Providers from the MFA Server blade.

Answer: A (LEAVE A REPLY)

When you connect a Windows device with Azure AD using an Azure AD join, Azure AD adds the following security principles to the local administrators group on the device:

The Azure AD global administrator role

The Azure AD device administrator role

The user performing the Azure AD join

In the Azure portal, you can manage the device administrator role on the Devices page. To open the Devices page:

1. Sign in to your Azure portal as a global administrator or device administrator.
2. On the left navbar, click Azure Active Directory.
3. In the Manage section, click Devices.
4. On the Devices page, click Device settings.
5. To modify the device administrator role, configure Additional local administrators on Azure AD joined devices.

NEW QUESTION: 236

You have an Azure subscription that has the public IP addresses shown in the following table.

You plan to deploy an instance of Azure Firewall Premium named FW1.

Which IP addresses can you use?

- A. IP1, IP2, and IP5 only
- B. IP1, IP2, IP4, and IP5 only
- C. IP2 Only
- D. IP1 and IP2 only

Answer: A (LEAVE A REPLY)

NEW QUESTION: 237

You have an Azure virtual machine named VM1.

The network interface for VM1 is configured as shown in the exhibit. (Click the Exhibit tab.)

You need to ensure that users can connect to the website from the internet.

What should you do?

- A. Create a new inbound rule that allows TCP protocol 443 and configure the protocol to have a priority of 501.
- B. For Rule5, change the Action to Allow and change the priority to 401.
- C. Delete Rule1.

D. Modify the protocol of Rule4.

Answer: B (LEAVE A REPLY)

Rule 2 is blocking HTTPS access (port 443) and has a priority of 500.

Changing Rule 5 (ports 50-5000) and giving it a lower priority number will allow access on port 443.

Note: Rules are processed in priority order, with lower numbers processed before higher numbers, because lower numbers have higher priority. Once traffic matches a rule, processing stops.

Reference:

<https://docs.microsoft.com/en-us/azure/virtual-network/security-overview>

NEW QUESTION: 238

You have an Azure subscription that contains the resources shown in the following table.

All virtual machines run Windows Server 2016.

On VM1, you back up a folder named Folder1 as shown in the following exhibit.

You plan to restore the backup to a different virtual machine.

You need to restore the backup to VM2.

What should you do first?

A. From VM2, install the Microsoft Azure Recovery Services Agent

B. From VM1, install the Windows Server Backup feature

C. From VM2, install the Windows Server Backup feature

D. From VM1, install the Microsoft Azure Recovery Services Agent

Answer: A (LEAVE A REPLY)

Reference:

<https://docs.microsoft.com/en-us/azure/backup/backup-azure-restore-windows-server>

NEW QUESTION: 239

You have a computer named Computer1 that has a point-to-site VPN connection to an Azure virtual network named VNet1. The point-to-site connection uses a self-signed certificate.

From Azure, you download and install the VPN client configuration package on a computer named Computer2.

You need to ensure that you can establish a point-to-site VPN connection to VNet1 from Computer2.

Solution: You join Computer2 to Azure Active Directory (Azure AD).

Does this meet the goal?

A. Yes

B. No

Answer: (SHOW ANSWER)

A client computer that connects to a VNet using Point-to-Site must have a client certificate installed.

Reference:

<https://docs.microsoft.com/en-us/azure/vpn-gateway/vpn-gateway-certificates-point-to-site>

NEW QUESTION: 240

You have an Azure subscription named Subscription1 that contains the resources shown in the following table.

The status of VM1 is Running.

You assign an Azure policy as shown in the exhibit. (Click the Exhibit tab.)

You assign the policy by using the following parameters:

For each of the following statements, select Yes if the statement is true. Otherwise, select No.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/governance/policy/assign-policy-portal>

NEW QUESTION: 241

You create an App Service plan named plan1 and an Azure web app named webapp1. You discover that the option to create a staging slot is unavailable. You need to create a staging slot for plan1.

What should you do first?

- A. From webapp1, modify the Application settings.
- B. From webapp1, add a custom domain.
- C. From plan1, scale up the App Service plan.
- D. From plan1, scale out the App Service plan.

Answer: C ([LEAVE A REPLY](#))

Scale up: Get more CPU, memory, disk space, and extra features like dedicated virtual machines (VMs), custom domains and certificates, staging slots, autoscaling, and more.

You scale up by changing the pricing tier of the App Service plan that your app belongs to.

Reference:

<https://docs.microsoft.com/en-us/azure/app-service/manage-scale-up>

Valid AZ-104 Dumps shared by Actual4test.com for Helping Passing AZ-104 Exam!

Actual4test.com now offer the **newest AZ-104 exam dumps**, the Actual4test.com AZ-104 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com AZ-104 dumps with Test Engine here:

https://www.actual4test.com/AZ-104_examcollection.html (430 Q&As Dumps, **30%OFF**)

Special Discount: [Freepdfdumps](#))

NEW QUESTION: 242

You have an Azure subscription named Subscription1 that contains the storage accounts shown in the following table.

You plan to use the Azure Import/Export service to export data from Subscription1.

- A. storage1
- B. storage2
- C. storage3
- D. storage4

Answer: D ([LEAVE A REPLY](#))

Azure Import/Export service supports the following of storage accounts:

Standard General Purpose v2 storage accounts (recommended for most scenarios) Blob Storage accounts General Purpose v1 storage accounts (both Classic or Azure Resource Manager deployments), Azure Import/Export service supports the following storage types Import supports Azure Blob storage and Azure File storage Export supports Azure Blob storage Reference: <https://docs.microsoft.com/en-us/azure/storage/common/storage-import-export-requirements>

NEW QUESTION: 243

You have an Azure subscription that contains the Azure virtual machines shown in the following table.

You add inbound security rules to a network security group (NSG) named NSG1 as shown in the following table.

You run Azure Network Watcher as shown in the following exhibit.

You run Network Watcher again as shown in the following exhibit.

For each of the following statements, select Yes if the statement is true. Otherwise, select No.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/virtual-network/network-security-group-how-it-works>

NEW QUESTION: 244

You have an Azure web app named webapp1.

You have a virtual network named VNET1 and an Azure virtual machine named VM1 that hosts a MySQL database. VM1 connects to VNET1. You need to ensure that webapp1 can access the data hosted on VM1. What should you do?

- A. Deploy an Azure Application Gateway.
- B. Peer VNET1 to another virtual network.
- C. Connect webapp1 to VNET1.
- D. Deploy an internal load balancer

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 245

You have a hybrid infrastructure that contains an Azure Active Directory (Azure AD) tenant named contoso.onmicrosoft.com. The tenant contains the users shown in the following table.

You plan to share a cloud resource to the All Users group.

You need to ensure that User1, User2, User3, and User4 can connect successfully to the cloud resource.

What should you do first?

- A. Create a user account of the member type for User4.
- B. Create a user account of the member type for User3.
- C. Modify the Directory-wide Groups settings.
- D. Modify the External collaboration settings.

Answer: C (LEAVE A REPLY)

Ensure that "Enable an 'All Users' group in the directory" policy is set to "Yes" in your Azure Active Directory (AD) settings in order to enable the "All Users" group for centralized access administration. This group represents the entire collection of the Active Directory users, including guests and external users, that you can use to make the access permissions easier to manage within your directory.

Incorrect Answers:

A, B: User3 and User4 are guests already.

Note: By default, all users and guests in your directory can invite guests even if they're not assigned to an admin role. External collaboration settings let you turn guest invitations on or off for different types of users in your organization. You can also delegate invitations to individual users by assigning roles that allow them to invite guests.

Reference:

<https://www.cloudconformity.com/knowledge-base/azure/ActiveDirectory/enable-all-users-group.html>

NEW QUESTION: 246

You have an Azure subscription that contains a storage account named storage1. The storage1 account contains a file share named share1. The subscription is linked to a hybrid Azure Active Directory (Azure AD) tenant that contains a security group named Group1. You need to grant Group1 the Storage File Data SMB Share Elevated Contributor role for share1. What should you do first?

- A. Mount share1 by using File Explorer.
- B. Create a private endpoint.
- C. Enable Active Directory Domain Service (ADDS) authentication for storage1.
- D. Grant share-level permissions by using File Explorer.

Answer: (SHOW ANSWER)

NEW QUESTION: 247

You have an Azure subscription that contains the resources shown in the following table.

VMSS1 is set to VM (virtual machines) orchestration mode.

You need to deploy a new Azure virtual machine named VM1, and then add VM1 to VMSS1. Which resource group and location should you use to deploy VM1? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/azure-resource-manager/management/overview>

NEW QUESTION: 248

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution. After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure web app named App1. App1 runs in an Azure App Service plan named Plan1. Plan1 is associated to the Free pricing tier.

You discover that App1 stops each day after running continuously for 60 minutes.

You need to ensure that App1 can run continuously for the entire day.

Solution: You change the pricing tier of Plan1 to Basic. Does this meet the goal?

A. Yes

B. No

Answer: A (LEAVE A REPLY)

The Free Tier provides 60 CPU minutes / day. This explains why App1 is stops. The Basic tier has no such cap.

Reference:

<https://azure.microsoft.com/en-us/pricing/details/app-service/windows/>

NEW QUESTION: 249

You have an Azure subscription that contains the virtual networks shown in the following table.

You have the virtual machines shown in the following table.

You have the virtual network interfaces shown in the following table.

Server1 is a DNS server that contains the resources shown in the following table.

You have an Azure private DNS zone named contoso.com that has a virtual network link to VNET2 and the records shown in the following table.

For each of the following statements, select Yes if the statement is true. Otherwise, select No.

NOTE: Each correct selection is worth one point.

Answer:

NEW QUESTION: 250

Note: The question is included in a number of questions that depicts the identical set-up. However, every question has a distinctive result. Establish if the solution satisfies the requirements.

Your company has an Azure Active Directory (Azure AD) subscription.

You want to implement an Azure AD conditional access policy.

The policy must be configured to require members of the Global Administrators group to use Multi-Factor Authentication and an Azure AD-joined device when they connect to Azure AD from untrusted locations.

Solution: You access the multi-factor authentication page to alter the user settings.

Does the solution meet the goal?

A. Yes

B. No

Answer: B (LEAVE A REPLY)

<https://docs.microsoft.com/en-us/azure/active-directory/conditional-access/howto-conditional-access-policy-admin-mfa>

NEW QUESTION: 251

You have two Azure Active Directory (Azure AD) tenants named contoso.com and fabrikam.com.

You have a Microsoft account that you use to sign in to both tenants.

You need to configure the default sign-in tenant for the Azure portal.

What should you do?

A. From the Azure portal, configure the portal settings.

B. From the Azure portal, change the directory.

C. From Azure Cloud Shell, run Set-AzureRmContext.

D. From Azure Cloud Shell, run Set-AzureRmSubscription.

Answer: B (LEAVE A REPLY)

The Set-AzureRmContext cmdlet sets authentication information for cmdlets that you run in the current session. The context includes tenant, subscription, and environment information.

Reference:

<https://docs.microsoft.com/en-us/powershell/module/azurermsprofile/set-azurermscontext>

NEW QUESTION: 252

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure web app named App1. App1 runs in an Azure App Service plan named Plan1. Plan1 is associated to the Free pricing tier.

You discover that App1 stops each day after running continuously for 60 minutes.

You need to ensure that App1 can run continuously for the entire day.

Solution: You add a continuous WebJob to App1.

Does this meet the goal?

A. Yes

B. No

Answer: ([SHOW ANSWER](#))

A web app can time out after 20 minutes of inactivity. Only requests to the actual web app reset the timer. Viewing the app's configuration in the Azure portal or making requests to the advanced tools site (https://<app_name>.scm.azurewebsites.net) don't reset the timer. If your app runs continuous or scheduled (Timer trigger) WebJobs, enable Always On to ensure that the WebJobs run reliably. This feature is available only in the Basic, Standard, and Premium pricing tiers. The app service plan mentioned in the question is associated to the free tier, so addition of a continuous WebJob to App1 is not possible. So the proposed solution won't meet the goal.

Reference:

<https://docs.microsoft.com/en-us/azure/app-service/webjobs-create>

NEW QUESTION: 253

You deploy Azure virtual machines to three Azure regions.

Each region contains a virtual network. Each virtual network contains multiple subnets peered in a full mesh topology.

Each subnet contains a network security group (NSG) that has defined rules.

A user reports that he cannot use port 33000 to connect from a virtual machine in one region to a virtual machine in another region.

Which two options can you use to diagnose the issue? Each correct answer presents a complete solution.

NOTE: Each correct selection is worth one point.

A. Azure Virtual Network Manager

B. Azure Monitor Network Insights

C. IP flow verify DD.

D. effective security rules

E. Connection troubleshoot

Answer: C,E ([LEAVE A REPLY](#))

NEW QUESTION: 254

You have an Azure subscription that contains two virtual machines named VM1 and VM2. You create an Azure load balancer.

You plan to create a load balancing rule that will load balance HTTPS traffic between VM1 and VM2.

Which two additional load balance resources should you create before you can create the load balancing rule? Each correct answer presents part of the solution. Each correct selection is worth one point.

A. an inbound NAT rule

- B. a backend pool
- C. a frontend IP address
- D. a virtual network
- E. a health probe

Answer: B,E ([LEAVE A REPLY](#))

NEW QUESTION: 255

You have an Azure Storage account named storage1 that uses Azure Blob storage and Azure File storage.

You need to use AzCopy to copy data to the blob storage and file storage in storage1.

Which authentication method should you use for each type of storage? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer:

Reference:

<https://docs.microsoft.com/en-us/azure/storage/common/storage-use-azcopy-v10>

Valid AZ-104 Dumps shared by Actual4test.com for Helping Passing AZ-104 Exam!

Actual4test.com now offer the **newest AZ-104 exam dumps**, the Actual4test.com AZ-104 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com AZ-104 dumps with Test Engine here:

https://www.actual4test.com/AZ-104_examcollection.html (430 Q&As Dumps, **30%OFF**

Special Discount: [Freepdfdumps](#))