

Salesforce.CRT-450.v2021-12-08.q226

Exam Code:	CRT-450
Exam Name:	Salesforce Certified Platform Developer I
Certification Provider:	Salesforce
Free Question Number:	226
Version:	v2021-12-08
# of views:	6561
# of Questions views:	2260
https://www.freepdfdumps.com/Salesforce.CRT-450.v2021-12-08.q226.html	

NEW QUESTION: 1

An Apex transaction inserts 100 Account records and 2,000 Contact records before encountering a DML exception when attempting to insert 500 Opportunity records.

The Account records are inserted by calling the `database.insert()` method with the `allOrNone` argument set to `false`. The Contact and Opportunity records are inserted using the standalone insert statement.

How many total records will be committed to the database in this transaction?

- A. 100
- B. 2,000
- C. 0
- D. 2,100

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 2

A developer creates a new Apex trigger with a helper class, and writes a test class that only exercises 95% coverage of the new Apex helper class.

Change Set deployment to production fails with the test coverage warning:

"Test coverage of selected Apex Trigger is 0%, at least 1% test coverage is required." What should the developer do to successfully deploy the new Apex trigger and helper class?

- A. Increase the test class coverage on the helper class.
- B. Run the tests using the 'Run All Tests' method.
- C. Create a test class and methods to cover the Apex trigger.
- D. Remove the failing test methods from the test class.

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 3

A developer is debugging the following code to determine why Accounts are not being created.

```
Account a = new Account(Name = 'A');
```

```
Database.insert(a, false);
```

How should the code be altered to help debug the issue?

- A. Set the second insert method parameter to TRUE.
- B. Add a System.debug() statement before the insert method.
- C. Add a try/catch around the insert method.
- D. Collect the insert method return value in a SaveResult record.

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 4

A candidate may apply to multiple jobs at the company Universal Containers by submitting a single application per job posting. Once an application is submitted for a job posting, that application cannot be modified to be resubmitted to a different job posting. What can the administrator do to associate an application with each job posting in the schema for the organization?

- A. Create a lookup relationship in the Applications custom object to the Job Postings custom object
- B. Create a master-detail relationship in the Job Postings custom object to the Applications custom object.
- C. Create a lookup relationship on both objects to a junction object called Job Posting Applications.
- D. Create a master-detail relationship in the Application custom object to the Job Postings custom object.

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 5

A developer must create a CreditcardPayment class that provides an implementation of an existing Payment class. Public virtual class Payment { public virtual void makePayment(Decimal amount) {

```
/*implementation*/ } } Which is the correct implementation?
```

- A. Public class CreditcardPayment extends Payment {
public override void makePayment(Decimal amount) { /*implementation*/ }
}
- B. Public class CreditCardPayment implements Payment {
public override void makePayment(Decimal amount) { /*Implementation*/ }
}
- C. Public class CreditCardPayment implements Payment {
public virtual void makePayment(Decimal amount) { /*implementation*/ }
}
- D. Public class CreditCardPayment extends Payment {
public virtual void makePayment(Decimal amount) { /*implementation*/ }
}

}

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 6

A developer is asked to create a custom visualforce page that will be used as a dashboard component.

Which three are valid controller options for this page? Choose 3 answers

- A. Use a custom controller with extensions
- B. Use a standard controller
- C. Do not specify a controller
- D. Use a custom controller
- E. Use a standard controller with extensions

Answer: B,D,E ([LEAVE A REPLY](#))

NEW QUESTION: 7

A developer creates an Apex Trigger with the following code block:
`List<Account> customers = new List<Account>();
For (Order__c o: trigger.new){
Account a = [SELECT Id, Is_Customer__c FROM Account WHERE Id :o.Customer__c];
a.Is_Customer__c = true;
customers.add(a);
Database.update(customers, false);
}`
The developer tests the code using Apex Data Loader and successfully loads 10 Orders. Then, the developer loads 150 Orders. How many Orders are successfully loaded when the developer attempts to load the 150 Orders?

- A. 1
- B. 150
- C. 100
- D. 0

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 8

A developer is asked to write negative tests as part of the unit testing for a method that calculates a person's age based on birth date. What should the negative tests include?

- A. Assert that a null value is accepted by the method.
- B. Assert that past dates are accepted by the method.
- C. Assert that future dates are rejected by the method.
- D. Throwing a custom exception in the unit test.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 9

A developer has the controller class below.

```
public with sharing class myFooController {
    public integer prop { get; private set; }
}
```

Which code block will run successfully in an execute anonymous window?

- A. myFooController m = new myFooController();System.assert(m.prop ==null);
- B. myFooController m = new myFooController();System.assert(m.prop ==1);
- C. myFooController m = new myFooController();System.assert(m.prop ==0);
- D. myFooController m = new myFooController();System.assert(m.prop !=null);

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 10

A developer wants to display all of the available record types for a Case object. The developer also wants to display the picklist values for the Case.Status field. The Case object and the Case.Status field are on a custom Visualforce page. Which action can the developer perform to get the record types and picklist values in the controller? (Choose 2)

- A. Use Schema.PicklistEntry returned by Case.Status.getDescribe().getPicklistValues().
- B. Use Schema.RecordTypeInfo returned by Case.sObjectType.getDescribe().getRecordTypeInfos().
- C. Use SOQL to query Case records in the org to get all the RecordType values available for Case.
- D. Use SOQL to query case records in the org to get all values for the Status picklist field.

Answer: A,B ([LEAVE A REPLY](#))

NEW QUESTION: 11

A developer wants multiple test classes to use the same set of test data. How should the developer create the test data?

- A. Reference a test utility class in each test class
- B. Create a test setup method for each test class
- C. Use the seealldata=true annotation in each test class
- D. Define a variable for test records in each test classes

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 12

What is a benefit of the lightning component framework?

- A. Better integration with Force.com sites
- B. More pre-built components to replicate the salesforce look and feel
- C. Better performance for custom Salesforce1 Mobile Apps
- D. More Centralized control via server-side logic

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 13

Universal Containers implemented a private sharing model for the Account object. A custom Account search tool was developed with Apex to help sales representatives find accounts that match multiple criteria they specify. Since its release, users of the tool report they can see Accounts they do not own.

What should the developer use to enforce sharing permission for the currently logged-in user while using the custom search tool?

- A. Use the UserInfo Apex class to filter all SOQL queries to returned records owned by the logged-in user.
- B. Use the without sharing keyword on the class declaration.
- C. Use the with sharing keyword on the class declaration.
- D. Use the schema describe calls to determine if the logged-in users has access to the Account object.

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 14

If Apex code executes inside the execute() method of an Apex class when implementing the Batchable interface, which two statements are true regarding governor limits? (Choose two.)

- A. The Apex governor limits are relaxed while calling the constructor of the Apex class.
- B. The Apex governor limits cannot be exceeded due to the asynchronous nature of the transaction.
- C. The Apex governor limits are reset for each iteration of the execute() method.
- D. The Apex governor limits might be higher due to the asynchronous nature of the transaction.

Answer: C,D ([LEAVE A REPLY](#))

NEW QUESTION: 15

A developer writes a SOQL query to find child records for a specific parent. How many levels can be returned in a single query?

- A. 3
- B. 1
- C. 5
- D. 7

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 16

Which two statements are true about Apex code executed in Anonymous Blocks? (Choose two.)

- A. Successful DML operations are automatically committed.
- B. The code runs with the permissions of the logged in user.
- C. All DML operations are automatically rolled back.
- D. The code runs with the permissions of the user specified in the runAs() statement.
- E. The code runs in system mode having access to all objects and fields.

Answer: A,B ([LEAVE A REPLY](#))

Valid CRT-450 Dumps shared by Actual4test.com for Helping Passing CRT-450 Exam! Actual4test.com now offer the **newest CRT-450 exam dumps**, the Actual4test.com CRT-450 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com CRT-450 dumps with Test Engine here:
https://www.actual4test.com/CRT-450_examcollection.html (240 Q&As Dumps, **30%OFF** Special Discount: **Freepdfdumps**)

NEW QUESTION: 17

A lead object has a custom field Prior_Email__c. The following trigger is intended to copy the current Email into the Prior_Email__c field any time the Email field is changed:

```
trigger test on Lead (before update) {
    for(Lead ld: trigger.new)
    {
        if(ld.Email != trigger.oldMap.get (ld.ld).email)
        {
            ld.Prior_Email__c = trigger.old,ap.get(ld.ld).email;
            update ld;
        }
    }
}
```



Which type of exception will this trigger cause?

- A. A DML exception
- B. A compile time exception
- C. A null reference exception
- D. A limit exception when doing a bulk update

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 18

What are two considerations for custom Apex Exception classes? Choose 2 answers.

- A. Custom Exceptions cannot be extended by other Exception classes.
- B. Custom Exception class names must end with the word 'Exception'.
- C. Custom Exception classes must extend the base Exception class.
- D. Constructor for custom Exceptions can only accept string values as arguments.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 19

A developer needs to provide a way to mass edit, update, and delete records from a list view. In which two ways can this be accomplished? Choose 2 answers

- A. Download a managed package from the AppExchange that provides customizable Enhanced List Views and buttons

- B. Download an unmanaged package from the AppExchange that provide customizable mass edit, update, and delete functionality.
- C. Create a new Visualforce page and Apex Controller for the list view that provides mass edit, update and delete functionality.
- D. Configure the user interface and enable both inline editing and enhanced lists.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 20

A developer wrote a unit test to confirm that a custom exception works properly in a custom controller, but the test failed due to an exception being thrown.

Which step should the developer take to resolve the issue and properly test the exception?

- A. Use the finally bloc within the unit test to populate the exception.
- B. Use try/catch within the unit test to catch the exception.
- C. Use the database methods with all or none set to FALSE.
- D. Use Test.isRunningTest() within the custom controller.

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 21

A developer wrote Apex code that calls out to an external system.

How should a developer write the test to provide test coverage?

- A. Write a class that extends HTTPCalloutMock.
- B. Write a class that extends WebserviceMock.
- C. Write a class that implements the HTTPCalloutMockinterface.
- D. Write a class that implements the WebserviceMockinterface.

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 22

Which option would a developer use to display the Accounts created in the current week and the number of related Contacts using a debug statement in Apex?

- A.

```
For(Account acc: [SELECT Id, Name, Account.Contacts FROM Account WHERE CreatedDate = THIS_WEEK]){ List cons = acc.Account.Contacts; System.debug(acc.Name + ' has ' + cons.size() + 'Contacts' }
```
- B.

```
For(Account acc:[SELECT Id, Name, Account.Contacts FROM Account WHERE CreatedDate = CURRENT_WEEK]) { List cons = acc.Account.Contacts; System.debug(acc.Name + ' has ' + cons.size() + 'Contacts'); }
```
- C.

```
For(Account acc: [SELECT Id, Name, (SELECT Id, Name FROM Contacts) FROM Account WHERE CreatedDate = CURRENT_WEEK]){ List cons = acc.Contacts; System.debug(acc.Name + ' has ' + cons.size() + 'Contacts'); }
```

D. For(Account acc: [SELECT Id, Name,(SELECT Id, Name FROM Contacts) FROM Account WHERE CreatedDate = THIS_WEEK]) { List cons = acc.Contacts; System.debug(acc.Name + ' has ' + cons.size() + 'Contacts'; }

Answer: [\(SHOW ANSWER\)](#)

NEW QUESTION: 23

What is a valid Apex statement?

A. Map conMap = (SELECT Name FROM Contact);

B. Account[] acctList = new List{new Account()}

C. Private static constant Double rate = 775;

D. Integer w, x, y = 123, z = 'abc',

Answer: [B \(LEAVE A REPLY\)](#)

NEW QUESTION: 24

developer created this Apex trigger that calls MyClass .myStaticMethod: trigger myTrigger on Contact(before insert) (MyClass.myStaticMethod(trigger.new, trigger.oldMap); } The developer creates a test class with a test method that calls MyClass.mystaticMethod, resulting in 81% overall code coverage. What happens when the developer tries to deploy the trigger and two classes to production, assuming no other code exist?

A. The deployment passes because both classes and the trigger were included in the deployment.

B. The deployment fails because the Apex trigger has no code coverage.

C. The deployment fails because no assertions were made in the test method.

D. The deployment passes because the Apex code has required (>75%) code coverage.

Answer: [B \(LEAVE A REPLY\)](#)

NEW QUESTION: 25

Universal Containers (UC) decided it will not send emails to support personnel directly from Salesforce in the event that an unhandled exception occurs. Instead, UC wants an external system be notified of the error.

What is the appropriate publish/subscribe logic to meet these requirements?

A. Publish the error event using the addError()method and write a trigger to subscribe to the event and notify the external system.

B. Publish the error event using the EventBus.publish()method and have the external system subscribe to the event using CometD.

C. Have the external system subscribe to the BatchApexErrorevent, no publishing is necessary.

D. Publish the error event using the addError()method and have the external system subscribe to the event using CometD.

Answer: [B \(LEAVE A REPLY\)](#)

NEW QUESTION: 26

A developer has the controller class below.

```
public with sharing class myFooController {  
    public integer prop { get; private set; }  
}
```

Which code block will run successfully in an execute anonymous window?

- A. myFooController m = new myFooController();System.assert(m.prop !=null);
- B. myFooController m = new myFooController();System.assert(m.prop ==0);
- C. myFooController m = new myFooController();System.assert(m.prop ==1);
- D. myFooController m = new myFooController();System.assert(m.prop ==null);

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 27

A developer needs to have records with specific field values in order to test a new Apex class.

What should the developer do to ensure the data is available to the test?

- A. Use SOQL to query the org for the required data.
- B. Use Anonymous Apex to create the required data.
- C. Use Test.loadData() and reference a CSV file.
- D. Use Test.loadData() and reference a static resource.

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 28

A Hierarchy Custom Setting stores a specific URL for each profile in Salesforce. Which statement can a developer use to retrieve the correct URL for the current user's profile and display this on a Visualforce Page?

- A. {\$Setup.Url_Settings__C.[Profile.Id].URL__c}
- B. {\$Setup.Url_Settings__C.Instance[Profile.Id].URL__c}
- C. {\$Setup.Url_Settings__C.[\$Profile.Id].URL__c}
- D. {\$Setup.Url_Settings__C.URL__c}

Answer: (SHOW ANSWER)

NEW QUESTION: 29

Which actions can a developer perform using the Schema Builder? Choose 2 answers

- A. Create a custom object and define a lookup relationship on that object
- B. Create a view containing only standard and system objects.
- C. Create a custom field and automatically add it to an existing page layout.
- D. Create a view of objects and relationships without fields

Answer: A,B ([LEAVE A REPLY](#))

NEW QUESTION: 30

A candidate may apply to multiple jobs at the company Universal Containers by submitting a single application per job posting, that application cannot be modified to be resubmitted to a different job posting. What can the administrator do to associate an application with each job posting in the schema for the organization?

- A. Create a master-detail relationship in the Application custom object to the Job Postings custom object.
- B. Create a lookup relationship on both objects to a junction object called Job Posting Applications.
- C. Create a lookup relationship in the Applications custom object to the Job Postings custom object.
- D. Create a master-detail relationship in the Job Postings custom object to the Applications custom object.

Answer: A (LEAVE A REPLY)

NEW QUESTION: 31

What is the result of the debug statements in testMethod3 when you create test data using testSetup in below code?

```
@isTest
private class CreateAndExecuteTest{

    @testSetup
    static void setup() {
        // Create 2 test accounts
        List<Account> testAccts = new List<Account>();
        for(Integer i=0;i<2;i++) {
            testAccts.add(new Account(Name = 'MyTestAccount'+i, Phone='333-878'));
        }
        insert testAccts;
    }

    @isTest static void testMethod1() {
        Account acc = [SELECT Id,Phone FROM Account WHERE Name='MyTestAccount0' LIMIT 1];
        acc.Phone = '888-1515';
        update acc;

        Account acc2 = [SELECT Id,Phone FROM Account WHERE Name='MyTestAccount1' LIMIT 1];
        acc.Phone = '999-1515';
        update acc2;
    }

    @isTest static void testMethod2() {
        Account acc = [SELECT Id,Phone FROM Account WHERE Name='MyTestAccount1' LIMIT 1];
        acc.Phone = '888-2525';
        update acc;
    }

    @isTest static void testMethod3() {
        Account acc0 = [SELECT Id,Phone FROM Account WHERE Name='MyTestAccount0' LIMIT 1];
        Account acc1 = [SELECT Id,Phone FROM Account WHERE Name='MyTestAccount1' LIMIT 1];

        System.debug('Account0.Phone='+ acc0.Phone +', Account1.Phone='+acc1.Phone);
    }
}
```

- A. Account0.Phone=333-8780, Account1.Phone=333-8781
- B. Account0.Phone=888-1515, Account1.Phone=999-2525

C. Account0.Phone=333-8781, Account1.Phone=333-8780

D. Account0.Phone=888-1515, Account1.Phone=999-1515

Answer: ([SHOW ANSWER](#))

Valid CRT-450 Dumps shared by Actual4test.com for Helping Passing CRT-450 Exam! Actual4test.com now offer the **newest CRT-450 exam dumps**, the Actual4test.com CRT-450 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com CRT-450 dumps with Test Engine here:

https://www.actual4test.com/CRT-450_examcollection.html (**240 Q&As Dumps, 30%OFF**

Special Discount: Freepdfdumps)

NEW QUESTION: 32

A developer has the following code:try {List nameList;Account a;String s = a.Name;nameList.add(s);} catch (ListException le) {System.debug(' List Exception ');} catch (NullPointerException npe) {System.debug(' NullPointer Exception ');} catch (Exception e) {System.debug(' Generic Exception ');} What message will be logged?

- A. List Exception
- B. Generic Exception
- C. No message is logged
- D. NullPointer Exception

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 33

A developer must create a Lightning component that allows users to input Contact record information to create a Contact record, including a Salary__ccustom field.

What should the developer use, along with a lightning-record-edit-form, so that Salary__cfield functions as a currency input and is only viewable and editable by users that have the correct field level permissions on Salary__c?

- A. `<lightning-input type="number" value="Salary__c" formatter="currency">`
`</lightning-input>`
- B. `<lightning-formatted-number value="Salary__c" format-style="currency">`
`</lightning-formatted-number>`
- C. `<lightning-input-field field-name="Salary__c">`
`</lightning-input-field>`
- D. `<lightning-input-currency value="Salary__c">`
`</lightning-input-currency>`

Answer: C ([LEAVE A REPLY](#))

Explanation/Reference:

NEW QUESTION: 34

In an organization that has enabled multiple currencies, a developer needs to aggregate the sum of the Estimated_value__c currency field from the CampaignMember object using a roll-up summary field called Total_estimated_value__c on Campaign.

- A. The values in Campaignmember.Estimated_value__c are converted into the currency of the Campaign record and the sum is displayed using the currency on the Campaign record.
- B. The values in CampaignMember.Estimated_value__c are summed up and the resulting Total_estimated_value__c field is displayed as a numeric field on the Campaign record.
- C. The values In CampaignMember.Estimated_value__c are converted into the currency of the current user, and the sum is displayed using the currency on the Campaign record.
- D. The values in CampaignMember.Estimated_value__c are converted into the currency on the majority of the CampaignMember records and the sum is displayed using that currency.

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 35

What should a developer use to implement an automate approval process submission for case?

- A. An assignment rules.
- B. A workflow rules.
- C. Scheduled apex.
- D. Process builder.

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 36

What actions types should be configured to display a custom success message?

- A. Post a feed item.
- B. Delete a record.
- C. Update a record.
- D. Close a case.

Answer: (SHOW ANSWER)

NEW QUESTION: 37

A developer has the following class and trigger code public class insurancerates{ public static final decimal smokercharge = 0.01; } trigger contacttrigger on contact (before insert) { insurancerates rates = new insurancerates(); decimal basecost=xxx; } Which code segment should a developer insert at the xxx to set the basecost variable to the value of the class variable smokercharge?

- A. Insurancerates.smokercharge
- B. Contacttrigger.insurancerates.smokercharge
- C. Rates.smokercharge
- D. Rates.getsmokercharge()

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 38

A developer wants to handle the click event for a lightning:button component. The on click attribute for the component references a JavaScript function in which resource in the component bundle?

- A. Controller.js
- B. Renderer.js
- C. Handler.js
- D. Helper.js

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 39

Universal Containers recently transitioned from Classic to Lightning Experience. One of its business processes requires certain values from the Opportunity object to be sent via an HTTP REST callout to its external order management system based on a user-initiated action on the Opportunity detail page. Example values are as follows:

- * Name
- * Amount
- * Account

Which two methods should the developer implement to fulfill the business requirement? (Choose two.)

- A. Create a Lightning component that performs the HTTP REST callout, and use a Lightning Action to expose the component on the Opportunity detail page.
- B. Create a Visualforce page that performs the HTTP REST callout, and use a Visualforce quick action to expose the component on the Opportunity detail page.
- C. Create an after update trigger on the Opportunity object that calls a helper method using @Future (Callout=true) to perform the HTTP REST callout.
- D. Create a Process Builder on the Opportunity object that executes an Apex immediate action to perform the HTTP REST callout whenever the Opportunity is updated.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 40

A Next Best Action strategy uses an Enhance Element that invokes an Apex method to determine a discount level for a Contact, based on a number of factors. What is the correct definition of the Apex method?

- A. @InvocableMethod

```
global static List<List<Recommendation>> getLevel(List<ContactWrapper> input)
{ /*implementation*/ }
```

- B. @InvocableMethod

```
global Recommendation getLevel (ContactWrapper input)
{ /*implementation*/ }
```

C. @InvocableMethod

```
global List<List<Recommendation>> getLevel(List<ContactWrapper> input)
{ /*implementation*/ }
```

D. @InvocableMethod

```
global static ListRecommendation getLevel(List<ContactWrapper> input)
{ /*implementation*/ }
```

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 41

A developer is notified that a text field is being automatically populated with invalid values. However, this should be prevented by a custom validation rule that is in place. What could be causing this?

A. The user belongs to a permission set that suppresses the validation rule

B. A DML exception is occurring during the save order of execution

C. The field is being populated by a workflow field update

D. The field is being populated by a before trigger

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 42

A developer has the following query: `Contact c = [SELECT id, firstname, lastname, email FROM Contact WHERE lastname = 'Smith'];` What does the query return if there is no Contact with the last name 'Smith'?

A. An empty List of Contacts.

B. A Contact with empty values.

C. A contact initialized to null.

D. An error that no rows are found.

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 43

What can a developer use to determine if the core Apex code exceeds any governor limits in a test class during bulk execution?

A. @TestVisible

B. @TestSetup

C. Limits, startTest, stopTest

D. Test.getDmlStatements()

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 44

Universal Containers stores the availability date on each Line Item of an Order and Orders are only shipped when all of the Line Items are available. Which method should be used to calculate the estimated ship date for an Order?

- A. Use a CEILING formula on each of the Latest availability date fields.
- B. Use a DAYS formula on each of the availability date fields and a COUNT Roll-Up Summary field on the Order.
- C. Use a LATEST formula on each of the latest availability date fields.
- D. Use a Max Roll-Up Summary field on the Latest availability date fields.

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 45

A Visualforce page has a standard controller for an object that has a lookup relationship to a parent object.

How can a developer display data from the parent record on the page?

- A. By using SOQL on the Visualforce page to query for data from the parent record.
- B. By using merge field syntax to retrieve data from the parent record.
- C. By using a roll-up formula field on the child record to include data from the parent record.
- D. By adding a second standard controller to the page for the parent record.

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 46

When the number of record in a recordset is unknown, which control statement should a developer use to implement a set of code that executes for every record in the recordset, without performing a .size() or .length() method call?

- A. For (variable : list_or_set) { }
- B. For (init_stmt, exit_condition; increment_stmt) { }
- C. Do { } While (Condition)
- D. While (Condition) { ... }

Answer: A ([LEAVE A REPLY](#))

Valid CRT-450 Dumps shared by Actual4test.com for Helping Passing CRT-450 Exam! Actual4test.com now offer the **newest CRT-450 exam dumps**, the Actual4test.com CRT-450 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com CRT-450 dumps with Test Engine here:

https://www.actual4test.com/CRT-450_examcollection.html (**240** Q&As Dumps, **30%OFF**

Special Discount: [Freepdfdumps](#))

NEW QUESTION: 47

Which two conditions cause workflow rules to fire? Choose 2 answers

- A. Updating records using the bulk API
- B. An Apex Batch process that changes field values
- C. Changing the territory assignments of accounts and opportunities

D. Converting leads to person accounts

Answer: A,B ([LEAVE A REPLY](#))

NEW QUESTION: 48

A developer wants to invoke an outbound message when a record meets a specific criteria. Which three features satisfy this use case? (Choose three.)

- A. Process builder can be used to check the record criteria and send an outbound message with Apex Code.
- B. Process builder can be used to check the record criteria and send an outbound message without Apex Code.
- C. Approval Process has the capability to check the record criteria and send an outbound message without Apex Code.
- D. Workflows can be used to check the record criteria and send an outbound message.
- E. Visual Workflow can be used to check the record criteria and send an outbound message without Apex Code.

Answer: C,D,E ([LEAVE A REPLY](#))

Explanation/Reference:

NEW QUESTION: 49

A developer has the following trigger that fires after insert and creates a child Case whenever a new Case is created. `List<Case> childCases = new List<Case>();for (Case parent : Trigger.new) {Case child = new Case (ParentId = parent.Id, Subject = parent.Subject);childCases.add(child);}insert childCases;` What happens after the code block executes?

- A. Child case is created for each parent case in Trigger.new.
- B. The trigger enters an infinite loop and eventually fails.
- C. The trigger fails if the Subject field on the parent is blank.
- D. Multiple child cases are created for each parent case in Trigger.new.

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 50

custom picklist field, Food_Preference__c, exist on a custom object. The picklist contains the following options: 'Vegan','Kosher','No Preference'. The developer must ensure a value is populated every time a record is created or updated. What is the most efficient way to ensure a value is selected every time a record is saved?

- A. Mark the field as Required on the object's page layout.
- B. Set "Use the first value in the list as the default value" as True.
- C. Mark the field as Required on the field definition.
- D. Set a validation rule to enforce a value is selected.

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 51

In the code below, what type does Boolean inherit from?

```
Boolean b= true;
```

- A. Object
- B. String
- C. Class
- D. Enum

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 52

What is a good practice for a developer to follow when writing a trigger? (Choose 2)

- A. Using @future methods to perform DML operations.
- B. Using synchronous callouts to call external systems.
- C. Using the Map data structure to hold query results by ID.
- D. Using the Set data structure to ensure distinct records.

Answer: C,D ([LEAVE A REPLY](#))

NEW QUESTION: 53

A developer needs to confirm that an Account trigger is working correctly without changing the organization's data. What would the developer do to test the Account trigger?

- A. Use the Open Execute Anonymous feature on the Developer Console to run an 'insert Account' DML statement.
- B. Use the Test menu on the developer Console to run all test classes for the account trigger.
- C. Use the New button on the Salesforce Accounts Tab to create a new Account record.
- D. Use Deploy from the Force.com IDE to deploy an 'insert Account' Apex class.

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 54

Why would a developer consider using a custom controller over a controller extension?

- A. To implement all of the logic for a page and bypass default Salesforce functionality
- B. To enforce user sharing settings and permissions
- C. To increase the SOQL query governor limits.
- D. To leverage built-in functionality of a standard controller

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 55

Which approach should a developer take to automatically add a "Maintenance Plan" to each Opportunity that includes an "Annual Subscription" when an opportunity is closed?

- A. Build an OpportunityLineItem trigger to add an OpportunityLineItem record.
- B. Build an Opportunity trigger that adds a PriceBookEntry record.
- C. Build an Opportunity trigger that adds an OpportunityLineItem record.

D. Build a OpportunityLineItem trigger that adds a PriceBookEntry record.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 56

A developer has a Visualforce page and custom controller to save Account records. The developer wants to display any validation rule violation to the user. How can the developer make sure that validation rule violations are displayed?

- A. Add custom controller attributes to display the message.
- B. Include <apex:message> on the Visualforce page.
- C. Use a try/catch with a custom exception class.
- D. Perform the DML using the Database.upsert() method.

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 57

A developer needs to create a custom visualforce button for the opportunity object page layout that will cause a web service to be called and redirect the user to a new page when clicked. Which three attributes need to be defined in the <apx:page> tag of the visualforce page to enable this functionality?

- A. Readonly
- B. Standardcontroller
- C. Action
- D. Renders
- E. Extensions

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 58

A developer executes the following query in Apex to retrieve a list of contacts for each account:

```
List<account> accounts = [Select ID, Name, (Select ID, Name from Contacts) from Account] ;
```

Which two exceptions may occur when it executes? (Choose two.)

- A. SOQL query row limit exception due to the number of accounts.
- B. SOQL query limit exception due to the number of contacts.
- C. SOQL query row limit exception due to the number of contacts.
- D. CPU limit exception due to the complexity of the query.

Answer: A,B ([LEAVE A REPLY](#))

NEW QUESTION: 59

A reviewer is required to enter a reason in the comments field only when a candidate is recommended to be hired. Which action can a developer take to enforce this requirement?

- A. Create a required Visualforce component.
- B. Create a required comments field.
- C. Create a validation rule.

D. Create a formula field.

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 60

How can a developer warn users of SOQL governor limit violations in a trigger?

A. Use Messaging.SendEmail() to continue the transaction and send an alert to the user after the number of SOQL queries exceeds the limit.

B. Use PageReference.setRedirect() to redirect the user to a custom Visualforce page before the number of SOQL queries exceeds the limit.

C. Use ApexMessage.Message() to display an error message after the number of SOQL queries exceeds the limit.

D. Use Limits.getQueries() and display an error message before the number of SOQL queries exceeds the limit.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 61

A developer writes the following code:

```
List<Account> acc = [SELECT Id FROM Account LIMIT 10];
Delete acc;
Database.emptyRecycleBin(acc);
system.Debug(Limits.getDMLStatements() + ', ' + Limits.getLimitDMLStatements());
```

What is the result of the debug statement?

A. 2, 200

B. 1, 150

C. 2, 150

D. 1, 100

Answer: ([SHOW ANSWER](#))

Valid CRT-450 Dumps shared by Actual4test.com for Helping Passing CRT-450 Exam! Actual4test.com now offer the **newest CRT-450 exam dumps**, the Actual4test.com CRT-450 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com CRT-450 dumps with Test Engine here:

https://www.actual4test.com/CRT-450_examcollection.html (240 Q&As Dumps, **30%OFF**)

Special Discount: **Freepdfdumps**)

NEW QUESTION: 62

A developer needs to confirm that a Contact trigger works correctly without changing the organization's data.

What should the developer do to test the Contact trigger?

A. Use Deploy from the VSCode IDE to deploy an 'Insert Contact' Apex class.

- B. Use the New button on the Salesforce Contacts Tab to create a new Contact record.
- C. Use the Open Execute Anonymous feature on the Developer Console to run an 'Insert Contact' DML statement.
- D. Use the Test menu on the Developer Console to run all test classes for the Contact trigger.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 63

How can a developer avoid exceeding governor limits when using Apex Triggers? (Choose 2)

- A. By using a helper class that can be invoked from multiple triggers
- B. By using Maps to hold data from query results
- C. By performing DML transactions on a list of sObjects.
- D. By using the Database class to handle DML transactions

Answer: B,C ([LEAVE A REPLY](#))

NEW QUESTION: 64

Which three statements are true regarding the @istest annotation? Choose 3 answers

- A. Products and pricebooks are visible in a test even if a class is annotated @istest (seealldata=false)
- B. A method annotated @istest (seealldata=true) in a class annotated @istest (seealldata=false) has access to all org data
- C. Profiles are visible in a test even if a class is annotated @istest (seealldata=false)
- D. A class containing test methods counts toward the apex code limit regardless of any @istest annotation (Missed)
- E. A method annotated @istest (seealldata=false) in a class annotated @istest (seealldata=true) has access to all org data

Answer: C,D,E ([LEAVE A REPLY](#))

NEW QUESTION: 65

A developer has the following code block:

```
public class PaymentTax {public static decimal SalesTax = 0.0875;} trigger
OpportunityLineItemTrigger on OpportunityLineItem (before insert, before update) {PaymentTax
PayTax = new PaymentTax();decimal ProductTax = ProductCost * XXXXXXXXXXXX;} To calculate
the productTax, which code segment would a developer insert at the XXXXXXXXXXXX to make
the value the class variable SalesTax accessible within the trigger?
```

- A. PayTax.SalesTax
- B. OpportunityLineItemTngger.SalesTax
- C. PaymentTax.SalesTax
- D. SalesTax

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 66

A developer needs to find information about @futuremethods that were invoked. From which system monitoring feature can the developer see this information?

- A. Asynchronous Jobs
- B. Apex Jobs
- C. Scheduled Jobs
- D. Background Jobs

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 67

Which two roll-up summary field types are required to find the average of values on detail records in a Master-Detail relationship?

- A. Roll-up summary field of type TOTAL
- B. Roll-up summary field of type NUM
- C. Roll-up summary field of type COUNT
- D. Roll-up summary field of type SUM

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 68

How many levels of child records can be returned in a single SOQL query from one parent object?

- A. 1
- B. 3
- C. 5
- D. 7

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 69

A developer must create a DrawList class that provides capabilities defined in the Sortable and Drawable interfaces. public interface Sortable { void sort(); } public interface Drawable { void draw(); } Which is the correct implementation?

A. Public class DrawList implements Sortable, Drawable {
public void sort() { /*implementation*/}
public void draw() { /*implementation*/}
}

B. Public class DrawList extends Sortable, Drawable {
public void sort() { /*implementation*/}
public void draw() { /*implementation*/}
}

C. Public class DrawList extends Sortable, extends Sortable, extends Drawable { public void sort() { /*implementation*/ } public void draw() { /* implementation */}

D. Public class DrawList implements Sortable, Implements Drawable {

```
public void sort() { /*implementation*/}
public void draw() { /*implementation*/}
]
```

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 70

Which two operations can be performed using a formula field? (Choose two.)

- A. Triggering a Process Builder
- B. Displaying the last four digits of an encrypted Social Security number
- C. Calculating a score on a Lead based on the information from another field
- D. Displaying an Image based on the Opportunity Amount

Answer: C,D ([LEAVE A REPLY](#))

NEW QUESTION: 71

A developer needs to create a Visualforce page that displays Case data. The page will be used by both support reps and support managers. The Support Rep profile does not allow visibility of the Customer_Satisfaction__c field, but the Support Manager profile does.

How can the developer create the page to enforce Field Level Security and keep future maintenance to a minimum?

- A. Create one Visualforce Page for use by both profiles.
- B. Use a new Support Manager permission set.
- C. Create a separate Visualforce Page for each profile.
- D. Use a custom controller that has the with sharing keywords.

Answer: D ([LEAVE A REPLY](#))

Explanation/Reference:

NEW QUESTION: 72

A developer needs to avoid potential system problems that can arise in a multi-tenant architecture. Which requirement helps prevent poorly written applications from being deployed to a production environment?

- A. SOQL queries must reference sObjects with their appropriate namespace.
- B. All Apex code must be annotated with the with sharing keyword.
- C. Unit tests must cover at least 75% of the application's Apex code
- D. All validation rules must be active before they can be deployed.

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 73

If apex code executes inside the execute() method of an Apex class when implementing the Batchable interface, which statements are true regarding governor limits? Choose 2 answers

- A. The Apex governor limits might be higher due to the asynchronous nature of the transaction.

(Missed)

- B. The apex governor limits are reset for each iteration of the execute() method. (Missed)
- C. The Apex governor limits are relaxed while calling the constructor of the Apex class.
- D. The Apex governor limits cannot be exceeded due to the asynchronous nature of the transaction,

Answer: A,B ([LEAVE A REPLY](#))

NEW QUESTION: 74

When an Account's custom picklist field called Customer Sentiment is changed to a value of "Confused", a new related Case should automatically be created.

Which two methods should a developer use to create this case? (Choose two.)

- A. Workflow Rule
- B. Process Builder
- C. Custom Button
- D. Apex Trigger

Answer: B,D ([LEAVE A REPLY](#))

NEW QUESTION: 75

A change set deployment from a sandbox to production fails due to a failure in a managed package unit test. The developer spoke with the managed package owner and they determined it is a false positive and can be ignored. What should the developer do to successfully deploy?

- A. Select 'Fast Deploy' to run only the tests that are in the change set.
- B. Edit the managed package's unit test.
- C. Select 'Run local tests' to run all tests in the org that are not in the managed package.
- D. Select 'Run local tests' to run only the tests that are in the change set.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 76

Which two statements can a developer use to throw a custom exception of type MissingFieldValueException? Choose 2 answers.

- A. Throw Exception (new MissingFieldValueException());
- B. Throw (MissingFieldValueException, 'Problem occurred');
- C. Throw new MissingFieldValueException();
- D. Throw new MissingFieldValueException ('Problem occurred');

Answer: C,D ([LEAVE A REPLY](#))

Valid CRT-450 Dumps shared by Actual4test.com for Helping Passing CRT-450 Exam!
Actual4test.com now offer the **newest CRT-450 exam dumps**, the Actual4test.com CRT-450 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com CRT-450 dumps with Test Engine here:

Special Discount: **Freepdfdumps**)

NEW QUESTION: 77

A developer must create a Lightning component that allows user to input Contact record information to create a Contact record, including a Salary__c custom field. What should the developer use, along with a lightning-record-edit-form, so that Salary__c field functions as a currency input and is only viewable and editable by users that have the correct field level permissions on Salary__c?

- A. `<lightning-formatted-number value="Salary__c" format-style="currency">`
`</lightning-formatted-number>`
- B. `<lightning-input-field field-name="Salary__c">`
`</lightning-input-field>`
- C. `<lightning-input type="number" value="Salary__c" formatter="currency">`
`</lightning-input>`
- D. `<lightning-input-currency value="Salary__c">`
`</lightning-input-currency>`

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 78

A company wants to create an employee rating program that allows employees to rate each other. An employees average rating must be displayed on the employee record. Employees must be able to create rating records, but are not allowed to create employee records. Which two actions should a developer take to accomplish this task?

- A. Create a lookup relationship between the Rating and Employee object.
- B. Create a master-detail relationship between the Rating and Employee objects.
- C. Create a trigger on the Rating object than updates a field on the Employee object.
- D. Create a roll-up summary field on the Employee and use AVG to calculate the average rating score.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 79

Which two condition cause workflow rules to fire? Choose 2 answers

- A. Updating record using bulk API
- B. Changing territory assignments of accounts and opportunities
- C. An Apex batch process that changes field values
- D. Converting leads to person account

Answer: A,C ([LEAVE A REPLY](#))

NEW QUESTION: 80

What is accurate statement about with sharing keyword? Choose 2 answers

- A. Both inner and outer classes can be declared as with sharing
- B. Inner classes do not inherit the sharing settings from the container class
- C. Inner classes inherit the sharing settings from the container class.
- D. Either inner or outer classes can be declared as with sharing, but not both

Answer: A,B ([LEAVE A REPLY](#))

NEW QUESTION: 81

A developer needs an Apex method that can process Account or Contact records. Which method signature should the developer use?

- A. public void doWork(Account | Contact)
- B. public void doWork(Record theRecord)
- C. public void doWork(sObject theRecord)
- D. public void doWork(Account Contact)

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 82

An Approval Process is defined in the Expense_Item__c object. A business rule dictates that whenever a user changes the Status to 'Submitted' on an Expense_Report__c record, all the Expense_Item__c records related to the expense report must enter the approval process individually.

Which approach should be used to ensure the business requirement is met?

- A. Create a Process Builder on Expense_Report__c to mark the related Expense_Item__c as submittable and a trigger on Expense_Item__c to submit the records for approval.
- B. Create two Process Builders, one on Expense_Report__c to mark the related Expense_Item__c as submittable and the second on Expense_Item__c to submit the records for approval.
- C. Create a Process Builder on Expense_Report__c with a 'Submit for Approval' action type to submit all related Expense_Item__c records when the criteria are met.
- D. Create a Process Builder on Expense_Report__c with an 'Apex' action type to submit all related Expense_Item__c records when the criteria is met.

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 83

How should a developer write unit tests for a private method in an Apex class?

- A. Add a test method in the Apex class.
- B. Use the SeeAllData annotation.
- C. Use the TestVisible annotation.
- D. Mark the Apex class as global.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 84

Which three process automations can immediately send an email notification to the owner of an Opportunity when its Amount is changed to be greater than \$10,000? (Choose three.)

- A. Process Builder
- B. Escalation Rule
- C. Flow Builder
- D. Approval Process
- E. Workflow Rule

Answer: A,D,E ([LEAVE A REPLY](#))

Explanation/Reference:

NEW QUESTION: 85

Universal Containers stores Orders and Line Items in Salesforce. For security reasons, financial representatives are allowed to see information on the Order such as order amount, but they are not allowed to see the Line Items on the Order.

Which type of relationship should be used?

- A. Master-Detail
- B. Indirect Lookup
- C. Direct Lookup
- D. Lookup

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 86

What can be used to delete components from production?

- A. An ant migration tool deployment with a destructiveChanges XML file and an empty package.xml file
- B. A change set deployment with a destructiveChanges XML file
- C. An ant migration tool deployment with a desctuctiveChanges XML file and the components to delete in the package.xml file
- D. A change set deployment with the delete option checked

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 87

Which two declarative process automation features can be directly invoked when a field value changes on a record? (Choose two.)

- A. Process Builder processes
- B. Validation rules
- C. Cloud Flow Designer flows
- D. Workflow rules

Answer: A,D ([LEAVE A REPLY](#))

NEW QUESTION: 88

What is a valid source and destination pair that can send or receive change sets? (Choose 2)

- A. Sandbox to Production
- B. Sandbox to Sandbox
- C. Developer Edition to Sandbox
- D. Developer Edition to Production

Answer: A,B (LEAVE A REPLY)

NEW QUESTION: 89

A Platform Developer needs to write an Apex method that will only perform an action if a record is assigned to a specific Record Type.

Which two options allow the developer to dynamically determine the ID of the required Record Type by its name? (Choose two.)

- A. Use the `getRecordTypeInfoByName()` method in the `DescribeSObjectResult` class.
- B. Execute a SOQL query on the `RecordType` object.
- C. Make an outbound web services call to the SOAP API.
- D. Hardcode the ID as a constant in an Apex class.

Answer: A,B (LEAVE A REPLY)

NEW QUESTION: 90

A developer has JavaScript code that needs to be called by controller functions in multiple Aura components by extending a new abstract component.

Which resource in the abstract Aura component bundle allows the developer to achieve this?

- A. controllers
- B. `superRender.js`
- C. `helper.js`
- D. `renderer.js`

Answer: C (LEAVE A REPLY)

NEW QUESTION: 91

A developer writes the following code:

```
List<Account> acc = [SELECT Id FROM Account LIMIT 10];
Delete acc;
Database.emptyRecycleBin(acc);

System.Debug(Limits.getDMLStatements() + ', ' + Limits.getLimitDMLStatements());
```

What is the result of the debug statement?

- A. 1, 100
- B. 2, 150
- C. 2, 200
- D. 1, 150

Answer: B (LEAVE A REPLY)

Valid CRT-450 Dumps shared by Actual4test.com for Helping Passing CRT-450 Exam! Actual4test.com now offer the **newest CRT-450 exam dumps**, the Actual4test.com CRT-450 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com CRT-450 dumps with Test Engine here:

https://www.actual4test.com/CRT-450_examcollection.html (240 Q&As Dumps, **30%OFF**

Special Discount: Freepdfdumps)

NEW QUESTION: 92

What should be used to create scratch orgs?

- A. Developer Console
- B. Salesforce CLI
- C. Workbench
- D. Sandbox refresh

Answer: B (LEAVE A REPLY)

NEW QUESTION: 93

In which two trigger types can a developer modify the new sObject records that are obtained by the trigger.new context? Choose 2 answers

- A. Before insert
- B. After update
- C. After insert
- D. Before update

Answer: A,D (LEAVE A REPLY)

NEW QUESTION: 94

A developer needs to provide a Visualforce page that lets users enter Product-specific details during a Sales cycle. How can this be accomplished? (Choose 2)

- A. Download a Managed Package from the AppExchange that provides a custom Visualforce page to modify.
- B. Download an Unmanaged Package from the AppExchange that provides a custom Visualforce page to modify.
- C. Create a new Visualforce page and an Apex controller to provide Product data entry.
- D. Copy the standard page and then make a new Visualforce page for Product data entry.

Answer: (SHOW ANSWER)

NEW QUESTION: 95

A developer is debugging the following code to determinate why Accounts are not being created Account a = new Account(Name = 'A'); Database.insert(a, false); How should the code be altered to help debug the issue?

- A. Set the second insert method parameter to TRUE
- B. Collect the insert method return value a Saveresult record
- C. Add a System.debug() statement before the insert method
- D. Add a try/catch around the insert method

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 96

What is an important consideration when developing in a multi-tenant environment?

- A. Org-wide data security determines whether other tenants can see data in multiple orgs on the same instance.
- B. Polyglot persistence provides support for a global, multilingual user base in multiple orgs on multiple instances.
- C. Unique domain names take the place of namespaces for code developed for multiple orgs on multiple instances.
- D. Governor limits prevent tenants from impacting performance in multiple orgs on the same instance.

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 97

From which 2 locations can a developer determine the overall code coverage for a sandbox?

- A. The test suite run panel of the developer console
- B. The tests tab of the developer console
- C. The apex test execution page
- D. The apex classes setup page

Answer: B,D ([LEAVE A REPLY](#))

NEW QUESTION: 98

Which three web technologies can be integrated into a Visualforce page? Choose 3 answers

- A. PHP
- B. CSS (Missed)
- C. Java
- D. JavaScript (Missed)
- E. HTML (Missed)

Answer: B,D,E ([LEAVE A REPLY](#))

NEW QUESTION: 99

A developer has a Visualforce page and custom controller to save Account records. The developer wants to display any validation rule violations to the user.

How can the developer make sure that validation rule violations are displayed?

- A. Add custom controller attributes to display the message.
- B. Use a try/catch with a custom exception class.

- C. Include <apex:messages> on the Visualforce page.
- D. Perform the DML using the Database.upsert() method.

Answer: ([SHOW ANSWER](#))

Explanation/Reference:

NEW QUESTION: 100

What is the requirement for a class to be used as a custom Visualforce controller?

- A. Any top-level Apex class that has a constructor that returns a PageReference
- B. Any top-level Apex class that extends a PageReference
- C. Any top-level Apex class that has a default, no-argument constructor
- D. Any top-level Apex class that implements the controller interface

Answer: D ([LEAVE A REPLY](#))

Explanation/Reference:

NEW QUESTION: 101

How can a developer avoid exceeding governor limits when using an Apex Trigger? choose 2 answers

- A. By using the Database class to handle DML transactions.
- B. By using Maps to hold data from query results.
- C. By using a helper class that can be invoked from multiple triggers.
- D. By performing DML transactions on lists of SObjects.

Answer: B,D ([LEAVE A REPLY](#))

NEW QUESTION: 102

A developer wants to display all of the available record types for a Case object. The developer also wants to display the picklist values for the Case.Status field. The Case object and the Case Status field are on a custom visualforce page.

Which action can the developer perform to get the record types and picklist values in the controller?

Choose 2 answers

- A. Use SOQL to query Case records in the org to get all value for the Status picklist field.
- B. Use SOQL to query Case records in the org to get all the RecordType values available for Case.
- C. Use Schema.RecordTypeInfo returned by Case.SObjectType describe().getRecordTypeInfos()
- D. Use Schema.PicklistEntry returned by Case Status describe().getPicklistValues().

Answer: C,D ([LEAVE A REPLY](#))

NEW QUESTION: 103

Which three options allow a developer to use custom styling in a Visualforce page? (Choose three.)

- A. <apex:stylesheets>tag
- B. Inline CSS
- C. <apex:stylesheet> tag
- D. A static resource
- E. <apex:style>tag

Answer: B,C,D ([LEAVE A REPLY](#))

NEW QUESTION: 104

Requirements state that a child record be to deleted when its parent is deleted, and a child can be moved to a different parent when necessary. Which type of relationship should be built between the parent and child objects in Schema Builder to support these requirements?

- A. Lookup Relationship from to child to the parent
- B. Master-Detail relationship
- C. Lookup Relationship from to parent to the child
- D. Child relationship

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 105

A developer has the following code:

```
try {List nameList;Account a;String s =
a.Name;nameList.add(s);} catch (ListException le ) {System.debug(' List Exception ');} catch
(NullPointerException npe)
{System.debug('
NullPointerException ');} catch (Exception e) {System.debug(' Generic Exception ');} What
message will be logged?
```

- A. Generic Exception
- B. List Exception
- C. No message is logged
- D. NullPointerException

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 106

From which two locations can a developer determine the overall code coverage for a sandbox?
Choose two answers

- A. The Test Tab of the Developer Console
- B. The Test Suite Run panel the Developer Console
- C. The Apex classes setup page
- D. The Apex Test Execution page

Answer: A,C ([LEAVE A REPLY](#))

Valid CRT-450 Dumps shared by Actual4test.com for Helping Passing CRT-450 Exam! Actual4test.com now offer the **newest CRT-450 exam dumps**, the Actual4test.com CRT-450 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com CRT-450 dumps with Test Engine here:

https://www.actual4test.com/CRT-450_examcollection.html (240 Q&As Dumps, **30%OFF**

Special Discount: Freepdfdumps)

NEW QUESTION: 107

What is the maximum number of SOQL queries used by the following code? List<Account> aList =

```
[SELECT Id FROM Account LIMIT 5]; for (Account a : aList){ List<Contact> cList = [SELECT Id FROM Contact WHERE AccountId = :a.Id]; }
```

- A. 6
- B. 2
- C. 5
- D. 1

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 108

When would a developer use a custom controller instead of a controller extension? Choose 2 answers:

- A. When a Visualforce page does not reference a single primary object.
- B. When a Visualforce page needs to add new actions to a standard controller.
- C. When a Visualforce page needs to replace the functionality of a standard controller.
- D. When a Visualforce page should not enforce permissions or field-level security.

Answer: ([SHOW ANSWER](#)**)**

NEW QUESTION: 109

Which aspect of Apex programming is limited due to multitenancy?

- A. The number of active Apex classes
- B. The number of records processed in a loop
- C. The number of records returned from database queries
- D. The number of methods in an Apex Class

Answer: ([SHOW ANSWER](#)**)**

NEW QUESTION: 110

Manage package can be created in which type of org?

- A. Developer Edition
- B. Partial copy sandbox
- C. Unlimited edition

D. Developer sandbox

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 111

The initial value for a number field on a record is 1. A user updated the value of the number field to 10. This action invokes a workflow field update, which changes the value of the number field to 11. After the workflow field update, an update trigger fires. What is the value of the number field of the object that is obtained from `Trigger.old`?

- A. 1
- B. 11
- C. Null
- D. 10

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 112

A developer needs to create a custom Visualforce button for the Opportunity object page layout that will cause a web service to be called and redirect the user to a new page when clicked. Which three attributes need to be defined in the `<apex:page>` tag of the Visualforce page to enable this functionality? Choose three answers.

- A. StandardController
- B. Controller
- C. Extensions
- D. Action

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 113

A developer is asked to create a PDF quote document formatted using the company's branding guidelines, and automatically save it to the Opportunity record.

Which two ways should a developer create this functionality? (Choose two.)

- A. Install an application from the AppExchange to generate documents.
- B. Create a Visualforce page with custom styling.
- C. Create an email template and use it in Process Builder.
- D. Create a visual flow that implements the company's formatting.

Answer: A,B ([LEAVE A REPLY](#))

Explanation

NEW QUESTION: 114

A recursive transaction is initiated by a DML statement creating records for these two objects:

1. Accounts
2. Contacts

The Account trigger hits a stack depth of 16.

Which statement is true regarding the outcome of the transaction?

- A. The transaction fails only if the Contact trigger stack depth is greater or equal to 16.
- B. The transaction succeeds and all changes are committed to the database.
- C. The transaction succeeds as long as the Contact trigger stack depth is less than 16.
- D. The transaction fails and all the changes are rolled back.

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 115

Which two practices should be used for processing records in a trigger? Choose 2 answers

- A. Use a Map to reduce the number of SOQL calls
- B. Use (callout=true) to update an external system
- C. Use @future methods to handle DML operations.
- D. Use a Set to ensure unique values in a query filter

Answer: ([SHOW ANSWER](#)**)**

NEW QUESTION: 116

What is considered the primary purpose for creating Apex tests?

- A. To ensure every use case of the application is covered by a test
- B. To guarantee at least 50% of code is covered by unit tests before it is deployed
- C. To confirm all classes and triggers compile successfully
- D. To confirm every trigger is executed at least once

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 117

A Visualforce page has a standard controller for an object that has a lookup relationship to a parent object. How can a developer display data from the parent record on the page?

- A. By adding a second standard controller to the page for the parent record.
- B. By using merge field syntax to retrieve data from the parent record.
- C. By using SOQL on the Visualforce page to query for data from the parent record.
- D. By using a roll-up formula field on the child record to include data from the parent record.

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 118

Which type of code represents the Controller in MVC architecture on the Force.com platform?

(Choose

2)

- A. Custom Apex and JavaScript code that is used to manipulate data.
- B. StandardController system methods that are referenced by Visualforce.
- C. JavaScript that is used to make a menu item display itself.
- D. A static resource that contains CSS and images.

Answer: A,B ([LEAVE A REPLY](#))

NEW QUESTION: 119

A developer wants multiple test classes to use the same set of test data.

How should the developer create the test data?

- A. Use the SeeAllData=true annotation in each test class.
- B. Define variables for test records in each test class.
- C. Create a Test Setup method for each test class.
- D. Reference a test utility class in each test class.

Answer: A (LEAVE A REPLY)

NEW QUESTION: 120

Which two are best practices when it comes to component and application event handling?

Choose 2 answers

- A. Use component events to communicate actions that should be handled at the application level.
- B. Reuse the event logic in a component bundle, by putting the logic in the helper. (Missed)
- C. Try to use application events as opposed to component events.
- D. Handle low-level events in the event handler and re-fire them as higher-level events. (Missed)

Answer: B,D (LEAVE A REPLY)

NEW QUESTION: 121

What are two considerations for deciding to use a roll-up summary field? Choose 2 answer's partner.

- A. Roll-up cannot be performed on formula fields.
- B. Roll-up summary can be performed on formula fields, but if their formula contains an #Error result, it may affect the summary value.
- C. Roll-up cannot be performed on formula fields that use cross-object references or on-the-fly calculations such as NOW().
- D. Roll-up summary fields do not cause validation rules on the parent object unless that object is edited separately.

Answer: B,C (LEAVE A REPLY)

Valid CRT-450 Dumps shared by Actual4test.com for Helping Passing CRT-450 Exam!
Actual4test.com now offer the **newest CRT-450 exam dumps**, the Actual4test.com CRT-450 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com CRT-450 dumps with Test Engine here:

https://www.actual4test.com/CRT-450_examcollection.html (240 Q&As Dumps, **30%OFF**

Special Discount: Freepdfdumps)

NEW QUESTION: 122

A developer needs to prevent the creation of request records when certain conditions exist in the system. A RequestLogic class exists to checks the conditions. What is the correct implementation?

- A.** Trigger RequestTrigger on Request (after insert) {
if (RequestLogic.isValid{Request})
Request.addError {'Your request cannot be created at this time.'};
}
- B.** Trigger RequestTrigger on Request (before insert) {
if (RequestLogic.isvalid{Request})
Request.addError {'Your request cannot be created at this time.'};
}
- C.** Trigger RequestTrigger on Request (after insert) {
RequestLogic.validateRecords {trigger.new};
}
- D.** Trigger RequestTrigger on Request (before insert) {
RequestLogic.validateRecords {trigger.new};
}

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 123

Using DescribeSObjectResult, which Apex method can a developer use to determine if the current user can edit records for an object?

- A.** canEdit()
- B.** isEditable()
- C.** isUpdateable()
- D.** canUpdate()

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 124

A developer tasked with creating a schema to track Movies, Actors, and contracts. A single movie can have many contracts and a single actor can have many contracts. Each contract is owned and actively managed by a single user. Which schema should be created to enable user to easily manage the contract they own; without requiring access to the movie or the actor records?

- A.** A lookup relationship to the movie object and a lookup relationship to the actor object
- B.** A master detail relationship to the movie object and a master detail relationship to the actor object
- C.** A master detail relationship to the movie object and a lookup relationship to the actor object
- D.** A lookup relationship to the movie object and a master detail relationship to the actor object

Answer: ([SHOW ANSWER](#)**)**

NEW QUESTION: 125

When a Task is created for a Contact, how can a developer prevent the task from being included on the Activity Timeline of the Contact's Account record?

- A. Create a Task trigger to set the Account field to NULL.
- B. In Activity Setting, uncheck Roll up activities to a contact's primary account.
- C. Use Process Builder to create a process to set the Task Account field to blank.
- D. By default, tasks do not display on the Account Activity Timeline.

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 126

What should a developer working in a sandbox use to exercise a new test Class before the developer deploys that test production? Choose 2 answers

- A. The Apex Test Execution page in Salesforce Setup.
- B. The REST API and ApexTestRun method
- C. The Test menu in the Developer Console.
- D. The Run Tests page in Salesforce Setup.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 127

What are three ways for a developer to execute tests in an org? Choose 3.

- A. Setup Menu
- B. Bulk API
- C. Developer Console
- D. Metadata API
- E. ToolingAPI

Answer: A,C,E ([LEAVE A REPLY](#))

NEW QUESTION: 128

A developer needs an Apex method that can process Account or Contact records. Which method signature should the developer use?

- A. Public void doWork(sObject theRecord)
- B. Public void doWork(Account || Contatc)
- C. Public void doWork(Record theRecord)
- D. Public void doWork(Account Contact)

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 129

Where can debug log filter settings be set? Choose 2 answers

- A. The Log Filters tab on a class or trigger detail page.
- B. The Filters link by the monitored user's name within the web UI.
- C. The Show More link on the debug log's record.
- D. On the monitored user's name.

Answer: A,B ([LEAVE A REPLY](#))

NEW QUESTION: 130

Which approach should a developer use to add pagination to a Visualforce page?

- A. The extensions attribute for a page
- B. A StandardController
- C. A StandardSetController
- D. The Action attribute for a page

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 131

What is the return data type when `ApexPages.currentPage().getParameters()` is used to retrieve URL parameters from a visualforce controller?

- A. List
- B. Map
- C. Enum
- D. String[]

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 132

How many level of child records can be returned in a single SOQL query from one parent object

- A. 5
- B. 1
- C. 7
- D. 3

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 133

Opportunity opp=[SELECT Id,StageName FROM Opportunity LIMIT 1]; Given the code above,how can a developer get the label for the StageName field?

- A. Call `Opp.StageName.Label`
- B. Call `Opportunity.StageName.getDescribe().getLabel()`
- C. Call `Opp.StageName.getDescri`
- D. Call `Opportunity.StageName.Label`

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 134

Which message is logged by the code below?

```

try{
    List<Id> idList;
    Account a;
    insert a;
    Id acctId = a.Id;
    idList.add( acctId );
}catch ( ListException le ){
    System.debug('List Exception');
}catch ( NullPointerException npe ){
    System.debug('NullPointer Exception');
}catch ( Exception e ){
    System.debug('Generic Exception');
}

```

- A. NullPointer Exception
- B. No message is logged.
- C. List Exception
- D. Generic Exception

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 135

Universal Containers requires Service Representatives to update all Cases at least one every three days.

To make sure of this policy is obeyed, a developer has been asked to implement a field that displays the number of days since the last Case update. What should the developer use to configure the solution?

- A. Formula field
- B. Workflow rule
- C. Scheduled Apex Class
- D. Process Builder

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 136

Which two are true regarding a Dyno? Choose 2 answers

- A. Is a lightweight Linux container used in a collection to run Heroku applications
- B. Is a light weight VM used to run code on the Heroku Platform
- C. Has Ephemeral filesystems and is rebooted every 24 hours.
- D. Has the ability to sleep as a standard and performance Dyno

Answer: A,C ([LEAVE A REPLY](#))

Valid CRT-450 Dumps shared by Actual4test.com for Helping Passing CRT-450 Exam!
 Actual4test.com now offer the **newest CRT-450 exam dumps**, the Actual4test.com CRT-450 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com CRT-450 dumps with Test Engine here:

Special Discount: **Freepdfdumps**)

NEW QUESTION: 137

What is the minimum log level needed to see user-generated debug statements?

- A. FINE
- B. INFO
- C. DEBUG
- D. WARN

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 138

What is the proper process for an Apex Unit Test

- A. Query for test data using SeeAllData = true. Execute runAllTests(). Verify that the results are correct.
- B. Query for test data using SeeAllData = true. Call the method being tested. Verify that the results are correct.
- C. Create data for testing. Execute runAllTests(). Verify that the results are correct.
- D. Create data for testing. Call the method being tested. Verify that the results are correct.

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 139

Which Apex collection is used to ensure that all values are unique?

- A. A List
- B. An Enum
- C. A Set
- D. An sObject

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 140

The Review_c object have a lookup relationship to the job_Application_c object. The job_Application_c object has a master detail relationship up to the position_c object. The relationship is based on the auto populated defaults?

What is the recommended way to display field data from the related Review _C records a Visualforce page for a single Position_c record? Select one of the following:

- A. Utilize the Standard Controller for Position_c and cross-object Formula Fields on the Review_c object to display Review_c data.
- B. Utilize the Standard Controller for Position_c and a Controller Extension to query for Review_c data.
- C. Utilize the Standard Controller for Position_c and expression syntax in the Page to display related Review_c through the Job_Application_c inject.

D. Utilize the Standard Controller for Position_c and cross-object Formula Fields on the Job_Application_c object to display Review_c data.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 141

What is a capability of the Developer Console?

- A. Execute Anonymous Apex code, Run REST API, deploy code changes.
- B. Execute Anonymous Apex code, Create/Edit code, view Debug Logs.
- C. Execute Anonymous Apex code, Run REST API, create/Edit code.
- D. Execute Anonymous Apex code, Create/Edit code, Deploy code changes.

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 142

A developer needs to create a Visualforce page that will override the standard Account edit button. The page will be used to validate the account's address using a SOQL query. The page will also allow the user to make edits to the address. Where would the developer write the Account address verification logic?

- A. In a Custom Controller.
- B. In a Standard Extension.
- C. In a Controller Extension.
- D. In a Standard Controller.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 143

A Platform Developer needs to implement a declarative solution that will display the most recent Closed Won date for all Opportunity records associated with an Account.

Which field is required to achieve this declaratively?

- A. Roll-up summary field on the Account object
- B. Cross-object formula field on the Opportunity object
- C. Cross-object formula field on the Account object
- D. Roll-up summary field on the Opportunity object

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 144

A lead object has a custom field Prior_Email__c. The following trigger is intended to copy the current Email into the Prior_Email__c field any time the Email field is changed:

```

trigger test on Lead (before update) {
    for(Lead ld: trigger.new)
    {
        if(ld.Email != trigger.oldMap.get (ld.ld).email)
        {
            ld.Prior_Email__c = trigger.old.ap.get(ld.ld).email;
            update ld;
        }
    }
}

```

Which type of exception will this trigger cause?

- A. A limit exception when doing a bulk update
- B. A null reference exception
- C. A DML exception
- D. A compile time exception

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 145

Which process automation should be used to send an outbound message without using Apex code?

- A. Workflow Rule
- B. Flow Builder
- C. Approval Process
- D. Process Builder

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 146

Which data structure is returned to a developer when performing a SOSL search?

- A. A list of lists of sObjects.
- B. A list of sObjects.
- C. A map of sObject types to a list of sObjects
- D. A map of sObject types to a list of lists of subjects

Answer: (SHOW ANSWER)

NEW QUESTION: 147

Universal Containers wants Opportunities to be locked from editing when reaching the Closed/Won stage.

Which two strategies should a developer use to accomplish this? (Choose two.)

- A. Use a validation rule.
- B. Use a Trigger.
- C. Use a Visual Workflow.
- D. Use the Process Automation Settings.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 148

Which two queries can a developer use in a Visualforce controller to protect against SOQL injection vulnerabilities? Choose 2 answers

- A.** `String qryName = % + String.enforceSecurityChecks(name)+ % ;`
`String qryString = SELECT Id FROM Contact WHERE Name LIKE :qryName ;`
`List queryResults = Database.query(qryString);`
- B.** `String qryName = % + String.escapeSingleQuotes(name)+ % ;`
`String qryString = SELECT Id FROM Contact WHERE Name LIKE :qryName ;`
`List queryResults = Database.query(qryString);`
- C.** `String qryName = % + name % ;`
`String qryString = SELECT Id FROM Contact WHERE Name LIKE :qryName ;`
`List queryResults = Database.query(qryString);`
- D.** `String qryString = SELECT Id FROM Contact WHERE Name LIKE :qryName ;`
`List queryResults = Database.query(qryString);`

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 149

Given the code block: `Integer x; For(x=0;x<10; x+=2) { If(x==8) break; If(x==10) break; } System.debug(x);` Which value will the system debug statement display?

- A.** 4
- B.** 2
- C.** 10
- D.** 8

Answer: **D** ([LEAVE A REPLY](#))

NEW QUESTION: 150

A developer wants to store a description of a product that can be entered on separate lines by a user during product setup and later displayed on a Visualforce page for shoppers.

Which field type should the developer choose to ensure that the description will be searchable in the custom Apex SOQL queries that are written?

- A.** Text Area
- B.** Text
- C.** Text Area (Long)
- D.** Text Area (Rich)

Answer: **A** ([LEAVE A REPLY](#))

NEW QUESTION: 151

A developer is creating a Visualforce page that allows users to create multiple Opportunities. The developer is asked to verify the current user's default Opportunity record type, and set certain

default values based on the record type before inserting the record. How can the developer find the current user's default record type?

- A. Use the Schema.userInfo.Opportunity.getDefaultRecordType() method.
- B. Create the opportunity and check the opportunity.recordType before inserting, which will have the record ID of the current user's default record type
- C. Query the Profile where the ID equals userInfo.getProfileID() and then use the profile.Opportunity.getDefaultRecordType() method.
- D. Use Opportunity.SObjectType.getDescribe().getRecordTypeInfoInfos() to get a list of record types, and iterate through them until isDefaultRecordTypeMapping() is true.

Answer: ([SHOW ANSWER](#))

Valid CRT-450 Dumps shared by Actual4test.com for Helping Passing CRT-450 Exam! Actual4test.com now offer the **newest CRT-450 exam dumps**, the Actual4test.com CRT-450 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com CRT-450 dumps with Test Engine here:

https://www.actual4test.com/CRT-450_examcollection.html (**240** Q&As Dumps, **30%OFF**

Special Discount: [Freepdfdumps](#))

NEW QUESTION: 152

Which exception type cannot be caught?

- A. LimitException
- B. NoAccessException
- C. A Custom Exception
- D. CalloutException

Answer: A ([LEAVE A REPLY](#))

Explanation

NEW QUESTION: 153

What is the data type returned by the following SOSL search? {FIND 'Acme*' in name fields returning account,opportunity};

- A. List<List<sObject>>
- B. Map<Id,sObject>
- C. Map<sObject,sObject>
- D. List<List<Account>,List<Opportunity>

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 154

A developer has a requirement to create an Order when an Opportunity reaches a 'Closed-Won' status.

Which tool should be used to implement this requirement?

- A. Lightning Component
- B. Apex Trigger
- C. Process Builder
- D. Lightning Flow

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 155

Given the code below, what can be done so that recordcount can be accessed by a test class, but not by a non-test class? `Public class mycontroller{ private integer recordcount; }`

- A. Add a seealldata annotation to the test class
- B. Add the testvisible annotation to recordcount
- C. Add the testvisible annotation to the mycontroller class
- D. Change recordcount from private to public

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 156

A developer is creating an application to track engines and their parts. An individual part can be used in different types of engines. What data model should be used to track the data and to prevent orphan records?

- A. Create a junction object to relate many engines to many parts through a master-detail relationship
- B. Create a master-detail relationship to represent the one-to-many model of engines to parts.
- C. Create a junction object to relate many engines to many parts through a lookup relationship
- D. Create a lookup relationship to represent how each part relates to the parent engine object.

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 157

The Sales Management team hires a new intern. The intern is not allowed to view Opportunities, but needs to see the Most Recent Closed Date of all child Opportunities when viewing an Account record. What would a developer do to meet this requirement?

- A. Create a formula field on the Account object that performs a MAX on the Opportunity Close Date field.
- B. Create a roll-up summary field on the Account object that performs a MAX on the Opportunity Close Date field.
- C. Create a Workflow rule on the Opportunity object that updates a field on the parent Account.
- D. Create a trigger on the Account object that queries the Close Date of the most recent Opportunities.

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 158

A developer wants to display all of the picklist entries for the Opportunity StageName field and all of the available record types for the Opportunity object on a Visualforce page.

Which two actions should the developer perform to get the available picklist values and record types in the controller? (Choose two.)

- A. Use Schema.RecordTypeInfo returned by Opportunity.SObjectType.getDescribe().getRecordTypeInfos().
- B. Use Schema.PicklistEntry returned by Opportunity.SObjectType.getDescribe().getPicklistValues ().
- C. Use Schema.RecordTypeInfo returned by RecordType.SObjectType.getDescribe().getRecordTypeInfos().
- D. Use Schema.PicklistEntry returned by Opportunity.StageName.getDescribe().getPicklistValues ().

Answer: (SHOW ANSWER)

Explanation

NEW QUESTION: 159

Which option would a developer use to display the Accounts created in the current week and the number of related Contacts using a debug statement in Apex?

- A. For(Account acc: [SELECT Id, Name, (SELECT Id, Name FROM Contacts) FROM Account WHERE CreatedDate = CURRENT_WEEK]){ List cons = acc.Contacts; System.debug(acc.Name + ' has ' + cons.size() + 'Contacts'); }
- B. For(Account acc: [SELECT Id, Name, Account.Contacts FROM Account WHERE CreatedDate = THIS_WEEK]){ List cons = acc.Account.Contacts; System.debug(acc.Name + ' has ' + cons.size() + 'Contacts' }
- C. For(Account acc: [SELECT Id, Name,(SELECT Id, Name FROM Contacts) FROM Account WHERE CreatedDate = THIS_WEEK]) { List cons = acc.Contacts; System.debug(acc.Name + ' has ' + cons.size() + 'Contacts'; }
- D. For(Account acc:[SELECT Id, Name, Account.Contacts FROM Account WHERE CreatedDate = CURRENT_WEEK]) { List cons = acc.Account.Contacts; System.debug(acc.Name + ' has ' + cons.size() + 'Contacts'); }

Answer: (SHOW ANSWER)

NEW QUESTION: 160

A developer writes the following code:

```
List<Account> acc = [SELECT Id FROM Account LIMIT 10];
Delete acc;
Database.emptyRecycleBin(acc);

System.Debug(Limits.getDMLStatements() + ', ' + Limits.getLimitDMLStatements());
```

What is the result of the debug statement?

- A. 2, 200

- B. 1, 150
- C. 2, 150
- D. 1, 100

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 161

Which tool can deploy destructive changes to Apex classes in production?

- A. Developer Console
- B. Salesforce Setup
- C. Change Sets
- D. Workbench

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 162

What is the order of operations when a record is saved in Salesforce?

- A. Triggers, workflow, process flows, commit
- B. Workflow, process flows, triggers, commit
- C. Workflow, triggers, process flows, commit
- D. Process flows, triggers, workflow, commit

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 163

A developer wants to store a description of a product that can be entered on separate lines by a user during product setup and later displayed on a Visualforce page for shoppers. Which field type should the developer choose to ensure that the description will be searchable in the custom Apex SOQL queries that are written?

- A. Text
- B. Text Area (Long)
- C. Text Area
- D. Text Area (Rich)

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 164

How would a developer determine if a CustomObject__c record has been manually shared with the current user in Apex?

- A. By querying the role hierarchy.
- B. By querying CustomObject__Share.
- C. By calling the isShared() method for the record.
- D. By calling the profile settings of the current user.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 165

Which action can a developer take to reduce the execution time of the following code?

```
List<account> allaccounts = [select id from account]; list<account> allcontacts = [select id, accountid from contact]; for (account a :allaccounts){ for (contact c:allcontacts){ if(c.accountid = a.id){ //do work } } }
```

- A. Use a map <id,contact> for allaccounts
- B. Put the account loop inside the contact loop
- C. Add a group by clause to the contact SOQL
- D. Create an apex helper class for the SOQL

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 166

Which Salesforce feature allows a developer to see when a user last logged in to Salesforce if real-time notification is not required?

- A. Event Monitoring Log
- B. Calendar Events
- C. Asynchronous Data Capture Events
- D. Developer Log

Answer: A ([LEAVE A REPLY](#))

Valid CRT-450 Dumps shared by Actual4test.com for Helping Passing CRT-450 Exam! Actual4test.com now offer the **newest CRT-450 exam dumps**, the Actual4test.com CRT-450 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com CRT-450 dumps with Test Engine here:

https://www.actual4test.com/CRT-450_examcollection.html (240 Q&As Dumps, **30%OFF**

Special Discount: Freepdfdumps)

NEW QUESTION: 167

A developer created a helper class with a method that can be called from Visualforce pages, web services, triggers, and of even anonymous code. When the method is called from a trigger, the developer needs to execute logic that should not be executed if the method is called from anywhere else. How can the developer determine if the code is executed in a trigger context?

- A. Check if Trigger.newMap !=null.
- B. Use the executeOnTrigger annotation on the method definition.
- C. Check if System.executionContext =='Trigger'.
- D. Check if Trigger.isExecuting ==true

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 168

A developer needs to test an Invoicing system integration. After reviewing the number of transactions required for the test, the developer estimates that the test data will total about 2 GB of data storage.

Production data is not required for the integration testing.

Which two environments meet the requirements for testing? (Choose two.)

- A. Partial Sandbox
- B. Full Sandbox
- C. Developer Sandbox
- D. Developer Pro Sandbox
- E. Developer Edition

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 169

What can used to delete components from production?

- A. A change set deployment with the delete option checked
- B. An ant migration tool deployment with destructivechanges xml file and the components to delete in the package .xml file
- C. A change set deployment with a destructivechanges XML file
- D. An ant migration tool deployment with a destructivechanges XML file and an empty package .xml file

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 170

Which one do you like?

What should a developer consider for an environment that has over 10,000 Case records?



```
Given the following Anonymous Block:
List<Case> casesToUpdate = new List<Case>();
for(Case thisCase : [Select Id, Status FROM Case LIMIT 50000]){
  thisCase.Status = 'Working';
  casesToUpdate.add(thisCase);
}
try{
  Database.update(casesToUpdate, false);
}catch(Exception e){
  System.debug(e.getMessage());
}
```

- A. The try/catch block will handle exceptions thrown by governor limits.
- B. The try/catch block will handle any DML exceptions thrown.
- C. The transaction will fail due to exceeding the governor limit.
- D. The transaction will succeed and changes will be committed.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 171

An sObject named Application_c has a lookup relationship to another sObject named Position_c. Both Application_c and Position_c have a picklist field named Status_c. When the Status_c field on Position_c is updated, the Status_c field on Application_c needs to be populated automatically with the same value, and execute a workflow rule on Application_c. How can a developer accomplish this?

- A. By configuring a cross-object field update with a workflow.
- B. By using an Apex trigger with a DML operation.
- C. By changing Application_c.Status_c into a formula field.
- D. By changing Application_c.Status_c into a roll-up summary field.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 172

Which type of code represents the Model in the MVC architecture when using Apex and Visualforce pages?

- A. Custom JavaScript that processes a list of Account records
- B. A Controller Extension method that uses SOQL to query for a list of Account records
- C. A Controller Extension method that saves a list of Account records
- D. A list of Account records returned from a Controller Extension method

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 173

A developer has created a Visualforce Page and Apex Controller that uses the With Sharing keyword.

The page will be used of by Sales Managers and should only display Accounts owned by Sales Representatives who report to the running Sales Manager. The organization-wide sharing for Accounts is set to Private. Which additional set of stops should the developer take?

- A. Create one Profile, one Permission Set, and two Roles.
- B. Create one Profile, one Permission Set, and one Role.
- C. Create one Profile, two Permission Sets, and one Role.
- D. Create two Profiles, one Permission Set, and one Role.

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 174

Universal Containers requires Service Representatives to update all Cases at least one every three days. To make sure of this policy is obeyed, a developer has been asked to implement a field that displays the number of days since the last Case update. What should the developer use to configure the solution?

- A. Scheduled Apex Class
- B. Process Builder
- C. Formula field
- D. Workflow rule

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 175

What is a capability of the <ltng:require> tag that is used for loading external Javascript libraries in Lightning Component? (Choose three.)

- A. Loading scripts in parallel.
- B. One-time loading for duplicate scripts.
- C. Loading externally hosted scripts.
- D. Specifying loading order.
- E. Loading files from Documents.

Answer: A,B,D ([LEAVE A REPLY](#))

NEW QUESTION: 176

A sales manager wants to make sure that whenever an opportunity stage is changed to 'Closed Won', a new case will be created for the support team to collect necessary information from the customer. How should a developer accomplish this?

- A. Set up a validation rule on the Opportunity Stage.
- B. Create a Process Builder to create the new case.
- C. Create a workflow rule to create the new case.
- D. Create a lookup field to the Case object on the opportunity object.

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 177

What is the preferred way to reference web content such as images, style sheets, JavaScript, and other libraries that is used in Visualforce pages?

- A. By accessing the content from a third -party CON.
- B. By uploading the content as a Static Resource.
- C. By uploading the content in the Documents tab.
- D. By accessing the content from Chatter Files.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 178

A developer wants to import 500 Opportunity records into a sandbox.

Why should the developer choose to use Data Loader instead of Data Import Wizard?

- A. Data Import Wizard can not import all 500 records.
- B. Data Loader runs from the developer's browser.
- C. Data Loader automatically relates Opportunities to Accounts.
- D. Data Import Wizard does not support Opportunities.

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 179

Which two SOSL searches will returns records matching search criteria contained in any of the searchable texts fields on an object? Choose 2 answers

- A. [FIND 'Acme*' RETURNING Account,Opportunity];
- B. [FIND 'Acme*' IN ALL FIELDS RETURNING Account,Opportunity];
- C. [FIND 'Acme*' IN TEXT FIELDS RETURNING Account,Opportunity];
- D. [FIND 'Acme*' IN ANY FIELDS RETURNING Account,Opportunity];

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 180

Which control statement should a developer use to ensure that a loop body executes at least once?

- A. While (condition){}
- B. For(init_stmt;exit_cond;increment){}
- C. For(variable : list_or_set){}
- D. Do {} while (cond)

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 181

Which two sosl searches will return records matching search criteria contained in any of the searchable text fields on an object? choose 2 answers

- A. [find 'acme*' in text fields returning account,opportunity]
- B. [find 'acme*'in all fields returning account,opportunity]
- C. [find 'acme*' in any fields returning account,opportunity]
- D. [find 'acme*'returning account,opportunity]

Answer: B ([LEAVE A REPLY](#))

Valid CRT-450 Dumps shared by Actual4test.com for Helping Passing CRT-450 Exam!
Actual4test.com now offer the **newest CRT-450 exam dumps**, the Actual4test.com CRT-450 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com CRT-450 dumps with Test Engine here:

https://www.actual4test.com/CRT-450_examcollection.html (240 Q&As Dumps, **30%OFF**)

Special Discount: **Freepdfdumps**)

NEW QUESTION: 182

What is an accurate statement about variable scope? (Choose 3)

- A. Sub-blocks can reuse a parent block's variable name if it's value is null.
- B. Parallel blocks can use the same variable name.
- C. Sub-blocks cannot reuse a parent block's variable name.
- D. A static variable can restrict the scope to the current block of its value is null.

E. A variable can be defined at any point in a block.

Answer: B,C,E ([LEAVE A REPLY](#))

NEW QUESTION: 183

A Visualforce page is required for displaying and editing Case records that includes both standard and custom functionality defined in an Apex class called myControllerExtension.

The Visualforce page should include which <apex:page> attribute(s) to correctly implement controller functionality?

- A. controller="Case" and extensions="myControllerExtension"
- B. controller="myControllerExtension"
- C. standardController="Case" and extensions="myControllerExtension"
- D. extensions="myControllerExtension"

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 184

Which approach should be used to provide test data for a test class?

- A. Execute anonymous code blocks that create data.
- B. Use a test data factory class to create test data.
- C. Access data in @TestVisible class variables.
- D. Query for existing records in the database.

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 185

When can a developer use a custom Visualforce page in a Force.com application? (Choose 2)

- A. To generate a PDF document with application data
- B. To deploy components between two organizations
- C. To create components for dashboards and layouts
- D. To modify the page layout settings for a custom object

Answer: A,C ([LEAVE A REPLY](#))

NEW QUESTION: 186

A developer is creating an enhancement to an application that will allow people to be related to their employer.

Which data model provides the simplest solution to meet the requirements?

- A. Create a master-detail relationship to indicate that a person has an employer
- B. Create a junction object to relate many people to many through master-detail relationship
- C. Create a lookup relationship to indicate that a person has an employer
- D. Create a junction object to relate many people to many through lookup relationship

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 187

A developer uses an 'after update' trigger on the Account object to update all the Contacts related to the Account. The trigger code shown below is randomly failing.

```
List<Contacts> theContacts = new List<Contacts>(); for(Account a : Trigger.new){ for(Contact c : [SELECT Id, Account_Date__c FROM Contact WHERE AccountId = :a.Id]){ c.Account_Date__c = Date.today(); theContacts.add(c); } } updates theContacts;
```

Which line of code is causing the code block to fail?

- A. An exception is thrown if Account_Date__c is null.
- B. The trigger processes more than 200 records in the for loop.
- C. An exception is thrown if theContacts is empty
- D. A SOQL query is located inside of the for loop.

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 188

To which primitive data type is a text area (rich) field automatically assigned?

- A. Object
- B. Text
- C. String
- D. Blob

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 189

A developer is asked to set a picklist field to 'Monitor' on any new Leads owned by a subnet of Users.

How should the developer implement this request?

- A. Create a Lead formula field.
- B. Create a before insert Lead trigger.
- C. Create an after insert Lead trigger.
- D. Create a Lead Workflow Rule Field Update.

Answer: (SHOW ANSWER)

NEW QUESTION: 190

A developer working on a time management application wants to make total hours for each timecard available to applications users. A timecard entry has a Master-Detail relationship to a timecard. Which approach should the developer use to accomplish this declaratively?

- A. A visualforce page that calculates the total number of hours for a timecard and displays it on the page.
- B. A Process Builder process that updates a field on the timecard entry is created.
- C. A Roll-up Summary field on the Timecard Object that calculates the total hours from timecard entries for that timecard.

D. An Apex trigger that uses an Aggregate Query to calculate the hours for a given timecard and stores it in a custom field.

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 191

Which two approaches optimize test maintenance and support future declarative configuration changes?

Choose 2 answers.

- A. Create a method that creates valid records, then call this method within test methods.
- B. Create a methods that loads valid Account records from a static resources, then call this method within test methods.
- C. Create a method that queries for valid records, then call this method within test methods.
- D. Create a method that performs a callout for valid records, then call this method within test methods.

Answer: ([SHOW ANSWER](#)**)**

NEW QUESTION: 192

Account acct = {SELECT Id from Account limit 1}; Given the code above, how can a developer get the type of object from acct?

- A. Call "Account.getSubjectType()"
- B. Call "Account.SubjectType"
- C. Call "acct.getObjectType()"
- D. Call "acct.SubjectType"

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 193

Which two components are available to deploy using the METADATA API? Choose 2 answers

- A. Web-to-Case
- B. Web-to-Lead
- C. Case Settings
- D. Lead Conversion Settings

Answer: ([SHOW ANSWER](#)**)**

NEW QUESTION: 194

What are two uses for External IDs? (Choose two.)

- A. To create a record in a development environment with the same Salesforce ID as in another environment
- B. To create relationships between records imported from an external system.
- C. To prevent an import from creating duplicate records using Upsert
- D. To identify the sObject type in Salesforce

Answer: B,C ([LEAVE A REPLY](#))

NEW QUESTION: 195

From which two locations can a developer determine the overall code coverage for a sandbox?
(Choose two.)

- A. The Apex Test Execution page
- B. The Tests tab of the Developer Console
- C. The Apex classes setup page
- D. The Test Suite Run panel of the Developer Console

Answer: A,B (LEAVE A REPLY)

NEW QUESTION: 196

A developer wrote a unit test to confirm that a custom exception works properly in a custom controller, but the test failed due to an exception being thrown.

Which step should the developer take to resolve the issue and properly test the exception?

- A. Use try/catch within the unit test to catch the exception.
- B. Use the finally bloc within the unit test to populate the exception.
- C. Use the database methods with all or none set to FALSE.
- D. Use Test.isRunningTest() within the custom controller.

Answer: A (LEAVE A REPLY)

Explanation/Reference:

Valid CRT-450 Dumps shared by Actual4test.com for Helping Passing CRT-450 Exam!
Actual4test.com now offer the **newest CRT-450 exam dumps**, the Actual4test.com CRT-450 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com CRT-450 dumps with Test Engine here:

https://www.actual4test.com/CRT-450_examcollection.html (**240** Q&As Dumps, **30%OFF**

Special Discount: Freepdfdumps)

NEW QUESTION: 197

What is the result of the debug statements in testMethod3 when you create test data using testSetup in below code?

```

@sistest
private class CreateAndExecuteTest{

    @testSetup
    static void setup() {
        // Create 2 test accounts
        List<Account> testAccts = new List<Account>();
        for(Integer i=0;i<2;i++) {
            testAccts.add(new Account(Name = 'MyTestAccount'+i, Phone='333-878'));
        }
        insert testAccts;
    }

    @isTest static void testMethod1() {
        Account acc = [SELECT Id,Phone FROM Account WHERE Name='MyTestAccount0' LIMIT 1];
        acc.Phone = '888-1515';
        update acc;

        Account acc2 = [SELECT Id,Phone FROM Account WHERE Name='MyTestAccount1' LIMIT 1];
        acc.Phone = '999-1515';
        update acc2;
    }

    @isTest static void testMethod2() {
        Account acc = [SELECT Id,Phone FROM Account WHERE Name='MyTestAccount1' LIMIT 1];
        acc.Phone = '888-2525';
        update acc;
    }

    @isTest static void testMethod3() {
        Account acc0 = [SELECT Id,Phone FROM Account WHERE Name='MyTestAccount0' LIMIT 1];
        Account acc1 = [SELECT Id,Phone FROM Account WHERE Name='MyTestAccount1' LIMIT 1];

        System.debug('Account0.Phone='+ acc0.Phone +', Account1.Phone='+acc1.Phone);
    }
}

```

- A. Account0.Phone=888-1515, Account1.Phone=999-2525
- B. Account0.Phone=888-1515, Account1.Phone=999-1515
- C. Account0.Phone=333-8781, Account1.Phone=333-8780
- D. Account0.Phone=333-8780, Account1.Phone=333-8781

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 198

Which statement is true about a hierarchical relationship as it pertains to user records?

- A. It uses a special lookup relationship to allow one user record to be related to another user record
- B. It uses a junction object and lookup relationships to allow many user records to be related to many other user records
- C. It uses a junction object and master-detail relationship to allow many user records to be related to many other user records
- D. It uses a master-detail relationship to allow one user record to be related to another user record

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 199

A Visual Flow uses an apex Action to provide additional information about multiple Contacts, stored in a custom class, contactInfo. Which is the correct definition of the Apex method that gets additional information?

A. @InvocableMethod(label='additional Info')

```
public static ContactInfo getInfo(Id contactId)
{ /*implementation*/ }
```

B. @invocableMethod(label='Additional Info')

```
public static List<ContactInfo> getInfo(List<Id> contactIds)
{ /*Implementation*/ }
```

C. @InvocableMethod(Label='additional Info')

```
public ContactInfo(Id contactId)
{ /*implementation*/ }
```

D. @InvocableMethod(label='Additional Info')

```
public List<ContactInfo> getInfo(List<Id> contactIds)
{ /*implementation*/ }
```

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 200

A developer wants to display all of the available record types for a Case object. The developer also wants to display the picklist values for the Case.Status field. The Case object and the Case Status field are on a custom visualforce page.

Which action can the developer perform to get the record types and picklist values in the controller? Choose 2 answers

A. Use SOQL to query Case records in the org to get all value for the Status picklist field.

B. Use Schema.PicklistEntry returned by Case Status getDescribe().getPicklistValues().

C. Use Schema.RecordTypeInfo returned by Case.SObjectType
getDescribe().getRecordTypeInfo()

D. Use SOQL to query Case records in the org to get all the RecordType values available for Case.

Answer: ([SHOW ANSWER](#)**)**

NEW QUESTION: 201

A developer must implement a CheckPaymentProcessor class that provides check processing payment capabilities that adhere to what defined for payments in the PaymentProcessor interface. public interface PaymentProcessor { void pay(Decimal amount); } Which is the correct implementation to use the PaymentProcessor interface class?

A. Public class CheckPaymentProcessor implements PaymentProcessor {
public void pay(Decimal amount);
}

B. Public class CheckPaymentProcessor extends PaymentProcessor {
public void pay(Decimal amount);

```

}
C. Public class CheckPaymentProcessor implements PaymentProcessor {
public void pay(Decimal amount) {}
}
D. Public class CheckPaymentProcessor extends PaymentProcessor {
public void pay(Decimal amount) {}
}

```

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 202

What is the result of the debug statements in testMethod3 when you create test data using testSetup in below code?

```

@isTest
private class CreateAndExecuteTest{

    @testSetup
    static void setup() {
        // Create 2 test accounts
        List<Account> testAccts = new List<Account>();
        for(Integer i=0;i<2;i++) {
            testAccts.add(new Account(Name = 'MyTestAccount'+i, Phone='333-8781'));
        }
        insert testAccts;
    }

    @isTest static void testMethod1() {
        Account acc = [SELECT Id,Phone FROM Account WHERE Name='MyTestAccount0' LIMIT 1];
        acc.Phone = '888-1515';
        update acc;

        Account acc2 = [SELECT Id,Phone FROM Account WHERE Name='MyTestAccount1' LIMIT 1];
        acc.Phone = '999-1515';
        update acc2;
    }

    @isTest static void testMethod2() {
        Account acc = [SELECT Id,Phone FROM Account WHERE Name='MyTestAccount1' LIMIT 1];
        acc.Phone = '888-2525';
        update acc;
    }

    @isTest static void testMethod3() {
        Account acc0 = [SELECT Id,Phone FROM Account WHERE Name='MyTestAccount0' LIMIT 1];
        Account acc1 = [SELECT Id,Phone FROM Account WHERE Name='MyTestAccount1' LIMIT 1];

        System.debug('Account0.Phone='+ acc0.Phone +', Account1.Phone='+acc1.Phone);
    }
}

```

- A. Account0.Phone=888-1515, Account1.Phone=999-1515
- B. Account0.Phone=333-8781, Account1.Phone=333-8780
- C. Account0.Phone=333-8780, Account1.Phone=333-8781
- D. Account0.Phone=888-1515, Account1.Phone=999-2525

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 203

A developer wants to override a button using Visualforce on an object. What is the requirement?

- A. The object record must be instantiated in a controller or extension.
- B. The controller or extension must have a PageReference method.
- C. The standardController attribute must be set to the object.
- D. The action attribute must be set to a controller method.

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 204

The Account object has a custom formula field, Level__c, that is defined as a Formula(Number) with two decimal places. Which three are valid assignments? Choose 3.

- A. Integer myLevel = acct.Level__c;
- B. Decimal myLevel = acct.Level__c;
- C. Double myLevel = acct.Level__c;
- D. Long myLevel = acct.Level__c;
- E. Object myLevel = acct.Level__c;

Answer: B,C,E ([LEAVE A REPLY](#))

NEW QUESTION: 205

Which three methods help ensure quality data?

- A. Create a lookup filter
- B. Handling an exception in Apex
- C. Adding a validation rule
- D. Sending an email alert using a workflow rule
- E. Adding an error to a field in before trigger

Answer: A,C,D ([LEAVE A REPLY](#))

NEW QUESTION: 206

How can a custom type be identified as unique when added to a Set?

- A. Methods in the class must be static
- B. The class must have a method with the @InvocableMethod annotation
- C. Methods in the class must be global
- D. The class must implement the Equals and Hashcode methods

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 207

Which action can a developer take to reduce the execution time of the following code?

```

List<Account> allAccounts = [SELECT Id FROM Account];
List<Contact> allContacts = [SELECT Id, AccountId FROM Contact];

for (Account a : allAccounts) {
    for (Contact c: allContacts) {
        if (c.AccountId = a.Id) {
            // do work
        }
    }
}

```

salesforce

- A. Add a GROUP BY clause to the Contact SOQL.
- B. Use a Map<Id List<Contact> for allContacts.
- C. Put the Account loop inside the Contact loop.
- D. Create an Apex helper class for SOQL.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 208

What is a benefit of using an after insert trigger over using a before insert trigger?

- A. An after insert trigger allows a developer to bypass validation rules when updating fields on the new record.
- B. An after insert trigger allows a developer to modify fields in the new record without a query.
- C. An after insert trigger allows a developer to make a callout to an external service.
- D. An after insert trigger allows a developer to insert other objects that reference the new record.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 209

A developer needs to display all of the available fields for an object.

In which two ways can the developer retrieve the available fields if the variable myObject represents the name of the object? (Choose two.)

- A. Use `getGlobalDescribe().get(myObject).getDescribe().fields.getMap()` to return a map of fields.
- B. Use `Schema.describeSObjects(new String[]{myObject})[0].fields.getMap()` to return a map of fields.
- C. Use `mySObject.myObject.fields.getMap()` to return a map of fields.
- D. Use `myObject.sObjectType.getDescribe().fieldSet()` to return a set of fields.

Answer: B,C ([LEAVE A REPLY](#))

NEW QUESTION: 210

How can a developer get all of the available record types for the current user on the case object?

- A. Use `describesobjectresult` of the case object
- B. Use SOQL to get all cases
- C. Use `describfieldresult` of the case.recordtype field
- D. Use `case.getrecordtypes()`

Answer: (SHOW ANSWER)

NEW QUESTION: 211

A Licensed_Professional__c custom object exist in the system with two Master-Detail fields for the following objects: Certification__c and Contact. Users with the "Certification Representative" role can access the Certification records they own and view the related Licensed Professionals records, however users with the "Salesforce representative" role report they cannot view any Licensed professional records even though they own the associated Contact record. What are two likely causes of users in the "Sales Representative" role not being able to access the Licensed Professional records? Choose 2 answers

- A.** The organization's sharing rules for Licensed_Professional__c have not finished their recalculation process. (Missed)
- B.** The organization has a private sharing model for Certification__c, and Contact is the primary relationship in the Licensed_Professional__c object
- C.** The organization has a private sharing model for Certification__c, and Certification__c is the primary relationship in the Licensed_Professional__c object. (Missed)
- D.** The organization recently modified the Sales representative role to restrict Read/Write access to Licensed_Professional__c

Answer: C,D (LEAVE A REPLY)

Valid CRT-450 Dumps shared by Actual4test.com for Helping Passing CRT-450 Exam! Actual4test.com now offer the **newest CRT-450 exam dumps**, the Actual4test.com CRT-450 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com CRT-450 dumps with Test Engine here:

https://www.actual4test.com/CRT-450_examcollection.html (240 Q&As Dumps, **30%OFF**)

Special Discount: Freepdfdumps)

NEW QUESTION: 212

A developer at Universal Containers is tasked with implementing a new Salesforce application that must be able to be maintained completely by their company's Salesforce administrator. Which three options should be considered for building out the business logic layer of the application? (Choose three.)

- A.** Scheduled Jobs
- B.** Validation Rules
- C.** Process Builder
- D.** Invocable Actions
- E.** Workflows

Answer: B,C,E (LEAVE A REPLY)

NEW QUESTION: 213

Which two statements are acceptable for a developer to use inside procedural loops?

- A. Contact con = new Contact()
- B. Delete contactList
- C. Account a = [select id, name from Account where id=:con.accountid limit 1]
- D. ContactList.remove(i)

Answer: A,D ([LEAVE A REPLY](#))

NEW QUESTION: 214

Which three code lines are required to create a Lightning component on a Visualforce page?

Choose 3 answers

- A. \$Lightning.use (Missed)
- B. \$Lightning.createComponent
- C. <apex:slds/>
- D. <apex:includeLightning/>
- E. \$Lightning.useComponent

Answer: A,B,D ([LEAVE A REPLY](#))

NEW QUESTION: 215

How should a developer prevent a recursive trigger?

- A. Use a "one trigger per object" pattern.
- B. Use a static Boolean variable.
- C. Use a trigger handler.
- D. Use a private Boolean variable.

Answer: B ([LEAVE A REPLY](#))

Explanation/Reference:

NEW QUESTION: 216

A Lead object has a custom field Prior_Email__c. The following trigger is intended to copy the current Email into the Prior_Email__c field any time the Email field is changed:

```
trigger test on Lead (before update) {
    for(Lead ld: trigger.new)
    {
        if(ld.Email != trigger.oldMap.get (ld.Id).email)
        {
            ld.Prior_Email__c = trigger.oldMap.get (ld.Id).email;
            update ld;
        }
    }
}
```

Which type of exception will this trigger cause?

- A. A DML exception
- B. A null reference exception
- C. A compile time exception
- D. A limit exception when doing a bulk update

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 217

A lead object has a custom field Prior_Email__c. The following trigger is intended to copy the current Email into the Prior_Email__c field any time the Email field is changed:

```
trigger test on Lead (before update) {
    for(Lead ld: trigger.new)
    {
        if(ld.Email != trigger.oldMap.get (ld.Id).email)
        {
            ld.Prior_Email__c = trigger.oldMap.get (ld.Id).email;
            update ld;
        }
    }
}
```



Which type of exception will this trigger cause?

- A. A null reference exception
- B. A DML exception
- C. A limit exception when doing a bulk update
- D. A compile time exception

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 218

Universal Containers (UC) has an integration with its Accounting system that creates tens of thousands of Orders inside of Salesforce in a nightly batch. UC wants to add automation that can attempt to match Leads and Contacts to these Orders using the Email Address field on the insert. UC is concerned about the performance of the automation with a large data volume. Which tool should UC use to automate this process?

- A. Process Builder with an Autolaunched Flow
- B. Apex
- C. Process Builder
- D. Workflow Rules

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 219

A lead object has a custom field Prior_Email__c. The following trigger is intended to copy the current Email into the Prior_Email__c field any time the Email field is changed:

```

trigger test on Lead (before update) {
    for(Lead ld: trigger.new)
    {
        if(ld.Email != trigger.oldMap.get (ld.ld).email)
        {
            ld.Prior_Email__c = trigger.old.ap.get (ld.ld).email;
            update ld;
        }
    }
}

```

Which type of exception will this trigger cause?

- A. A null reference exception
- B. A compile time exception
- C. A limit exception when doing a bulk update
- D. A DML exception

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 220

A developer must create a DrawListclass that provides capabilities defined in the Sortableand Drawable interfaces.

```

public interface Sortable {
    void sort();
}
public interface Drawable {
    void draw();
}

```

Which is the correct implementation?

A.

```

public class DrawList implements Sortable, implements Drawable {
    public void sort() { /*implementation*/}
    public void draw() { /*implementation*/}
}

```

B.

```

public class DrawList implements Sortable, Drawable {
    public void sort() { /*implementation*/}
    public void draw() { /*implementation*/}
}

```

C.

```

public class DrawList extends Sortable, extends Drawable {
    public void sort() { /*implementation*/}
    public void draw() { /*implementation*/}
}

```

D.

```

public class DrawList extends Sortable, Drawable {
    public void sort() { /*implementation*/}
    public void draw() { /*implementation*/}
}

```

Answer: D (LEAVE A REPLY)

Explanation/Reference:

NEW QUESTION: 221

The operation manager at a construction company uses a custom object called Machinery to manage the usage and maintenance of its cranes and other machinery. The manager wants to be able to assign machinery to different constructions jobs, and track the dates and costs associated with each job. More than one piece of machinery can be assigned to one construction job.

What should a developer do to meet these requirements?

- A. Create a lookup field on the Machinery object to the Construction Job object.
- B. Create a Master-Detail Lookup on the Machinery object to the Construction Job object.
- C. Create a junction object with Master-Detail Relationship to both the Machinery object and the Construction Job object.
- D. Create a lookup field on the Construction Job object to the Machinery object.

Answer: D (LEAVE A REPLY)

NEW QUESTION: 222

Which code should be used to update an existing Visualforce page that uses standard Visualforce components so that the page matches the look and feel of Lightning Experience?

- A. `<apex:slds/>`
- B. `<apex:styleSheet value="{!$URLFOR($Resource.slds,'assets/slds.css')}">`
- C. `<apex:includeLightning/>`
- D. `<apex:page lightningStyleSheets="true">`

Answer: D (LEAVE A REPLY)

NEW QUESTION: 223

What are two ways a developer can get the status of an enqueued job for a class that queueable interface? Choose 2 answers

- A. Query the AsyncApexJob object (Missed)
- B. View the apex Jobs page (Missed)
- C. View the apex flex Queue
- D. View the apex status Page

Answer: A,B (LEAVE A REPLY)

NEW QUESTION: 224

The initial value for a number field on a record is 1. A user updated the value of the number field to 10.

This action invokes a workflow field update, which changes the value of the number field to 11.

After the workflow field update, an update trigger fires. What is the value of the number field of the object that is obtained from `Trigger.old`?

- A. 1

- B. 11
- C. Null
- D. 10

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 225

A developer considers the following snippet of code:

```
Boolean isOK;
integer x;
String theString = 'Hello';

if (isOK == false && theString == 'Hello'){
    x = 1;
} else if (isOK == true && theString == 'Hello'){
    x = 2;
} else if (isOK != null && theString == 'Hello'){
    x = 3;
} else {
    x = 4;
}
```

Based on this code, what is the value of x?

- A. 1
- B. 4
- C. 2
- D. 3

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 226

A developer working on a time management application wants to make total hours for each timecard available to application users. A timecard entry has a Master-Detail relationship to a timecard.

Which approach should the developer use to accomplish this declaratively?

- A. A Visualforce page that calculates the total number of hours for a timecard and displays it on the page
- B. An Apex trigger that uses an Aggregate Query to calculate the hours for a given timecard and stores it in a custom field
- C. A Process Builder process that updates a field on the timecard when a timecard entry is created
- D. A Roll-Up Summary field on the Timecard Object that calculates the total hours from timecard entries for that timecard

Answer: D ([LEAVE A REPLY](#))

Valid CRT-450 Dumps shared by Actual4test.com for Helping Passing CRT-450 Exam!
Actual4test.com now offer the **newest CRT-450 exam dumps**, the Actual4test.com CRT-450 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com CRT-450 dumps with Test Engine here:

https://www.actual4test.com/CRT-450_examcollection.html (240 Q&As Dumps, **30%OFF**

Special Discount: Freepdfdumps)

Valid CRT-450 Dumps shared by Actual4test.com for Helping Passing CRT-450 Exam!
Actual4test.com now offer the **newest CRT-450 exam dumps**, the Actual4test.com CRT-450 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com CRT-450 dumps with Test Engine here:

https://www.actual4test.com/CRT-450_examcollection.html (240 Q&As Dumps, **30%OFF**

Special Discount: Freepdfdumps)