

Salesforce.JS-Dev-101.v2026-04-23.q96

Exam Code:	JS-Dev-101
Exam Name:	Salesforce Certified JavaScript Developer - Multiple Choice
Certification Provider:	Salesforce
Free Question Number:	96
Version:	v2026-04-23
# of views:	109
# of Questions views:	960
https://www.freepdfdumps.com/Salesforce.JS-Dev-101.v2026-04-23.q96.html	

NEW QUESTION: 1

Given the code below:

`const copy = JSON.stringify([ newString(' false '), new Bollean( false ), undefined ])`; What is the value of copy?

- A. -- [\"false\" , false, undefined]--
- B. -- [\"false\" ,false, null]--
- C. -- [\"false\" , { }]--
- D. -- [false, { }]--

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 2

Refer to the code below

`let inArray = [[1,2],[3,4,5]];`

which two statements results in the array [1,2,3,4,5]?

choose 2 answer

- A. `[ ].concat.apply([ ],inArray);`
- B. `[ ].concat.apply(inArray,[ ]);`
- C. `[ ].concat(...inArray);`
- D. `[ ].concat([...inArray])`

Answer: A,C ([LEAVE A REPLY](#))

NEW QUESTION: 3

Which three options show valid methods for creating a fat arrow function?

Choose 3 answers

- A. `[ ] => ( console.log(' executed ' ) ;)`
- B. `(x,y,z) => ( console.log(' executed ' ) ;)`
- C. `x => ( console.log(' executed ' ) ; )`

- D. () => (console.log(' executed ') ;)
- E. X,y,z => (console.log(' executed ') ;)

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 4

A developer implements a function that adds a few values.

```
Function sum(num) {  
  If (num == undefined) {  
    Num =0;  
  }  
  Return function( num2, num3){  
    If (num3 ===undefined) {  
      Num3 =0 ;  
    }  
    Return num + num2 + num3;  
  }  
}
```

Which three options can the developer invoke for this function to get a return value of 10 ?

Choose 3 answers

- A. sum() (5, 5)
- B. sum(5)(5)
- C. Sum () (20)
- D. sum(10) ()
- E. Sum (5, 5) ()

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 5

Refer to the following code:

```
Let obj ={  
  Foo: 1,  
  Bar: 2  
}  
Let output =[],  
for(let something in obj){  
  output.push(something);  
}  
console.log(output);
```

What is the output line 11?

- A. ["foo:1","bar:2"]
- B. [1,2]
- C. ["foo","bar"]

D. ["bar","foo"]

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 6

A developer is leading the creation of a new web server for their team that will fulfill API requests from an existing client.

The team wants a web server that runs on Node.Js, and they want to use the new web framework Minimalist.Js. The lead developer wants to advocate for a more seasoned back-end framework that already has a community around it.

Which two frameworks could the lead developer advocate for?

Choose 2 answers

A. Gatsby

B. Angular

C. Koa

D. Express

Answer: A,B ([LEAVE A REPLY](#))

NEW QUESTION: 7

Refer to code below:

```
Let first = 'who';
```

```
Let second = 'what';
```

```
Try{
```

```
Try{
```

```
Throw new error('Sad trombone');
```

```
}catch (err){
```

```
First ='Why';
```

```
}finally {
```

```
Second ='when';
```

```
} catch (err) {
```

```
Second ='Where';
```

```
}
```

What are the values for first and second once the code executes ?

A. First is why and second is where

B. First is Who and second is When

C. First is why and second is when

D. First is who and second is where

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 8

Refer to code below:

```
function Person() {
```

```
this.firstName = 'John';
}
Person.prototype = {
  Job: x => 'Developer'
};
const myFather = new Person();
const result = myFather.firstName + ' ' + myFather.job();
What is the value of the result after line 10 executes?
```

- A. John Developer
- B. John undefined
- C. Undefined Developer
- D. Error: myFather.job is not a function

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 9

Which statement accurately describes the behaviour of the async/ await keywords ?

- A. The associated sometimes returns a promise.
- B. The associated function will always return a promise
- C. The associated function can only be called via asynchronous methods
- D. The associated class contains some asynchronous functions.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 10

Refer to HTML below:

```
<div id ="main">
<div id = " card-00">This card is smaller.</div>
<div id = "card-01">The width and height of this card is determined by its contents.</div>
</div>
```

Which expression outputs the screen width of the element with the ID card-01?

- A. document.getElementById(' card-01 ').getBoundingClientRect().width
- B. document.getElementById(' card-01 ').width
- C. document.getElementById(' card-01 ').innerHTML.length
- D. document.getElementById(' card-01 ').style.width

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 11

Refer to the code below:

```
const car = {
  price: 100,
  getPrice: function(){
    return this.price;
  }
}
```

```
}  
};  
const customCar = Object.create(car);  
customCar.price = 70;  
delete customCar.price; const result = customCar.getPrice();
```

What is the value of result after the code executes?

- A. null
- B. 70
- C. undefined
- D. 100

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 12

Refer to the code below:

```
01 function Person() {  
02   this.firstName = 'John';  
03 }  
04  
05 Person.prototype = {  
06   job: x => 'Developer'  
07 };  
08  
09 const myFather = new Person();  
10 const result = myFather.firstName + ' ' + myFather.job();
```

What is the value of result after line 10 executes?

- A. John undefined
- B. undefined Developer
- C. John Developer
- D. Error: myFather.job is not a function

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 13

Refer to the code below:

Const searchText = 'Yay! Salesforce is amazing!';

Let result1 = searchText.search(/sales/i);

Let result 21 = searchText.search(/sales/i);

console.log(result1);

console.log(result2);

After running this code, which result is displayed on the console?

- A. > true > false B. > 5 > undefined

B. $> 5 > -1$

C. $> 5 > 0$

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 14

Given the following code, what is the value of x?

```
let x = '15' + (10 * 2);
```

A. 50

B. 1520

C. 3020

D. 35

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 15

Refer to the code snippet:

```
Function getAvailabilityMessage(item) {  
  If (getAvailability(item)){  
    Var msg ="Username available";  
  }  
  Return msg;  
}
```

A developer writes this code to return a message to user attempting to register a new username.

If the username is available, variable.

What is the return value of msg when getAvailabilityMessage ("newUserName") is executed and getAvailability("newUserName") returns false?

A. "newUserName"

B. undefined

C. "Username available"

D. "Msg is not defined"

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 16

Given a value, which three options can a developer use to detect if the value is NaN?

Choose 3 answers !

A. `value == NaN`

B. `Number.isNaN(value)`

C. `value !== value`

D. `Object.is(value, NaN)`

E. `value === Number.NaN`

Answer: ([SHOW ANSWER](#)**)**

Valid JS-Dev-101 Dumps shared by Actual4test.com for Helping Passing JS-Dev-101 Exam! Actual4test.com now offer the **newest JS-Dev-101 exam dumps**, the Actual4test.com JS-Dev-101 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com JS-Dev-101 dumps with Test Engine here:

https://www.actual4test.com/JS-Dev-101_examcollection.html (149 Q&As Dumps, **30%OFF**

Special Discount: Freepdfdumps)

NEW QUESTION: 17

Why would a developerspecify a package.json as a developed forge instead of a dependency ?

- A.** It is required by the application in production.
- B.** It should be bundled when the package is published.
- C.** Other required packages depend on it for development.
- D.** It is only needed for local development and testing.

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 18

Referto the following code:

```
01 function Tiger() {
02   this.type = 'Cat';
03   this.size = 'large';
04 }
05
06 let tony = new Tiger();
07 tony.roar = () => {
08   console.log('They\'re great!');
09 };
10
11 function Lion() {
12   this.type = 'Cat';
13   this.size = 'large';
14 }
15
16 let leo = new Lion();
17 // Insert code here
18 leo.roar();
```

salesforce

Which two statements could be inserted at line 17 to enable the function call on line 18? Choose 2 answers

- A. `leo.roar = () => { console.log('They\'re pretty good!'); };`
- B. `Object.assign (leo, tony);`
- C. `leo.prototype.roar = ( ) =>( console.log('They\'re pretty good!'); );`
- D. `Object.assign (leo, Tiger);`

Answer: A,B ([LEAVE A REPLY](#))

NEW QUESTION: 19

Refer to the code below:

```
Let str = 'javascript';
```

```
Str[0] = 'J';
```

```
Str[4] = 'S';
```

After changing the string index values, the value of str is 'javascript'. What is the reason for this value:

- A. Non-primitive values are mutable.
- B. Primitive values are mutable.
- C. Primitive values are immutable.
- D. Non-primitive values are immutable.

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 20

A developer is leading the creation of a new browser application that will serve a single page application. The team wants to use a new web framework Minimalsit.js. The Lead developer wants to advocate for a more seasoned web framework that already has a community around it.

Which two frameworks should the lead developer advocate for?

Choose 2 answers

- A. Express
- B. Koa
- C. Vue
- D. Angular

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 21

Refer to code below:

```
Let a ='a';
```

```
Let b;
```

```
// b = a;
```

```
console.log(b);
```

What is displayed when the code executes?

- A. Null
- B. A
- C. ReferenceError: b is not defined
- D. Undefined

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 22

Which statement accurately describes the behaviour of the async/ await keywords ?

- A. The associated sometimes returns a promise.
- B. The associated class contains some asynchronous functions.
- C. The associated function can only be called via asynchronous methods
- D. The associated function will always return a promise

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 23

After user acceptance testing, the developer is asked to change the webpage background based on user's location. This change was implemented and deployed for testing.

The tester reports that the background is not changing, however it works as required when viewing on the developer's computer.

Which two actions will help determine accurate results?

Choose 2 answers

- A. The developer should rework the code.
- B. The tester should disable their browser cache.
- C. The tester should clear their browser cache.
- D. The developer should inspect their browser refresh settings.

Answer: C,D ([LEAVE A REPLY](#))

NEW QUESTION: 24

is below:

```
<input type="file" onchange="previewFile()">
<img src="" height="200" alt="Image Preview...">
```

The JavaScript portion is:

```
01 function previewFile(){
02   const preview = document.querySelector('img');
03   const file = document.querySelector('input[type=file]').files[0];
04   //line 4 code
05   reader.addEventListener("load", () => {
06     preview.src = reader.result;
07   }, false);
08   //line 8 code
09 }
```

In lines 04 and 08, which code allows the user to select an image from their local computer, and to display the image in the browser?

- A. 04 const reader = new File(); 08 if (file) URL.createObjectURL(file);
- B. 04 const reader = new FileReader(); 08 if (file) reader.readAsDataURL(file);
- C. 04 const reader = new FileReader(); 08 if (file) URL.createObjectURL(file);
- D. 04 const reader = new File(); 08 if (file) reader.readAsDataURL(file);

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 25

Refer to the code below:

```
Function Person(firstName, lastName, eyecolor) {  
  this.firstName =firstName;  
  this.lastName = lastName;  
  this.eyeColor = eyeColor;  
}
```

```
Person.job = 'Developer';  
const myFather = new Person('John', 'Doe');  
console.log(myFather.job);
```

What is the output after the code executes?

- A. Undefined
- B. Developer
- C. ReferenceError: eyeColor is not defined
- D. ReferenceError: assignment to undeclared variable "Person"

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 26

A developer is asked to fix some bugs reported by users. To do that, the developer adds a breakpoint for debugging.

```
Function Car (maxSpeed, color){  
  This.maxspeed =masSpeed;  
  This.color = color;  
  Let carSpeed = document.getElementById(' CarSpeed');  
  Debugger;  
  Let fourWheels =new Car (carSpeed.value, 'red');
```

When the code execution stops at the breakpoint on line 06, which two types of information are available in the browser console ?

Choose 2 answers:

- A. The style, event listeners and other attributes applied to the carSpeed DOM element
- B. A variable displaying the number of instances created for the Car Object.
- C. The information stored in the window.localStorage property
- D. The values of the carSpeed and fourWheels variables

Answer: A,C ([LEAVE A REPLY](#))

NEW QUESTION: 27

A developer wants to set up a secure web server with Node.js. The developer creates a directory locally called app-server, and the first file is app-server/index.js Without using any third-party libraries, what should the developer add to index.js to create the secure web server?

- A. `const http =require('http');`
- B. `const https =require('https');`

C. `const tls = require('tls');`
D. `const server =require('secure-server');`
Answer: ([SHOW ANSWER](#))

NEW QUESTION: 28

Given the following code:

```
01 counter = 0;
02 const logCounter = () => {
03   console.log(counter);
04 };
05 setInterval(logCounter, 2100);
06 setInterval(() => {
07   counter++;
08   logCounter();
09 }, 1000);
```



What will be the first four numbers logged?

- A. 0122
- B. 0112
- C. 0123
- D. 0012

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 29

A developer uses a parsed JSON string to work with user information as in the block below:

```
01 const userInformation = {
02   "id" : "user-01",
03   "email" : "user01@universalcontainers.demo",
04   "age" : 25
05 }
```

Which two options access the email attribute in the object?

Choose 2 answers

- A. userInformation.email
- B. userInformation.get("email")
- C. userInformation("email")
- D. userInformation(email)

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 30

A developer wants to create an object from a function in the browser using the code below.

```
01 function Monster(){ this.name = 'hello' };  
02 const m = Monster();
```

What happens due to the lack of the mm keyword on line 02?

- A. The m variable is assigned the correct object but this.name remains undefined.
- B. The m variable is assigned the correct object.
- C. window.name is assigned to 'hello' and the variable = remains undefined.
- D. window.m is assigned the correct object.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 31

Refer to the HTML below:

```
<div id="main">  
  
  <ul>  
  
    <li>Leo</li>  
  
    <li>Tony</li>  
  
    <li>Tiger</li>  
  
  </ul>  
  
</div>
```

Which JavaScript statement results in changing " The Lion."?

- A. document.querySelectorAll('\$main \$TONY').innerHTML = " The Lion
- B. document.querySelector('\$main li:second-child').innerHTML = "The Lion ';
- C. document.querySelector('\$main li:nth-child(2)'),innerHTML = " The Lion. ';
- D. document.querySelector('\$main li.Tony').innerHTML = " The Lion ';

Answer: A ([LEAVE A REPLY](#))

Valid JS-Dev-101 Dumps shared by Actual4test.com for Helping Passing JS-Dev-101 Exam! Actual4test.com now offer the **newest JS-Dev-101 exam dumps**, the Actual4test.com JS-Dev-101 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com JS-Dev-101 dumps with Test Engine here:
https://www.actual4test.com/JS-Dev-101_examcollection.html (149 Q&As Dumps, **30%OFF** Special Discount: **Freepdfdumps**)

NEW QUESTION: 32

A developer creates an object where its properties should be immutable and prevent properties from being added or modified.

Which method should be used to execute this business requirement ?

- A. Object.lock()
- B. Object.freeze()
- C. Object.eval()
- D. Object.const()

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 33

Refer to the code below:

```
Async func on functionUnderTest(isOK) {  
  If (isOK) return 'OK';  
  Throw new Error('not OK');  
}
```

Which assertion accurately tests the above code?

- A. Console.assert (await functionUnderTest(true), ' OK ')
- B. Console.assert (await functionUnderTest(true), 'OK')
- C. Console.assert (await functionUnderTest(true), ' notOK ')
- D. Console.assert (await functionUnderTest(true), ' not OK ')

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 34

Refer to following code:

```
class Vehicle {  
  constructor(plate) {  
    This.plate =plate;  
  }  
}  
  
Class Truck extends Vehicle {  
  constructor(plate, weight) {
```

//Missing code

This.weight = weight;

}

displayWeight() {

console.log('The truck \${this.plate} has a weight of\${this.weight} lb.');

Let myTruck = new Truck('123AB', 5000); myTruck.displayWeight(); Which statement should be added to line 09 for the code to display 'The truck 123AB has a weight of 5000lb.'?

A. super(plate);

B. Vehicle.plate = plate;

C. Super.plate =plate;

D. This.plate =plate;

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 35

A team that works on a big project uses npm to deal with projects dependencies.

A developer added a dependency does not get downloaded when they execute npm install.

Which two reasons could be possible explanations for this?

Choose 2 answers

A. The developer missed the option --save when adding the dependency.

B. The developer added the dependency as a dev dependency, andNODE_ENVIs set to production.

C. The developer missed the option --add when adding the dependency.

D. The developer added the dependency as a dev dependency, andNODE_ENV is set to production.

Answer: A,B,D ([LEAVE A REPLY](#))

NEW QUESTION: 36

developer creates a new web server that uses Node.js. It imports a server library that uses events and callbacks for handling server functionality.

The server library is imported with require and is made available to the code by a variable named server. The developer wants to log any issues that the server has while booting up.

Given the code and the information thedeveloper has, which code logs an error at boost with an event?

A. Server.catch ((server) => {console.log('ERROR', error)});

B. Server.error ((server) => {console.log('ERROR', error)});

C. Server.on ('error', (error) => {console.log('ERROR', error)});

D. Try{server.start();} catch(error) {console.log('ERROR', error);}

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 37

A Developer wrote the following code to test a sum3 function that takes in an array of numbers and returns the sum of the first three number in the array, The test passes:

```
Let res = sum2([1, 2, 3 ]) ;  
console.assert(res === 6 );  
Res = sum3([ 1, 2, 3, 4]);  
console.assert(res=== 6);
```

A different developer made changes to the behavior of sum3 to instead sum all of the numbers present in the array. The test passes:

Which two results occur when running the test on the updated sum3 function ?

Choose 2 answers

- A. The line 02 assertion passes.
- B. The line 02 assertion fails
- C. The line 05 assertion fails.
- D. The line 05 assertion passes.

Answer: A,C ([LEAVE A REPLY](#))

NEW QUESTION: 38

Given the code below:

```
const delay = sync delay => {  
  Return new Promise((resolve, reject) => {  
    setTimeout (resolve,delay);});};  
const callDelay =async () =>{  
  const yup =await delay(1000);  
  console.log(1);  
}
```

What is logged to the console?

- A. 2 1 3
- B. 1 3 2
- C. 1 2 3
- D. 2 3 1

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 39

Refer to the code below:

```
01 const exec = (item, delay) =>{  
02   newPromise(resolve => setTimeout( () => resolve(item), delay)),  
03   async function runParallel() {  
04     Const (result1, result2, result3) = await Promise.all{  
05       [exec ('x', '100') , exec('y', 500), exec('z', '100')]  
06     };  
07     return `parallel is done: ${result1}${result2}${result3}`;  
08   }  
}
```

```
}  
}
```

Which two statements correctly execute the runParallel () function?

Choose 2 answers

- A. runParallel () .then(function(data){return data
- B. Async runParallel () .then(data);
- C. runParallel (). done(function(data){return data;});
- D. runParallel () .then(data);

Answer: A,C ([LEAVE A REPLY](#))

NEW QUESTION: 40

Given the HTML below:

```
<div>  
  <div id="row-wc">Universal Containers</div>  
  <div id="row-as">Applied Shipping</div>  
  <div id="row-bt">Burlington Textiles</div>  
</div>
```

Which statement adds the priority-account css class to the Applied Shipping row?

Answer:

```
document.querySelector('#row-as').classList.add('priority-account');
```

NEW QUESTION: 41

Refer to code below:

```
Let productSKU = '8675309' ;
```

A developer has a requirement to generate SKU numbers that are always 19 characters long, starting with 'sku', and padded with zeros.

Which statement assigns the values sku00000000008675309 ?

- A. productSKU = productSKU .padEnd (16. '0').padstart(19, 'sku');
- B. productSKU = productSKU .padStart (16. '0').padstart(19, 'sku');
- C. productSKU = productSKU .padEnd (16. '0').padstart('sku');
- D. productSKU = productSKU .padStart (19. '0').padstart('sku');

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 42

Refer to the string below.

```
Const str='Salesforce';
```

Which two statements results in the word 'Sales'?

Answer:

See the Answer below in explanation

NEW QUESTION: 43

Given the code below:

Which three code segments result in a correct conversion from number to string? Choose 3 answers

- A. `let strValue = * * 4 numValue;`
- B. `let strValue = (String)numValue;`
- C. `let scrValue = String(numValue);`
- D. `let strValue = numValue. toString();`
- E. `let strValue = numValue.toText ();`

Answer: A,C,D ([LEAVE A REPLY](#))

NEW QUESTION: 44

Refer to the code below:

```
Const resolveAfterMilliseconds = (ms) => Promise.resolve (  
  setTimeout ((=> console.log(ms), ms ));
```

```
Const aPromise = await resolveAfterMilliseconds(500);
```

```
Const bPromise = await resolveAfterMilliseconds(500);
```

```
Await aPromise, wait bPromise;
```

What is the result of running line 05?

- A. Only aPromise runs.
- B. Neither aPromise or bPromise runs.
- C. aPromise and bPromise run sequentially.
- D. aPromise and bPromise run in parallel.

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 45

Refer to the code snippet below:

```
Let array = [1, 2, 3, 4, 4, 5, 4, 4];
```

```
For (let i =0; i <array.length; i++){
```

```
  if (array[i] === 4) {
```

```
    array.splice(i, 1);
```

```
  }
```

```
}
```

What is the value of the array after the code executes?

- A. `[1, 2, 3, 4, 4, 5, 4]`
- B. `[1, 2, 3, 4, 5, 4]`
- C. `[1, 2, 3, 5]`
- D. `[1, 2, 3, 4, 5, 4, 4]`

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 46

Refer to the following array:

Let arr1 = [1,2, 3, 4, 5];

```
let arr1 = [ 1, 2, 3, 4, 5 ];
let arr2 = arr1.slice(0, 5);

console.log(arr2)
▶ (5) [1, 2, 3, 4, 5] VM1767:4
undefined
let arr1 = [ 1, 2, 3, 4, 5 ];
let arr2 = Array.from(arr1);
console.log(arr2)
▶ (5) [1, 2, 3, 4, 5] VM1827:3
undefined
```

Which two lines of code result in a second array, arr2 being created such that arr2 is not a reference to arr1?

- A. Let arr2 = arr1.slice(0, 5);
- B. Let arr2 = arr1.sort();
- C. Let arr2 = arr1;
- D. Let arr2 = Array.from(arr1);

Answer: A,D ([LEAVE A REPLY](#))

Valid JS-Dev-101 Dumps shared by Actual4test.com for Helping Passing JS-Dev-101 Exam! Actual4test.com now offer the **newest JS-Dev-101 exam dumps**, the Actual4test.com JS-Dev-101 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com JS-Dev-101 dumps with Test Engine here:

https://www.actual4test.com/JS-Dev-101_examcollection.html (149 Q&As Dumps, **30%OFF**

Special Discount: **Freepdfdumps**)

NEW QUESTION: 47

Refer to thecode below:

Const pi = 3.1415326,

What is the data type of pi?

- A. Number
- B. Double
- C. Decimal
- D. Float

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 48

Refer to the code below:

```
Let textValue = '1984';
```

Which code assignment shows a correct way to convert this string to an integer?

- A. let numberValue = Number(textValue);
- B. Let numberValue = (Number)textValue;
- C. Let numberValue = textValue.toInteger();
- D. Let numberValue = Integer(textValue);

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 49

Refer to the code below:

```
let car1 = new Promise((_ ,reject)=> setTimeout(reject,2000,"Car1 crashed in")); let car2 = new Promise(resolve => setTimeout(resolve,1500,"Car2 completed")); let car3 = new Promise(resolve => setTimeout(resolve,3000,"Car3 completed")); Promise.race([car1,car2,car3]).then(value=>{let result = `${value} the race.`;}).catch(err=>{console.log('Race is cancelled.',err);});
```

What is the value of result when promise.race executes?

Answer:

Car2 completed the race.

NEW QUESTION: 50

Refer to the code:

```
function Animal (size, type) {  
  
    this.size = size || 'small';  
  
    this.type = type || 'Animal';  
  
    this.cantalk = false;  
  
}
```

```
let Pet = function (size, type, name, owner) {  
  
    Animal.call(this, size, type);  
  
    this.name = name;  
  
    this.owner = owner;  
  
}
```

Pet prototype = object create (Animal.prototype);

let pet1 = new Pet ();

Given the code above, which three properties are set for pet1? Choose 3 answers

A. type

- B. size
- C. owner
- D. canTalk
- E. name

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 51

Which three actions can be using the JavaScript browser console?

Choose 3 answers:

- A. Run code that is not related to page.
- B. Display a report showing the performance of a page.
- C. View and change security cookies.
- D. View and change DOM the page.
- E. view , change, and debug the JavaScript code of the page.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 52

Given two expressions var1 and var2. What are two valid ways to return the logical AND of the two expressions and ensure it is data type Boolean ?

Choose 2 answers:

- A. var1 && var2
- B. Boolean(var1) && Boolean(var2)
- C. Boolean(var1 && var2)
- D. var1.toBoolean() && var2.toBoolean()

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 53

Refer to the code below:

```
Function changeValue(obj) {  
  Obj.value = obj.value/2;  
}
```

```
Const objA = (value: 10);
```

```
Const objB = objA;
```

```
changeValue(objB);
```

```
Const result = objA.value;
```

What is the value of result after the code executes?

- A. 10
- B. Undefined
- C. 5
- D. Nan

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 54

Refer to the code below:

```
01 const server = require('server');  
02 /* Insert code here */
```

A developer imports a library that creates a web server. The imported library uses events and callbacks to start the servers. Which code should be inserted at the line 03 to set up an event and start the web server?

- A. `serve(( port) => (`
- B. `server()`
- C. `server.on(' connect ' , ( port) => {console.log('Listening on ' , port) ;})`
- D. `console.log( 'Listening on ' , port) ;`
- E. `Server.start ();`

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 55

A developer needs to debug a Node.js web server because a runtime error keeps occurring at one of the endpoints.

The developer wants to test the endpoint on a local machine and make the request against a local server to look at the behavior. In the source code, the `server.js` file will start the server. the developer wants to debug the Node.js server only using the terminal.

Which command can the developer use to open the CLI debugger in their current terminal window?

- A. `node -i server.js`
- B. `node start inspect server.js`
- C. `node server.js inspect`
- D. `node inspect server.js`

Answer: ([SHOW ANSWER](#)**)**

NEW QUESTION: 56

Refer to the code below:

```
Let foodMenu1 = ['pizza', 'burger', 'French fries'];  
Let finalMenu = foodMenu1;  
finalMenu.push('Garlic bread');
```

What is the value of `foodMenu1` after the code executes?

- A. `[ 'Garlicbread' ]`
- B. `[ 'pizza','Burger', 'French fires' ]`
- C. `[ 'pizza','Burger', 'French fires', 'Garlic bread' ]`
- D. `[ 'Garlic bread' , 'pizza','Burger', 'French fires' ]`

Answer: ([SHOW ANSWER](#)**)**

NEW QUESTION: 57

There is a new requirement for a developer to implement a currPrice method that will return the current price of the item or sales..

```
01 let regItem = new Item('Scarf', 50); // Name, Price
02 let saleItem = new SaleItem('Shirt', 80, .1); // Name, Price, Discount
03 Item.prototype.currPrice = function() { return this.price; }
04 console.log(regItem.currPrice());
05 console.log(saleItem.currPrice());
06
07 SaleItem.prototype.currPrice = function() { return this.price - (this.price * this.discount); }
08 console.log(regItem.currPrice());
09 console.log(saleItem.currPrice());
```

What is the output when executing the code above

- A. 508072
- B. 50Uncaught TypeError: saleItem.description is not a function5080
- C. 5080Uncaught ReferenceError:this,discount is undefined72
- D. 50805072

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 58

Given the HTML below:

```
<div>
  <div id="row-uc">Universal Containers</div>
  <div id="row-as">Applied Shipping</div>
  <div id="row-bt">Burlington Textiles</div>
</div>
```

Which statement adds the priority-account CSS class to the Universal Containers row?

- A. document.querySelector('#row-uc').classList.add('priority-account');
- B. document.querySelectorAll('#row-uc').classList.add('priority-account');
- C. document.getElementById('row-uc').addClass('priority-account');
- D. document.querySelector('#row-uc').classList.push('priority-account');

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 59

Refer to the following object.

```

01 const dog = {
02   firstName: 'Beau',
03   lastName: 'Boo',
04   get fullName() {
05     return this.firstName + ' ' + this.lastName;
06   }
07 };

```

How can a developer access the fullName property for dog?

- A. Dog.fullName ()
- B. Dog, get,fullName
- C. Dog, function, fullName
- D. Dog.fullName

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 60

Refer to the code below:

```

01 let country = {
02   get capital() {
03     let city = Number("London");
04
05     return {
06       cityString: city.toString(),
07     }
08   }
09 }

```

Which value can a developer expect when referencing country.capital,cityString?

- A. undefined
- B. 'London'
- C. An error
- D. 'NaN'

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 61

Refer to the code below:

```
<html lang="en">
<table onclick="console.log(Table log);">
<tr id="row1">
<td>Click me!</td>
</tr>
</table>
<script>
function printMessage(event) {
  console.log('Row log');
}
let elem = document.getElementById('row1');
elem.addEventListener('click', printMessage, false);
</script>
</html>
```

Which code change should be made for the console to log only Row log when 'Click me! ' is clicked?

- A. Add `event.stopPropagation();` to `window.onload` event handler.
- B. Add `event.removeEventListener();` to `window.onload` event handler.
- C. Add `event.stopPropagation();` to `printMessage` function.
- D. Add `event.removeEventListener();` to `printMessage` function.

Answer: C ([LEAVE A REPLY](#))

Valid JS-Dev-101 Dumps shared by Actual4test.com for Helping Passing JS-Dev-101 Exam! Actual4test.com now offer the **newest JS-Dev-101 exam dumps**, the Actual4test.com JS-Dev-101 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com JS-Dev-101 dumps with Test Engine here:

https://www.actual4test.com/JS-Dev-101_examcollection.html (149 Q&As Dumps, **30%OFF**

Special Discount: Freepdfdumps)

NEW QUESTION: 62

In which situation should a developer include a try .. catch block around their function call ?

- A. The function might raise a runtime error that needs to be handled.
- B. The function contains scheduled code.
- C. The function has an error that should not be silenced.
- D. The function results in an out of memory issue.

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 63

myArray can have one level, two levels, or more levels.

Which statement flattens myArray when it can be arbitrarily nested?

- A. `myArray.flat(Infinity);`
- B. `myArray.reduce ((prev, curr) => prev.concat(curr) [ ]);`
- C. `[ ] .concat { . . myArray } ;`
- D. `myArray.join (",").split ("",);`

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 64

Refer to the code below:

Let `inArray =[ [ 1, 2 ] , [ 3, 4, 5 ] ];`

Which two statements result in the array `[1, 2, 3, 4, 5]` ?

Choose 2 answers

- A. `[ ]. Concat.apply ([ ], inArray);`
- B. `[ ]. concat ( [ ....inArray ] );`
- C. `[ ]. Concat (... inArray);`
- D. `[ ]. concat.apply(inArray, [ ]);`

Answer: A,C ([LEAVE A REPLY](#))

NEW QUESTION: 65

Refer of the string below:

`Const str = 'sa;esforce';;`

Which two statement result in the word 'Sale'?

Choose 2 answers

- A. `str, substring(1,5) ;`
- B. `str, substr(0,5) ;`
- C. `str, substr(1,5) ;`
- D. `str, substring(0,5) ;`

Answer: B,D ([LEAVE A REPLY](#))

NEW QUESTION: 66

Universal Container(UC) just launched a new landing page, but users complain that the website is slow. A developer found some functions that cause this problem.To verify this, the developer decides to do everything and log the time each of these three suspicious functions consumes.

```
console.time('Performance');
```

```
maybeAHeavyFunction();
```

```
thisCouldTakeTooLong();
```

```
orMaybeThisOne();
```

```
console.endTime('Performance');
```

Which function can the developer use to obtain the time spent by every one of the three functions?

- A. console.timeLog()
- B. console.trace()
- C. console.getTime()
- D. console.timeStamp()

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 67

Refer the following code

```
let array=[1,2,3,4,4,5,4,4];
for(let i=0;i<array.length;i++)
{
    if(array[i]===4){
        array.splice(i,1);
        i--;
    }
}
alert(array);
```

what is the value of array after code executes?

Answer:

See the Answer below in explanation

NEW QUESTION: 68

Consider type coercion, what does the following expression evaluate to?

True + 3 + '100' + null

- A. 104
- B. 4100
- C. '3100null'

D. '4100null'

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 69

Refer to the following code block:

```
01 class Student {
02   constructor(name) {
03     this.name = name;
04   }
05
06   takeTest() {
07     console.log(`${this.name} got 70% on test.`);
08   }
09 }
10
11 class BetterStudent extends Student {
12   constructor(name) {
13     super(name);
14     this.name = 'Better student ' + name;
15   }
16   takeTest() {
17     console.log(`${this.name} got 100% on test.`);
18   }
19 }
20
21 let student = new BetterStudent('Jackie');
```

What is the console output?

- A. > Uncaught Reference Error
- B. > Better student Jackie got 100% on test.
- C. > Jackie got 70% on test.
- D. > Better student Jackie got 70% on test.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 70

Refer to the code below:

```
function changeValue(param) {
  Param =5;
}
```

Let a =10;

Let b =5;

changeValue(b);

Const result = a+ " - "+ b;

What is the value of result when code executes?

- A. 5 -5

B. 10 -10

C. 5 - 10

D. 10 - 5

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 71

Refer to the code below:

```
function foo () {  
  const a =2;  
  function bar() {  
    console.log(a);  
  }  
  return bar;  
}
```

Why does the function bar have access to variable a ?

A. Hoisting

B. Inner function's scope

C. Prototype chain

D. Outer function's scope

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 72

Refer to the following code:

```
01 class Ship {  
02   constructor(size) {  
03     this.size = size;  
04   }  
05 }  
06  
07 class FishingBoat extends Ship {  
08   constructor(size, capacity) {  
09     //Missing code  
10     this.capacity = capacity;  
11   }  
12   displayCapacity() {  
13     console.log('The Boat has a capacity of ${this.capacity} people.');14   }  
15 }  
16  
17 let myBoat = new FishingBoat('medium', 10);  
18 myBoat.displayCapacity();
```



Which statement should be added to line 09 for the code to display. The boat has a capacity of 10 people?

A. ship.size size;

B. this.size = size;

C. super.size = size;

D. super (size);

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 73

A developer has a formatName function that takes two arguments, firstName and lastName and returns a string. They want to schedule the function to run once after five seconds.

What is the correct syntax to schedule this function?

A. setTimeout ('formatName', 5000, 'John', 'Doe');

B. setTimeout(() => { formatName('John', 'Doe') }, 5000);

C. setTimeout (formatName('John', 'Doe'), 5000);

D. setTimeout (formatName(), 5000, 'John', 'BDoe');

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 74

Refer to the code below:

```
let o = {  
  get js() {  
    let city1 = String("st. Louis");  
    let city2 = String(" New York");  
    return {  
      firstCity: city1.toLowerCase(),  
      secondCity: city2.toLowerCase(),  
    }  
  }  
}
```

What value can a developer expect when referencing o.js.secondCity?

A. ' new york '

B. Undefined

C. ' New York '

D. An error

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 75

refer to the exhibit.

```

02 <table onclick="console.log('Table log');">
03   <tr id="row1">
04     <td>Click me!</td>
05   </tr>
06 </table>
07 <script>
08   function printMessage(event) {
09     console.log('Row log');
10     event.stopPropagation();
11   }
12
13   let elem = document.getElementById('row1');
14   elem.addEventListener('click', printMessage, false);
15 </script>
16 </html>

```

Which code change should be done for the console to log the following when 'Click me!' is clicked' > Row log > Table log

- A. Change line 14 to `elem.addEventListener('click', printMessage, true);`
- B. Change line 10 to `event.stopPropagation(false);`
- C. Remove line 10
- D. Remove lines 13 and 14

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 76

A developer implements and calls the following code when an application state change occurs:

```

Const onStateChange = (innerPageState) => {
  window.history.pushState(newPageState, '', null);
}

```

If the back button is clicked after this method is executed, what can a developer expect?

- A. A popstate event is fired with a state property that details the application's last state.
- B. The page is navigated away from and the previous page in the browser's history is loaded.
- C. The page reloads and all Javascript is reinitialized.
- D. A navigate event is fired with a state property that details the previous application state.

Answer: B ([LEAVE A REPLY](#))

Valid JS-Dev-101 Dumps shared by Actual4test.com for Helping Passing JS-Dev-101 Exam! Actual4test.com now offer the **newest JS-Dev-101 exam dumps**, the Actual4test.com JS-Dev-101 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com JS-Dev-101 dumps with Test Engine here:

https://www.actual4test.com/JS-Dev-101_examcollection.html (149 Q&As Dumps, **30%OFF**

Special Discount: Freepdfdumps)

NEW QUESTION: 77

developer uses the code below to format a date.

```
01 const date = new Date(2020, 05, 10);  
02 const dateDisplayOptions = {  
03   year: 'numeric',  
04   month: 'long',  
05   day: 'numeric'  
06 };  
07  
08 const formattedDate = date.toLocaleDateString('en', dateDisplayOptions);
```

After executing, what is the value of formattedDate?

- A. May 10, 2020
- B. October 05, 2020
- C. June 10, 2020
- D. November 05, 2020

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 78

Cloud Kicks has a class to represent items for sale in an online store, as shown below:

```
Class Item{  
  constructor (name, price){  
    this.name = name;  
    this.price = price;  
  }  
  formattedPrice(){  
    return 's' + String(this.price);}}}
```

A new business requirement comes in that requests a ClothingItem class that should have all of the properties and methods of the Item class but will also have properties that are specific to clothes.

Which line of code properly declares the clothingItem class such that it inherits from Item?

- A. Class ClothingItem implements Item{
- B. Class ClothingItem {
- C. Class ClothingItem super Item {
- D. Class ClothingItem extends Item {

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 79

A developer has the function, shown below, that is called when a page loads.

```
function onload() {  
  console.log("Page has loaded!");  
}
```

Where can the developer see the log statement after loading the page in the browser?

- A. On the webpage.
- B. Terminal running the web server.
- C. Browser performance tools
- D. Browser javaScript console

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 80

A developer is required to write a function that calculates the sum of elements in an array but is getting undefined every time the code is executed. The developer needs to find what is missing in the code below.

```
Const sumFunction = arr => {  
  Return arr.reduce((result, current) => {  
    //  
    Result += current;  
    //  
  }, 10);  
};
```

Which option makes the code work as expected?

- A. Replace line 04 with result = result +current;
- B. Replace line 03 with if(arr.length == 0) (return 0;)
- C. Replace line02 with return arr.map((result, current) => (
- D. Replace line 05 with return result;

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 81

A developer is working on an ecommerce website where the delivery date is dynamically calculated based on the current day. The code line below is responsible for this calculation.

```
Const deliveryDate = new Date ();
```

Due to changes in the business requirements, the delivery date must now be today's date + 9 days.

Which code meets thisnew requirement?

- A. deliveryDate.setDate((new Date ()).getDate () +9);
- B. deliveryDate.date = new Date(+9) ;
- C. deliveryDate.date = Date.current () + 9;

D. `deliveryDate.setDate( Date.current () + 9);`

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 82

Refer to the following object:

```
const cat = {  
  firstName: 'Fancy',  
  lastName: ' Whiskers',  
  Get fullName() {  
    return this.firstName + ' ' + this.lastName;  
  }  
};
```

How can a developer access the `fullName` property for `cat`?

- A. `cat.get.fullName`
- B. `cat.fullName`
- C. `cat.fullName()`
- D. `cat.function.fullName()`

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 83

Refer to the code below:

```
const event = new CustomEvent(  
  //Missing Code  
);  
obj.dispatchEvent(event);
```

A developer needs to dispatch a custom event called `update` to send information about `recordId`.

Which two options could a developer insert at the placeholder in line 02 to achieve this?

Choose 2 answers

- A. `'Update' , (recordId : '123abc' )`
- B. `'Update' , '123abc'`
- C. `'Update' , {Details : {recordId : '123abc'}}`
- D. `{ type : 'update', recordId : '123abc' }`

Answer: A,C ([LEAVE A REPLY](#))

NEW QUESTION: 84

A developer has an `ErrorHandler` module that contains multiple functions.

What kind of export be leverages so that multiple functions can be used?

- A. Named
- B. Default
- C. All
- D. Multi

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 85

developer is trying to convince management that their team will benefit from using Node.js for a backend server that they are going to create. The server will be a web server that handles API requests from a website that the team has already built using HTML, CSS, and JavaScript.

Which three benefits of Node.js can the developer use to persuade their manager?

Choose 3 answers:

- A.** Uses non-blocking functionality for performant request handling .
- B.** Installs with its own package manager to install and manage third-party libraries.
- C.** Ensures stability with one major release every few years.
- D.** Executes server-side JavaScript code to avoid learning a new language.
- E.** Performs a static analysis on code before execution to look for runtime errors.

Answer: A,B,E ([LEAVE A REPLY](#))

NEW QUESTION: 86

A developer receives a comment from the Tech Lead that the code given below has error:

```
const monthName = 'July';  
const year = 2019;  
if(year === 2019) {  
  monthName = 'June';  
}
```

Which line edit should be made to make this code run?

- A.** 02 const year = 2020;
- B.** 02 let year = 2019;
- C.** 03 if (year == 2019) {
- D.** 01 let monthName = 'July';

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 87

Given the code below:

```
const delay = async delay => {  
  return new Promise((resolve, reject) => {  
    console.log(1);  
    setTimeout(resolve, delay);  
  });  
};  
  
const callDelay = async () => {  
  console.log(2);  
  const yup = await delay(1000);  
  console.log(3);  
};
```

```
}  
console.log(4);  
callDelay();  
console.log(5);  
What is logged to the console?
```

Answer:

4 2 1 5 3

NEW QUESTION: 88

Refer to the code below:



```
01 let greeting = 'Goodbye';  
02 let salutation = 'Hello, hello, he  
03 try {  
04   greeting = 'Hello';  
05   decodeURI('???'); // throws error  
06   salutation = 'Goodbye';  
07 } catch(err) {  
08   salutation = 'I say hello';  
09 } finally {  
10   salutation = 'Hello, Hello';  
11 }
```

Line 05 causes an error. What are the values of greeting and salutation once code completes?

- A. Greeting is Goodbye and salutation is Hello, Hello.
- B. Greeting is Goodbye and salutation is I say Hello.
- C. Greeting is Hello and salutation is I say hello.
- D. Greeting is Hello and salutation is Hello, Hello.

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 89

Which code statement correctly retrieves and returns an object from localStorage?

- A. const retrieveFromLocalStorage = (storageKey) => {return window.localStorage[storageKey];}
- B. const retrieveFromLocalStorage = (storageKey) => {return window.localStorage.getItem(storageKey);}
- C. const retrieveFromLocalStorage = (storageKey) => {return JSON.parse(window.localStorage.getItem(storageKey));}
- D. const retrieveFromLocalStorage = () => {return JSON.stringify(window.localStorage.getItem(storageKey));}

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 90

Given the following code:

```
Let x = null;  
console.log(typeof x);  
What is the output of the line 02?
```

- A. "Object"
- B. "X"
- C. "Null"
- D. "undefined"

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 91

Universal Containers recently launched its new landing page to host a crowd-funding campaign. The page uses an external library to display some third-party ads. Once the page is fully loaded, it creates more than 50 new HTML items placed randomly inside the DOM, like the one in the code below:

```
<!-- This is an ad -->
<div class="ad-library-item ad-hidden" onload="myfunction()">
  
</div>
```

All the elements include the same ad-library-item class. They are hidden by default, and they are randomly displayed while the user navigates through the page.

- A. Use the browser console to execute a script that prevents the load event to be fired.
- B. Use the DOM inspector to remove all the elements containing the class ad-library-item.
- C. Use the DOM inspector to prevent the load event to be fired.
- D. Use the browser to execute a script that removes all the element containing the class ad-library-item.

Answer: D ([LEAVE A REPLY](#))

Valid JS-Dev-101 Dumps shared by Actual4test.com for Helping Passing JS-Dev-101 Exam! Actual4test.com now offer the **newest JS-Dev-101 exam dumps**, the Actual4test.com JS-Dev-101 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com JS-Dev-101 dumps with Test Engine here:

https://www.actual4test.com/JS-Dev-101_examcollection.html (149 Q&As Dumps, **30%OFF**

Special Discount: **Freepdfdumps**)

NEW QUESTION: 92

A developer initiates a server with the file server.js and adds dependencies in the source codes package.json that are required to run the server.

Which command should the developer run to start the server locally?

- A. npm start server.js
- B. start server.js
- C. node start
- D. npm start

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 93

A developer wants to use a module called DataPrettyPrint. This module exports one default function called printDate ().

How can a developer import and use the printDate() function?

- `import printDate from '/path/DatePrettyPrint.js';`
- A. `DatePrettyPrint.printDate();`
- `import DatePrettyPrint() from '/path/DatePrettyPrint.js';`
- B. `printDate();`
- `import printDate from '/path/DatePrettyPrint.js';`
- C. `printDate();`
- `import DatePrettyPrint from '/path/DatePrettyPrint.js';`
- D. `DatePrettyPrint.printDate();`

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 94

Refer to the following code:

```
<html lang="en">
<body>
<div onclick = "console.log('Outer message') ;">
<button id ="myButton">Click me</button>
</div>
</body>
<script>
function displayMessage(ev) {
ev.stopPropagation();
console.log('Inner message. ');
}
const elem = document.getElementById('myButton');
elem.addEventListener('click' , displayMessage);
</script>
</html>
```

What will the console show when the button is clicked?

- A. Inner messageOuter message
- B. Outer messageInner message
- C. Inner message
- D. Outer message

Answer: ([SHOW ANSWER](#)**)**

NEW QUESTION: 95

A class was written to represent items for purchase in an online store, and a second class representing items that are on sale at a discounted price. The constructor sets the name to the first value passed in. The pseudocode is below:

```
Class Item {  
  constructor(name, price) {  
    ... // Constructor Implementation  
  }  
}  
  
Class SaleItem extends Item {  
  constructor (name, price, discount) {  
    ...//Constructor Implementation  
  }  
}
```

There is a new requirement for a developer to implement a description method that will return a brief description for Item and SaleItem.

```
let regItem = new Item('Scarf', 55);
```

```
let saleItem = new SaleItem('Shirt' 80, -1);
```

```
Item.prototype.description = function () { return 'This is a ' + this.name;
```

```
console.log(regItem.description()); console.log(saleItem.description());
```

```
SaleItem.prototype.description = function () { return 'This is a discounted ' + this.name; }
```

```
console.log(regItem.description()); console.log(saleItem.description());
```

What is the output when executing the code above ?

- A.** This is a ScarfUncaught TypeError: saleItem.description is not a functionThis is aScarfThis is a discounted Shirt
- B.** This is aScarfUncaught TypeError: saleItem.description is not a functionThis is a ShirtThis is a did counted Shirt
- C.** This is a ScarfThis is a ShirtThis is a discounted ScarfThis is a discounted Shirt
- D.** This is a ScarfThis is a ShirtThis is a ScarfThis is a discounted Shirt

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 96

A developer writes the code below to calculate the factorial of a given number function

```
sum(number){ return number * sum(number-1);
```

```
}
```

```
sum(3);
```

what is the result of executing the code.

- A.** 0
- B.** 6
- C.** Error
- D.** -Infinity

Answer: C ([LEAVE A REPLY](#))

Valid JS-Dev-101 Dumps shared by Actual4test.com for Helping Passing JS-Dev-101 Exam! Actual4test.com now offer the **newest JS-Dev-101 exam dumps**, the Actual4test.com JS-Dev-101 exam **questions have been updated** and **answers have been corrected** get the **newest** Actual4test.com JS-Dev-101 dumps with Test Engine here:
https://www.actual4test.com/JS-Dev-101_examcollection.html (**149** Q&As Dumps, **30%OFF**
Special Discount: **Freepdfdumps**)